SRL «EMCC TRADING»

moldova@emcc.pro

str. Alecu Russo 24, ap. 130 MD-2044, mun. Chişinău Republica Moldova IDNO: 1023605001088 www.emcc.pro

Ref. № 024.1.MD/2025 dated 10.11.2025

Commercial offer for tender No. 21502296

"Administrația Națională a Drumurilor" S.A. for the attention of Mr. Cristian Dragalin

Dear Mr. Dragalin,

We thank you for your kind inquiry and we are pleased to present the attached offer for the products and services you are interested in.

Please feel free to contact us if you require further information or clarification.

| # | Product code | Description / Descriere | Q- ty | Unit NET- price, MDL | Total NET- price, MDL |
|----------------|-----------------|---|----------|-------------------------|--------------------------|
| 1.1 Lot nr. | nge 402 C | Rectangular gage block set made of ceramic 32 Pieces: - 1,005 mm - pc; - 1,01 1,09 - 9 pcs; - 1,11,9 mm - 9 pcs; - 1 9 mm - 9 pcs; - 10 30 mm 3 pcs; - 50 mm - 1 pc. Tolerance class: 1 DIN EN ISO 3650 Supplied complete with wooden case with clear labeling strips, and Mahr calibration certificate Origin: Mahr / Germany | 1 | 47480.0 | 47480.0 |
| ECO13 GTF10 | Senseca (s) | Professional Thermometer with type K thermocouple (NiCr-Ni), -200 +1150 °C A compact, durable, and splash-protected housing (except for the probe connection), combined with fast measurement response and excellent reliability, makes the ECO 130 an ideal tool for professional users. Key Advantages: - High-precision thermocouple compensation for superior measurement reliability - Fast measurement rate — 3 readings per second - Three-line backlit LCD with wide-angle visibility - Min/Max/Hold functions, Auto Power-Off, zero and slope adjustment - Long operating time — over 3000 hours on just two AA batteries Main Specifications: - Measurement range: -651200 °C - Accuracy: ±0.1% of measured value ±1 °C, reference junction ±0.3 °C - Protection class: IP40 - Weight: 125 g, impact-resistant ABS housing Supplied complete with thermocouple, Type K (NiCr-Ni), -200 +1150 °C, 3 mm probe diameter, 1000 mm length, 1 m silicone cable. Origin: SENSECA / Germany | 1 | 7000.0 | 7000.0 |





| (| CONTROLS | BINDER Magdeburger Plufgerdebau GmbH | | ww | w.emcc.pro |
|---|---------------|--|----|------------|------------|
| | | | | | |
| | Product | | Q- | Unit NET- | Total NET- |
| # | code | Description / Descriere | ty | price, MDL | price, MDL |
| 3 | Lot nr. 3 | Universal Motorized Specimen Extruder with adjustable | 1 | 75000.0 | 75000.0 |
| J | 1 1 | piston speed | 1 | 73000.0 | 73000.0 |
| | | The extruder is used to push out specimens from Marshall, | | | |
| | 111 | Proctor/CBR and other moulds. | | | |
| | | The adapters can be easily fit by conforming to the mould | | | |
| | | diameter: 50 mm, 75 mm, 100 mm, 150 mm. | | | |
| | | The extruder is equipped with a hydraulic power pack with a | | | |
| | | safety bypass valve and a stop limit switch for the lower ram | | | |
| | | position. | | | |
| | | The ram lift is controlled by a foot pedal, which frees the | | | |
| | | hands to hold the mould while lifting. The RT-MG-007/HFC model is additionally equipped with a | | | |
| | | frequency converter to control the piston lifting/lowering | | | |
| | | speed. | | | |
| | RT-MG-007/HFC | The extruder supplied complete with an adapter kit for | | | |
| | | specimens 50, 75, 100 and 150 mm. | | | |
| | | Origin: RadialTec / Ukraine | | | |
| 4 | Lot nr. 4 | Wheel Tracker verification kit | 1 | 141500.0 | 141500.0 |
| | | Including: | | | |
| | . 1 | - a high-resolution encoder; | | | |
| | 111118 | - shaped metal specimen conforming to the specification of | | | |
| | 8-4 | AASHTO T324-2019 Section X2 and Figure X1.1; | | | |
| | | 3500 N capacity load cell;digital thermometer with probe; | | | |
| | 78 PV3/KIT | - adapters and spacers; | | | |
| | | - Laptop PC with dedicated software. | | | |
| | | Origin: Controls / Italy | | | |
| 5 | Lot nr. 5 | Test sieves d 300 mm | 1 | 70085.0 | 70085.0 |
| | 1 was leve | Including perforated and woven cloth sieves: | | | |
| | Test Sien | - 63 mm – 1 pc; | | | |
| | | - 45 mm – 1 pc; | | | |
| | | - 40 mm – 1 pc; - 31.5 mm – 1 pc; | | | |
| | 15-D3365/Set | - 22.4 mm – 1 pc; | | | |
| | 15 05505/500 | - 16 mm – 1 pc; | | | |
| | | - 11.2 mm – 1 pc; | | | |
| | | - 8.0 mm − 1 pc; | | | |
| | | - 4 mm – 1 pc; | | | |
| | | - 2 mm – 2 pcs; | | | |
| | | - 1 mm - 2 pcs; | | | |
| | | - 500 μm – 2 pcs; | | | |
| | | - 250 μm – 4 pcs; | | | |
| | | - 125 μm – 4 pcs; - 63 μm – 5 pcs; | | | |
| | | - lid and pan. | | | |
| | | Origin: Controls / Italy | | | |
| 6 | Lot nr. 6 | Test sieves d 200 mm | 1 | 46785.0 | 46785.0 |
| | s was leve | Including perforated and woven cloth sieves: | | | |
| | Test Sievi | - 63 mm – 1 pc; | | | |
| | | - 45 mm – 1 pc; | | | |
| | | - 40 mm – 1 pc; | | | |
| | 45 D2255/5 : | - 31.5 mm – 1 pc; | | | |
| | 15-D2365/Set | - 22.4 mm – 1 pc; | | | |

16 mm - 1 pc;
 11.2 mm - 1 pc;
 8.0 mm - 1 pc;





| # | Product code | Description / Descriere | Q- ty | Unit NET- price, MDL | Total NET- price, MDL |
|---|-----------------|---|------------------|-------------------------|--------------------------|
| | | 4 mm - 1 pc; 2 mm - 2 pcs; 1 mm - 2 pcs; 250 μm - 2 pcs; 200 μm - 4 pcs; 180 μm - 4 pcs; 63 μm - 5 pcs; lid and pan. Origin: Controls / Italy | | | |
| | | Total NET-p Pac | rice : king : | EUR EUR | 387850.0 Included |
| | | Deliv VAT (20 | very : | EUR EUR | Included 77570.0 |

Delivery terms and conditions:

Delivery : DDP Chisinau (Incoterms 2020)Delivery time : before December 31, 2025

Best regards,

Sales Department