



Product Data Sheet Olympic

May, 2023

Type of flooring	EN ISO 26986	Expanded (cushioned) polyvinyl chloride floor covering	
Class of use	ISO 10874 (EN 685)		
CE certification	EN 14041:2004/AC:2006	2701-0080-DoP-2021-11	
TECHNICAL CHARACTERISTICS AND PERFORMANCES			
 ISO 24346 (EN 428) Total thickness	2,70 mm	 ISO 24341 (EN 426) Roll length Roll width	35m (15-35) 33m (15-33) 2,5; 3; 3,5m; 2; 4m
 ISO 24340 (EN 429) Wear layer thickness	0,15 mm	 ISO 717/2 Impact sound absorption	19 dB
 ISO 23997 (EN 430) Weight per m ²	1,700 kg/m ²	 ISO 24343-1 (EN 433) Residual indentation	≤ 0,35 mm
 ISO 105 B02 Method 3 Light fastness	≥ 6	 Underfloor heating Suitable provided that the surface of the subfloor does not exceed 27°C	
 ISO 23999 (EN 434) Dimensional stability	Requirement by standard: < 0,4 % Tarkett result: ≤ 10,011 %	 EN 13893 Slip resistance	
 EN 13501-1 Fire classification	Bfl-s1	EN 12524 Thermal resistance	0,03 - 0,04m ² /kW
Wear layer binder content ISO 11638 Type I			



2701-0080-DoP-2021-11



This product is 100% recyclable

ISO 9001
ISO 14001
ISO 45001
ISO 50001
BUREAU VERITAS
Certification

