



42250 SELÇUKLU/KONYA

TECHNICAL DESCRIPTION

Carousel

Carousel - will be intended for children from 3 years old The construction must be made of a metal frame from a pipe with a cross section of 34 mm, which rotates on a bearing shaft. The seats with the floor of the carousel are made of double-walled LLDPE polyethylene by rotomolding technology. The carousel will be mounted on a reinforced concrete foundation.

Materials: Steel, plastic, LLDPE.

The foundation of the construction will have dimensions of Lxlxh=400x400x700 mm.

Installation requirements: To ensure safe and reliable operation, all supports are to be immersed in the ground (ground) to 0.70m to increase rigidity, then following the concrete process (concrete BC 300). The installation of the elements must exclude the possibility of disassembling them without the use of special purpose tools.

Technical characteristics.

General dimensions in the installed form of the construction, diameter – 1500 mm, height – 670 mm.

The foundation of the construction will have dimensions of Lxlxh=400x400x500mm.

Installation requirements: To ensure safe and reliable operation, all supports are to be immersed in the ground (ground) to 0.50m to increase rigidity, then following the concrete process (concrete BC 300).the installation of the elements must exclude the possibility of their disassembly without the use of special purpose tools.



42250 SELÇUKLU/KONYA



