



## PVC infusion tubes for syringes pumps

PVC infusion tubes acc. to ISO 8536 / DIN 58362-SL-P

- Luer-Lock and Luer fitting; with protection cap
- compatible for all equipments with authorization of standard infusion tubes acc. to DIN/ISO (e.g. Braun Perfusor)
- leakage tested, pressure of 500 kPa (5 bar)
- Sterile R (Gamma radiation)
- sterile EO (Ethylene oxide)



				<b>Art.-No.</b>	<b>kVE / VE</b>
	1,5 x 2,6	70 cm	transparent	50070	100 / 1000
<b>sterile EO (Ethylenoxid)</b>	<b>1,5 x 2,6</b>	<b>150 cm</b>	<b>transparent</b>	<b>50150</b>	100 / 1000
	1,5 x 2,6	180 cm	transparent	50180	100 / 1000
	1,5 x 2,6	200 cm	transparent	50200	100 / 1000
	1,5 x 2,5	300 cm	transparent	50300	100 / 1000
<b>for light sensitive pharmaceuticals</b>					
	1,5 x 2,6	150 cm	amber	50152	100 / 1000
sterile EO (Ethylenoxid)	1,5 x 2,6	150 cm	black	50151	100 / 1000
sterile EO (Ethylenoxid)	1,5 x 2,6	200 cm	black	50201	100 / 1000