



Unitec-240

65% POLYESTER / 35% COTTON

240 GSM / TWILL 2/1



Fabric name	Unitec-240
Fabric weight	240 ± 5 gsm
Composition	65% Polyester, 35% Cotton
Full width	150 ± 2 cm
Weave	twill 2/1
Finishes	—
Area of use	industrial workwear jackets, trousers and coveralls
Washing instruction	

Physical properties*

		warp	weft
1	Tensile strength, N	ISO 13934-1:2013	1400
2	Tearing strength, N	ISO 13937-3:2000	56
3	Dimensional Stability To Washing, max.	ISO 6330:2000	3.0%
4	Abrasion Resistance	ISO 12947-2:2002	> 30 000
5	Pilling Resistance (after 1000 rev.)	ISO 12945-2:2000	4
6	Colour Fastness To Washing (cotton+polyester) 60°C, min.	ISO 105-C06:2010	
	Colour change	ISO 105-C06:2010	4-5
	Colour staining	ISO 105-C06:2010	4-5
7	Colour Fastness To Perspiration, min.	ISO 105-E04:2013	
	Colour change		4-5
	Colour staining		4-5
8	Colour Fastness To Rubbing, min.	ISO 105-X12:2001	
	Dry		4-5
	Wet		3
9	Colour Fastness To Light	ISO 105-B02:2013	4

* The values shown are indicative and may vary slightly from batch to batch.

www.xmtextiles.com

XM TEXTILES EUROPE

Dariaus ir Gireno st. 42A, Room 509
Vilnius, LT-02189, Lithuania
Tel. +370 52 078 703
info@xmtextiles.com

XM TEXTILES ROMANIA

Sos.Tamasi 20, Hala 6B, Parter,
Buftea, 070000, Ilfov, Romania
Tel. +40 31 630 3639
info@xmtextiles.com

XM TEXTILES ITALIA SRL

Via dei Notai, Blocco 23, Centergross,
40050 Funo di Argelato (BO), Bologna, Italy
Tel. +39 051 952 8202
info@xmtextiles.com

SHANGHAI XM GROUP LTD.
Room 2402-2403 Zhongyi International
Commercial Plaza 1833 Zhongshan North
Road
Shanghai 200061
China

TESTEX AG, Swiss Textile Testing Institute
Gotthardstrasse 61
8002 Zurich
Switzerland

OEKO
TEX®

Certificate

OEKO-TEX® STANDARD 100

SHANGHAI XM GROUP LTD.

is granted the OEKO-TEX® STANDARD 100 certification
and the right to use the trademark.

SCOPE

Woven fabrics made of 100% CO, CO/PES, CO/CF, CO/PES/CF, CO/PA/CF (CF with anti-static function), piece-dyed (with vat and disperse dyestuffs) (partly finished with flame retardant products accepted by OEKO-TEX®) or with water, soil or oil repellent finishing; woven fabric made of 100% PES, 100% PA, PES/EL, white, piece-dyed (with disperse and acid dyestuffs) and finished [only 100% PES or 100% PA woven fabric with or without transparent PU coating (windproof) or water repellent (resistance)], partly 100% polyester woven fabric laminated with ... [Please scan QR code for full scope]

PRODUCT CLASS

II (products with direct contact to skin) - Annex 4



This certificate BEWO 084394 is valid until
15.08.2026.

SUPPORTING DOCUMENTS

- ✓ Test report : BJ015 266840.1
- ✓ Declaration of conformity in accordance with EN ISO 17050-1 as required by OEKO-TEX®
- ✓ OEKO-TEX® Terms of Use (ToU)

A handwritten signature in blue ink, appearing to read 'Matz Bachmann', is placed over a horizontal line.

Matz Bachmann
Managing Director

A handwritten signature in blue ink, appearing to read 'Janine Kuchelmeister', is placed over a horizontal line.

Janine Kuchelmeister
Ecology Team Leader

Further compliance information (REACH, SVHC, POP, GB18401 etc.) can be found on oeko-tex.com/en/faq.

The certificate is based on the test methods and requirements of the OEKO-TEX® STANDARD 100 that were in force at the time of evaluation.

Zurich, 2025-07-24

