

DoP - DECLARATION of PERFORMANCE
Construction Products Regulation nº305/2011

CPR-ES2-0004

Manufacturer	TECNOPOL SISTEMAS, S.L.
Address	Finlàndia, 33 08520 Les Franqueses del Vallès · Barcelona · Spain
Contact	t +34 935 682 111 · f +34 935 68 0211 · www.tecnopolgroup.com · info@tecnopol.es
Unique identification code of the product-type	DESMOPOL
Intended uses	liquid applied roof waterproofing kit, based on pure polyurethane
Harmonized standards	ETAG 005
Systems of AVCP	System 3
Notified bodies	The notified body Instituto de Ciencias de la Construcción Eduardo Torroja, nº1219, carried out the assessment of the performance according to the ETAG 005
Revision date	22-01-2019

DECLARED PERFORMANCES

ETA 10/0121 (10/10/2016) | liquid applied roof waterproofing kit, based on pure polyurethane

Characteristics of the system

Minimum polyurea membrane thickness	1,2 mm.
Resistance to water vapor	$\mu = 2.500$
Resistance to wind loads	Pass ($>50\text{kPa}$)
Resistance to plant roots	Resistant

Performance level according to the intended use

External fire performance	Broof (t1) roof slope $<20^\circ$, and support A1-A2 and Broof (t4)
Fire reaction	NPD
Expected working life	W3
Climatic zone of use	S(severe)
User loads	Concrete:P4: TH2 // P3: TH4 PU: P1:TH2
Roof slope	S1 ~S4 ($\geq 0^\circ$)
Minimum surface temperatures	TL3 (-20°C)
Maximum surface temperatures	TH4-TH2

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


David Pont Sanchez
Tecnopol Technical Manager

DoP in Pdf format available in the Tecnopol website.