

PLT CARGO S.R.L. mun. Chisinau, MD-4839

Stauceni, str. Ciorescu 1, of. 314

Attn: Eladii Sergiu

Our reference Dir.phone E-mail

: Thor Arve Øveraasen : +47 952 77 957

: thor.arve.overaasen@overaasen.no Date

: Gjøvik, 30.04.25

## Quotation, Øveraasen snow removal equipment

We hereby have the pleasure to present our offer:

- 1+1 pc. Øveraasen RS 400 Performance Line Euro-Airport standard runway sweepers with EP 9 snow ploughs and Mercedes Benz Arocs 2243 AS 4x4 trucks

Including:

- Central lubrication system
- Hydraulic oil tank heating
- Engine heater 220 volt
- Battery charger 220 volt
- 1 pc. spare wheel main axle
- 1 pc. spare castor wheel, complete
- 2 pcs. spare support wheels for plough, complete
- 2 sets of brushes
- 2 psc. adjustable support legs for parking
- Service Tool w/PC
- Reinforced spring, front axle
- Adjustable support legs for parking

Price, each : EUR 555.500,-

Technical data : RS 400

> - Diesel engine : MTU 6R1100

- Power output : 320 kW at 1 700 rpm - Emission standard : EU Stage V / T4final

: 2 585 mm - Width, transport : 12 600 mm - Length sweeper - Length with truck : 17 940 mm - Length with truck and plough : 20 330 mm

- Height : 3 580 mm : 14 240 kg - Weight

: 5 500 mm at 32° - Practical clearing width

- Clearing speed, max : 65 km/h - Capacity, max : 357 500 m<sup>2</sup>/h - Brush core length : 6 240 mm



- Brush diameter : 1 170 mm - Brush cassettes : Steel or poly

- Number of cassette rows : 20

- Brush speed : 0 – 720 rpm - Air blower capacity : 40 000 m³/h - Blowing speed at air nozzle : 150 m/s

- Brush pump : Danfoss Power Solutions

- Brush motor : RHL

- Air blower pump- Air blower motor: Danfoss Power Solutions

- Hydraulic tank
- Diesel tank
- Rear axle
- Electric system
: 150 I
: 1 000 I
: Steerable
: 24 Volt

- Batteries : 2 x 12 Volt / 180 Ah - Paint : Frame: RAL 7024

Hood, nozzle: RAL 1004

## EP 9 snow plough

- Clearing capacity : 442 650 m²/h
- Clearing width : 6 810 mm
- Max width : 8 690 mm
- Number of elements : 9 pcs.
- Element width : 925 mm
- Element height : 1 250 mm
- Clearing angle : 35°

Clearing angle
Weight incl. lifting device
Retract height, element
Parking system
Lifting device
35°
2 030 kg
app. 120 mm
Foldable wings
DuoLift parallelogram

- Support wheels : 2 pcs.

## Mercedes Benz truck

- Model : Arocs 2243 AS 4x4

- Emission standard : Euro 6
- Wheel base : 3 600 mm
- Total weight : 22 000 kg
- Engine power : 315 kW
- Steering : LHD
- Engine noice cover : Included
- Air filter with cyclone : Included

## Optional equipment RS 400

: - Magnet beam (pneumatic)	: EUR	22.141,-
- Rear view camera	: EUR	3.390,-
- Service tool w/PC	: EUR	1.859,-
- QR codes	: EUR	2.288,-
- Fleet Cloud, hardware and installatio	n : EUR	6.396,-
- Fleet Cloud, Basic 12 months	: EUR	1.216,-



Optional

equipment EP 9 : - Slush blade

7030,-: EUR

- Transport trolley with wheels

: EUR 1.892,-

- Snow stoppers, 1 pair L+R

: EUR 11.044,-

- Steel cutting edge

: EUR 1.185,-

Terms of

payment

: 33,33 % at the time of order.

33,33 % at before shipment.

33,33 % 10 days after delivery to Chisinau Airport.

Terms of

delivery

: FCA Gjøvik, Norway.

Shipment from

factory

: 16-20 weeks after receipt of purchase order.

Validity of offer : This offer is valid until 31st May 2025.

Warranty

: 24 months from date of delivery if defects are found in material or workmanship. Øveraasen is not responsible for failures resulting from any use or installation which we judge improper, abuse neglect and/or improper repair and user's unreasonable delay in making the machine available after being notified of a potential

product problem.

**Training** 

: According to requirements.

Documentation: 1 user manual on paper in English and 1 complete set of

documentation on USB stick in English will be supplied free of

charge.

We do hope you find our quotation interesting and are looking forward to hearing from you.

With best regards, **ØVERAASEN AS** 

Thor Arve Øveraasen Managing Director/CEO