

Certificate of constancy of performance **0620-CPR-45875/07**



Issued 2022-02-01 Replaces 0620-CPD-45875/06

First issued 2008-11-01 Page 1 of 2

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

High-pressure decorative laminates (HPL)

whereby the scope of construction product(s) is listed on page 2 of this certificate placed on the market under the name or trademark of

Gentas A.S.

and produced in the manufacturing plant

GENTAŞ GENEL METAL SANAYI VE TICARET A.Ş.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 438-7:2005

under system 1 for the performances set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.

This certificate was first issued on 1 November 2008 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Ron Scheepers
Managing director

Manufacturer

06160 SITELER-ANKARA

Tel. 312-3530206

www.gentas.com.tr

gentas@gentas.com.tr

Gentas A.S. Dolanti sok 21

Turkey

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273 Postbus 70 2280 AB RIJSWIJK The Netherlands Tel. +31 88 998 44 00

Fax +31 88 998 44 20

NL.Kiwa.info@Kiwa.com

www.kiwa.nl

Notified Body No. 0620



Manufacturing plant

GENTAŞ GENEL METAL SANAYI VE TICARET A.Ş. Serpek Mevkii 14841 Mengen/BOLU TURKEY

Tel. +90.374 356 18 78 gentas@gentas.com.tr www.gentas.com.tr page 2 of 2

High-pressure decorative laminates (HPL)

SCOPE

Interior and exterior grade Compact laminates with the reaction to fire classification **B-s1, d0**, with field of direct application:

- · Compact high-pressure decorative laminate (HPL) panels for internal and external wall and ceiling finishes and
- Compact high-pressure decorative laminate (HPL) panels for internal and external suspended ceilings.

Interior grade

G-Fire : ≥ 6 mm, CGF - Interior Compact General-purpose Flame-retardant grade
 G-BIO : ≥ 10 mm, CGF - Interior Compact General-purpose Flame-retardant grade
 ZERO PST : ≥ 10 mm, CGF - Interior Compact General-purpose Flame-retardant grade

Exterior grade

G-Ext : ≥ 6 mm, EDF - Exterior Severe-use Flame-retardant grade
 G-Com UV⁺ : ≥ 6 mm, EDF - Exterior Severe-use Flame-retardant grade