## **Quick Card**

# Freehand 3D for Gynecology

ACUSON Sequoia Ultrasound System 3.5 (VB30)

siemens-healthineers.com/sequoia





## **Getting Started**

The 3D volume data set is a series of 2D images gathered manually over a timed acquisition. Measurements can not be performed on the MPR's.

• The 5C1, 9C2, 9EC4, 10EV3, 10L4, 11M2, 11M3, 15L4, 18H6, 18L6, and HLX transducers are available to perform acquisitions of Freehand 3D volume data sets

## Step 1

- Select the appropriate curved transducer for scanning
- Press 3D/4D control
- The set up Touch Screen corresponding to the transducer selected will be displayed, showing the first scan direction and Rocked, highlighted in orange






## Step 2

- If desired, place the Volume of Interest (VOI) to include the anatomy desired. The VOI can be curved by selecting the Curve option on the Trackball Set key
- The VOI box may be deactivated by selecting the VOI key on the Touch Screen. When disabled, the entire field of view will be acquired in the volume. The VOI can also be selected after the acquisition is complete.

#### 3D

- Adjust Touch Screen parameters
- Find the midline uterus
- Angle the probe towards the right adnexa (notch up) or inferior to the cervix (notch towards to patient's right)
- Press Update above the Trackball or Start and perform a single sweep in the short axis with a paint brush motion
- Sweep right to left or inferior to superior
- Follow the timing of the progress bar









## Step 3

3D

• Press Image to store the volume





### **Render Modes**

There are four render modes available that can be selected on the Touch Screen before (page 1) or after acquisition (page 2):

- **Surface:** Smooths the image contours, creating a soft sculptured appearance for highlighting surface features of soft tissue
- Vascular (Minimum Intensity Projection/Min IP):
  Best for visualizing hypo-echoic lesions and vascular structures
- Skeletal (Maximum Intensity Projection/Max IP): Best for intrauterine devices and bony structures
- Light Source: Helps increase depth perception, reveals surface details, provides an element of texture, and can provide a deeper understanding of relational anatomy. The adjustable light source direction is automatically activated in a 1:1 layout, but may be activated/deactivated in any layout by selecting the Light key on page 1 of the Touch Screen

Use the Trackball to adjust the direction of the light.





## **FlexPlane**

The FlexPlane tool allows the user to obtain and visualize anatomy of any shape along any plane. This is especially useful when imaging complex or irregularly shaped structures.

The user can choose from:


- Line A straight line in any direction
- Trace A freehand line traced in any direction
- **Spline** An open spline controlled by selecting the Set key along the path of the spline

Once the desired option is chosen:

- Press either **Set** control to begin the line
- Press either Set key again to end the Line/Trace tools or to change the direction of the Spline tool (double-click either Set control to end the Spline)
- To redraw the slice, press the Update control

Use the rotary Soft Keys to adjust the volume thickness as well as line or slice orientation.

## FlexPlane




## **MPR & VR Orientation**

Adjust the Multiplanar Renderings (MPR) and the volume using the rotation tools on the Control Panel.

- Select the desired quadrant from the Touch Screen
- The MPR slicing function is manipulated using the 3D/4D control
- The X axis is manipulated using the M-mode control
- The Y axis is manipulated using the PW Doppler control
- The Z axis is manipulated using the Color Doppler control

Use the rotation tools on the Touch Screen to quickly rotate the volume rendering by set degrees.



## Multislice


The Multislice tab contains options for viewing multiple slices of the selected MPR plane at the same time. It is often referred to as a CT or MRI view.

• Select the desired plane using the A, B, and C keys

• Select the desired layout from the Touch Screen

Use the rotary soft keys to adjust the number of slices, distance between slices, and the position of the slices









Slices	Distance	Position of Slices
5	2 mm	0 mm

## **Editing**

The editing tab contains options for removing unnecessary structures.

- Select the desired tool from the Touch Screen
- Using the Trackball and **Set** keys to delineate the area for removal
- Place the scissor icon in the area to be removed and press the **Set** key to finalize
- Edits may be reversed using the Touch Screen options








### **Animation**

- The volume can be animated to rotate up to 360 degrees
- Located under the Editing tab
- Curved arrows will continuously rotate the volume up to 360 degrees after using the Trackball to select the First image to start with and the Last image to end with
- Double-straight arrows will animate the volume to rotate from the First selected image to the Last selected image in one direction; then go back in the opposite direction from the Last to the First and repeat
- Select the play icon to start animation
- X, Y, and Z controls can be used on the volume before animation
- Speed can be adjusted using the Rotary Control as Slow, Medium, and Fast



## **Additional Optimization – Acquisition**

## Quality

 Adjusts the resolution and sweep speed between Low, Mid, and High

## Additional Optimization – VR

## Threshold

 Decreasing the threshold removes low-level echoes, while increasing the threshold adds low-level echoes

## Opacity

• Adjusts the transparency of the voxel

#### Smooth

 Averages the edges of the voxels with adjacent voxels to smooth the volume image appearance

### **Brightness**

• Changes the voxel saturation

### Contrast

 Raises or lowers the percentage of contrast to enhance differences in tissue

#### **Tint**

• Applies assigned color shades to the gray scale

## **Additional Optimization – MPR**

## **Dynamic Range**

• Decreasing the threshold removes low-level echoes, while increasing the threshold adds low-level echoes

#### Map


• Adjusts the transparency of the voxel

#### Tint

• Applies assigned color shades to the gray scale

## **Review**

• Select **Review** from the Touch Screen with the pointer, select the image for review



- Select the **3D/4D** tab on the Touch Screen to activate the volume manipulation tools if desired
- Any additional images stored while the volume is active in the 3D/4D tab will be stored as volumes; additional images stored while in the Review tab will be stored as still images



For the proper use of the software or hardware, please always use the Operator Manual or Instructions for Use (hereinafter collectively "Operator Manual") issued by Siemens Healthineers. This material is to be used as training material only and shall by no means substitute the Operator Manual. Any material used in this training will not be updated on a regular basis and does not necessarily reflect the latest version of the software and hardware available at the time of the training. The Operator Manual shall be used as your main reference, in particular for relevant safety information like warnings and cautions.

Note: Some functions shown in this material are optional and might not be part of your system.

Certain products, product related claims or functionalities described in the material (hereinafter collectively "Functionality") may not (yet) be commercially available in your country. Due to regulatory requirements, the future availability of said functionalities in any specific country is not guaranteed. Please contact your local Siemens Healthineers sales representative for the most current information. The reproduction, transmission or distribution of this training or its contents is not permitted without express written authority. Offenders will be liable for damages.

All names and data of patients, parameters and configuration dependent designations are fictional and examples only. All rights, including rights created by patent grant or registration of a utility model or design, are reserved.

ACUSON Sequoia is a trademark of Siemens Medical Solutions USA, Inc.

Siemens Healthineers Ultrasound owns the rights to all images.

At Siemens Healthineers, we pioneer breakthroughs in healthcare. For everyone. Everywhere. Sustainably. As a leader in medical technology, we want to advance a world in which breakthroughs in healthcare create new possibilities with a minimal impact on our planet. By consistently bringing innovations to the market, we enable healthcare professionals to innovate personalized care, achieve operational excellence, and transform the system of care.

Our portfolio, spanning in vitro and in vivo diagnostics to imageguided therapy and cancer care, is crucial for clinical decisionmaking and treatment pathways. With the unique combination of our strengths in patient twinning<sup>1</sup>, precision therapy, as well as digital, data, and artificial intelligence (AI), we are well positioned to take on the greatest challenges in healthcare. We will continue to build on these strengths to help overcome the world's most threatening diseases, enable efficient operations, and expand access to care.

We are a team of more than 71,000 Healthineers in over 70 countries passionately pushing the boundaries of what is possible in healthcare to help improve the lives of people around the world.

<sup>1</sup> Personalization of diagnosis, therapy selection and monitoring, aftercare, and managing health.

### Siemens Healthineers Headquarters

Siemens Healthineers AG Siemensstr. 3 91301 Forchheim, Germany Phone: +49 9191 18-0 siemens-healthineers.com

#### Manufacturer

Siemens Medical Solutions USA, Inc. Ultrasound 22010 S.E. 51st Street Issaquah, WA 98029, USA Phone: 1-888-826-9702

siemens-healthineers.com/ultrasound