



— Since 1978 —

Interactive Flat Panel

(H7Q Specification)

65" / 75" / 86" / 100"



➤ **Eight machines in one**

It integrates the functions of projectors, screens, electronic whiteboards, televisions, computers, tablets, set-top boxes, and audio devices to realize modern smart office, improve corporate image, improve corporate office efficiency,

➤ **4K Anti-glare UHD display**

The detailed picture is vivid and lifelike, and it still can be presented clearly even in strong light and dark light environment.

➤ **Original handwriting**

Infrared touch technology, ±1MM high-precision pen control, could meets the requirements of efficient meeting writing.

➤ **Annotate, scan code, share and save**

The comment mode can be turned on on any interface, and the key points of the meeting can be recorded at any time, and the written content can be saved and shared with the QR code.

➤ **8-megapixel camera**

Excellent high-definition picture quality, multi-party audio and video interaction shows the images of the two places, making you feel like you are on the scene.

➤ **6 built-in array microphones**

The pickup distance is up to 8M, 2.1-channel stereo, bringing clear and stable video effects.

➤ **5G wireless screen mirroring**

Computers, mobile phones, and tablets can easily cast screen content wirelessly, and support split-screen display on four devices at the same time, so the comparison is clear at a glance.

➤ **Teleconferencing**

Open face-to-face meetings at any time to reduce travel.

➤ **VIP reception**

Create a welcome ceremony for every visitor at zero cost.

➤ **Powerful dual system**

Optional Android7.0/Windows10 dual system to carry more applications.

Screen parameters				
size	65"	75"	86"	100"
Screen type	ADS			
Response time	8 ms			
Aspect ratio	16:9			
Maximum display size mm	1428×804	1650×928	1895×1066	2159×1214
Resolution	3840(H)×2160(V)			
Pixel pitch mm	0.372×0.372	0.429×0.429	0.4935×0.4935	0.5622×0.5622
Refresh rate	60Hz	60Hz	60Hz	120Hz
Color brightness	1.07B(10bit)			
Color gamut NTSC (Typ)	72%			
Contrast (Typ)	4000 :1	1100:1	1200:1	1200:1
Viewing angle	178°(H/V)			
Backlight type	DLED			
Screen brightness (Typ)	350cd/m ²	350cd/m ²	330cd/m ²	350cd/m ²
Working life	≥30000 hours			

Touch writing system	
Principle of Recognition	Infrared recognition
Touch points	10-point touch
Support system	Windows10/Windows8/Windows7/ WindowsXP /Android/Linux/Mac OS X/Chrome
Smallest identifier	2mm
Input method	Fingers, touch pens and other opaque objects
Response time	≤10ms
Touch accuracy	±1mm (more than 90% touch area)
Writing height	≤3mm
Output coordinates	32767 (W) x32767(D)
Writing display	Two colors writing

Built-in system	
System version	Android 8.0
CPU	Dual-core A73+Dual-core A53
GPU	Quad-core Mali-G51
RAM (running memory)	4GB
ROM (storage)	32GB

Effective input and output ports (65/75/86/100")	
HDMI IN	3
HDMI OUT	1
USB 2.0	3
USB 3.0	3
TOUCH	2
VGA IN	1
AUDIO IN	1
AUDIO OUT	1
SPDIF	1
RS232	1
RJ45 IN	1

WiFi	
Version	802.11 a/b/g/n/ac
working frequency	2.4GHz/5GHz
Working distance	0~12m
RAM (running memory)	4GB
Remark	Realize this function through the wireless module SI02

Speaker	
Soundtrack	2.1
Power	2x10W+15W

Microphone	
Quantity	6
Pickup distance	8m

Built-in camera	
Quantity	1
Pixel	8-megapixel
Position	Border-top

Bluetooth	
version	4.0
working frequency	2.4GHz
Working distance	0~10m
Description	Realize this function through the wireless module SI02

Power				
Size	65"	75"	86"	100"
Power input 100-240V~50/60Hz	2.5A	3.0A	5.0A	7.5A
Maximum power consumption	250W	300W	500W	750W
Standby power consumption	≤0.5W			

Environmental factor	
Operating temperature	0°C~40°C
Operating humidity	10%~90%RH
storage temperature	-20°C~60°C
Storage humidity	10%~90%RH
Altitude	Below 5000 meters

PC system (optional)		
PC model	I3 / I5	
PC type	Ultra-thin pluggable Intel Core series modular computer	
CPU	Core	
Configuration	Configuration 1	I3, DDR4 4GB, M.2 solid state drive 128GB (SSD)
	Configuration 2	I5, DDR4 8GB, M.2 solid state drive 256GB (SSD)
Graphics card	Integrated Intel [®] HD Graphics	
Sound card	Integrated high-definition stereo sound card	
Built-in system	Windows 7/10 Enterprise Edition	
HDMI output	1	
USB2.0	2	
USB3.0	2	
Microphone input	1	
AUDIO OUT	1	
PC interface	120pin	

- **3.1 The main interface of the Android system, this product is compatible with Windows dual-system operation, and can be switched with one key on any interface using the floating menu.**



- **3.2 Support remote conference software and rich office applications, users can choose to install them according to their needs.**



➤ 4.1 Front view



➤ 4.2 Rear view




➤ 4.3 Product structure size (mm)

Model size	65"	75"	86"	100"
Display size (mm)	1428x804	1650x928	1895x1066	2159x1214
Overall machine size (mm)	1489x906x89	1710x1029x89	1957x1169x90	2245x1323x90
Packing size(mm)	1656x204x1050	1886x210x1196	2134x210x1334	2483x376x1493
Whole machine + wall thickness	119mm	119mm	120mm	135.5mm
VESA hole specifications	600x400mm	800x400mm	800x600mm	800x600mm
Wall-mounted screw specifications	M8x25mm			
Net weight (bare metal)	37.5kg	52.3kg	69.8kg	102kg
Gross weight (packaging)	49.8kg	66.2kg	89.4kg	136kg


➤ 3.3 H8Q series display uses built-in camera, one-button start, front microphone, stylus suction slot, front USB, the meeting is convenient and quick to use.




Built-in 8-megapixel camera




One-key start switch



Front speakers



Magnet pen adsorption slot



Android+windows dual channel USB interface



Laser logo

➤ 5.1 Safe packaging and worry-free protection



01.泡沫垫



02.进口美牛纸箱

➤ 5.2 Packaging accessories

Accessories	
Manual/warranty card	1
Pass card	1 10%~90%RH
Power cord	1 (Not equipped if the machine comes with it)
Writing pens	2
3 antenna poles	3 (The quantity is according to the models)

➤ 6.1 Two installation methods



Mobile bracket installation

Wall mount

➤ 6.2 Recommended model size

Recommended meeting tablet size				
Recommended model size	65"	75"	86"	100"
Area	20-30 m ²	30-40 m ²	50-80 m ²	≥80 m ²
Number of people	20	35	50	≥100

➤ 7.1 High-end mobile trolley stand (suitable for 65-86")



➤ 7.2 High-end mobile trolley stand (suitable for 65-86")

Bracket model	M33
Finished product size after assembly (Lx W x H)	1160x661x1597mm
Packing size (LxWxHt)	1625x785x160mm
Net weight	18kg
Gross weight	23.5kg
Weight capacity	100kg
Loadable model size	55-86"
Casters	3 inches mute wheel
Bracket color	Gray-black

➤ 7.3 Luxury mobile trolley stand (suitable for 65-86")



➤ **7.4 Parameters of the luxury mobile trolley stand**

Bracket model	Y2000 silver + black
Use material	High-quality cold-rolled steel, surface pickling process treatment, black fine grinding electrostatic spraying
Weight capacity	136Kg / 100lbs
Lifting height range (level off the ground)	1280 mm to 1700 mm
Load-bearing capacity of the middle pallet (place documents)	20Kg / 100lbs
Base area size	L1300 x W650 mm (L1300 x W650 mm (4 nylon casters with foot brake function)
Package size	L1590 x W630x H220 mm
Recommended size for whole machine	55"-98"

➤ 7.5 Universal all-in-one wall mount (suitable for 65-100 inches)




➤ 7.6 Universal all-in-one wall mount

Bracket model	BH-001
Product color	Matt black
Use material	Selected thick cold-rolled steel
Maximum load	≤80Kg
The distance from the wall	80 mm
Description	One-piece stamping, no need for splicing

➤ 7.7 OPS Computer


Equipped with Intel Core processor, Android and Windows dual system with one-key switch, convenient operation, meet all-round needs.



OPS Computer parameter		
7th generation Core i3	RAM 4G+SSD 128G	Office presentations, Internet entertainment
7th generation Core i5	RAM 8G + SSD 128G	4K video, video conference
7th generation Core i7	RAM 8G + SSD 128G	Drawing software, large-scale applications

➤ 7.8 Wireless screen sharing dongle.

The intelligent wireless screen device can realize the wireless projection of the computer to the conference board, two-way control, and interactive collaboration, which is simple and convenient.



➤ 7.9 Wireless screen sharing dongle parameters

Max. number of connections	1 USB receiver receiver, can connect 8 transmitters at the same time
Adaptation operating system	Support Windows 7/8/8.1/10, Mac OS 10.9/10.10/10.11
Adaptation interface	USB2.0
Operating frequency	2432MHz, 5180MHz
Transmission delay	Average delay <120ms
Whole machine power consumption	25W
Transmit power	16mW

Button position and number	Logo button, 1
Data transmission range	8 meters, high-strength encryption ensures information security
Dimensions	77x 178.7 x 44 mm

➤ 7.10 Smart page turning pen

Plug and play, touch writing, full-channel PPT page up and down, and device volume control function.



Wanbao focus on quality, service throughout



Factories and production processes



CERTIFICATIONS



<p>ETR Shenzhen Yitong Testing Technology Co., Ltd.</p> <p>TEST REPORT Determination of Hazardous Substance</p> <p>Report No.: ET-210500037 Applicant: Guangdong Deyan Technology Co., Ltd. Address: No. 32, Xixiu Road, Automobile industry city, Huadu District, Guangzhou, Guangdong Province, China, 510820 Commercial LED display (display device), Commercial whiteboard (display device), Interactive whiteboard (display device), Multimedia touch all-in-one machine (display device), Conference whiteboard (display device), Smart conference whiteboard (display device), Smart learning whiteboard (display device), Teaching touch all-in-one machine (display device), Smart screen (display device), Live broadcast screen (display device), Multimedia information publishing terminal (display device), Multimedia information terminal (display device), digital signage (display device), smart advertising machine (display device) Model No.: LED75H****, LED75G****, LED75C****, LED75S****, LED75T****, LED75A****, LED75M**** Represents the numbers 50, the letters a-z, the letters A-Z, or blank, for marketing purposes only, and does not affect the safety and EMC performance of the product Brand Name: N/A Issue Date: 2021-05-25 Test Requested: As requested by the applicant, test(s) was/were performed as below:</p> <table border="1"> <thead> <tr> <th>Test Summary</th> <th>Conclusion</th> </tr> </thead> <tbody> <tr> <td>EU RoHS Directive 2011/65/EU and its amendment directives 2015/863/EU (RoHS 2.0) on Lead, Cadmium, Mercury, Hexavalent Chromium, PBBs, PBDEs, DEHP, BHP, DBP & DBP content (EC 6321-4-2011/A1-2017) IEC 62321-4-2013 IEC 6321-7-2-2017/IEC 6321-6-2015 IEC 6321-8-2017</td> <td>Pass</td> </tr> </tbody> </table> <p>Test Results: Please refer to following page(s). Wrote by: [Signature] Approved by: [Signature] Date: 2021-05-24 Date: [Signature]</p> <p>903, Hongji building, 227, Fubin Second District, Sanbin community, Longhua street, Longhua District, Shenzhen Tel: +86 755 85259392 Fax: +86 755 27119460</p>	Test Summary	Conclusion	EU RoHS Directive 2011/65/EU and its amendment directives 2015/863/EU (RoHS 2.0) on Lead, Cadmium, Mercury, Hexavalent Chromium, PBBs, PBDEs, DEHP, BHP, DBP & DBP content (EC 6321-4-2011/A1-2017) IEC 62321-4-2013 IEC 6321-7-2-2017/IEC 6321-6-2015 IEC 6321-8-2017	Pass	<p>CQC</p> <p>QUALITY MANAGEMENT SYSTEM CERTIFICATE Certificate No. 00121Q31200R0M4100</p> <p>We hereby certify that Guangdong Deyan Technology Co., Ltd. (Shenzhen Deyan Technology Co., Ltd.) No. 32, Xixiu Road, Automobile industry city, Huadu District, Guangzhou, Guangdong Province, China has been awarded this certificate for compliance with the standard Quality Management System GBT 19001-2016 / ISO 9001:2015 The Quality Management System Applies in the following area: The R&D, Sales of Smart LED TV and Commercial Display Products/Interactive Whiteboard, Smart Advertising Player)</p> <p>Certified since: February 2, 2001 Valid from: February 2, 2021 Valid until: February 1, 2024</p> <p>After a successful audit, the certificate is valid only when used together with an Accreditation Notice of Surveillance Audit issued by CQC. Please access www.cqc.com.cn for checking validity of the certificate. This certificate and its relevant information are only in the custody of Certificate and Accreditation Administration of the People's Republic of China (www.cqc.com.cn)</p> <p>CHINA QUALITY CERTIFICATION CENTRE (Shenzhen) No. 100, Yantianhuashu Road, Fourth Bay Road, Nian'ao Road, Nanshan District, Shenzhen 518071, China www.cqc.com.cn</p> <p>A 0106741 2021.05.24</p>	<p>ETR Shenzhen ETR Standard Technology Co., Ltd.</p> <p>CERTIFICATE OF CONFORMITY No.: ET-21050287EC</p> <p>Applicant: Guangdong Deyan Technology Co., Ltd. Address: No. 32, Xixiu Road, Automobile industry city, Huadu District, Guangzhou, Guangdong Province, China, 510820 Manufacturer: Guangdong Deyan Technology Co., Ltd. Address: No. 32, Xixiu Road, Automobile industry city, Huadu District, Guangzhou, Guangdong Province, China, 510820 Product: Commercial LED display (display device), Commercial whiteboard (display device), Interactive whiteboard (display device), Multimedia touch all-in-one machine (display device), Conference whiteboard (display device), Smart conference whiteboard (display device), Smart learning whiteboard (display device), Teaching touch all-in-one machine (display device), Smart screen (display device), Live broadcast screen (display device), Multimedia information publishing terminal (display device), Multimedia information terminal (display device), digital signage (display device), smart advertising machine (display device) Model(s): LED75H****, LED75G****, LED75C****, LED75S****, LED75T****, LED75A****, LED75M**** Represents the numbers 50, the letters a-z, the letters A-Z, or blank, for marketing purposes only, and does not affect the safety and EMC performance of the product Brand Name: N/A Test Standards: EN 55032:2015+A11:2020, EN 55035:2017 EN 61000-3-2:2019, EN 61000-3-3:2013+A1:2019</p> <p>The EUT described above has been tested by us with the listed standards and found in compliance with the Council EMC Directive 2014/53/EU. It is possible to use CE marking to demonstrate the compliance with this EMC Directive. The certificate applies to the listed sample above mentioned only and shall not imply an assessment of the whole production. It is only valid in connection with the test report number: ET-21050287E.</p> <p>CE </p> <p>2021.05.24 (Manager)</p>
Test Summary	Conclusion					
EU RoHS Directive 2011/65/EU and its amendment directives 2015/863/EU (RoHS 2.0) on Lead, Cadmium, Mercury, Hexavalent Chromium, PBBs, PBDEs, DEHP, BHP, DBP & DBP content (EC 6321-4-2011/A1-2017) IEC 62321-4-2013 IEC 6321-7-2-2017/IEC 6321-6-2015 IEC 6321-8-2017	Pass					



Focus on quality, service throughout the world



Strength factory

41 years household appliance brand, self-built industrial park



Research and development strength

Product independent development and design have independent patent property rights



OEM/ODM

Fast delivery capability



Quality assurance

FCC, ISO 9001, RoHS, CE certification



High quality service

perfect after-sales service to avoid your worries



Convenient Logistics

Support DHL, TNT, UPS, EMS, Fedex and other

Transportation





Guangdong Deyuan Group Co., Ltd.

ADD: Xixiu Road 32, Xinhua Street, Huadu, Guangzhou City, Guangdong, CN.

Website: www.wanbaotv.com