

NT Low Voltage Fuse

Application

NT low voltage H.R.C. fuse features light in weight, small in size, low in power loss and high in breaking capacity. This product has been widely used in overload and short circuit protection of electric installation. This product conforms to IEC 60269 standards with all of the rating at the world advanced level.

Specifications



Type	Fuse link				Fuse base		
	Rated current (A)	Rated voltage (V)	Rated power loss (W)	Weight (kg)	Type	Rated current (A)	Weight (kg)
NT00C	2	500, 600	0.41	0.15	Sist 101	160	0.2
	4		0.62				
	6		0.81				
	10		1.08				
	16		1.60				
	20		1.81				
	25		2.31				
	32		3.07				
	36		3.17				
	40		4.05				
	50		4.25				
	63		4.70				
	80		5.7				
	100		7				
NT00	4	500, 600	0.67	0.15	Sist 101	160	0.2
	6		0.89				
	10		1.14				
	16		1.65				
	20		1.94				
	25		2.50				
	32		3.32				
	36		3.56				
	40		4.30				
	50		4.5				
	63		4.6				
	80		6				
	100		7.3				
	125		7.6				
	160		9.6				
	NT0		6				
10		1.42					
16		2.45					
20		2.36					
25		2.7					
32		3.74					
35		4.3					
40		4.7					
50		5.5					
63		6.9					
80		7.6					
100		8.9					
125		10.1					
160		15.2					

Specifications

Type	Fuse link				Fuse base		
	Rated current (A)	Rated voltage (V)	Rated power loss (W)	Weight (kg)	Type	Rated current (A)	Weight (kg)
NT1	80	500, 600	6.2	0.36	Sist 201	250	0.8
	100		7.5				
	125		10.2				
	160		13				
	200		15.2				
	224	500	16.8				
	250		18.3				
NT2	125	500, 600	9	0.65	Sist401	400	1.2
	160		11.5				
	200		15				
	224		16.6				
	250		18.4				
	300		21				
	315		19.2				
	355		24.5				
	400		26				
	NT3		315				
355		22.7					
400		26.8					
425		28.9					
500		500	32				
630			40.3				
NT4	800	380	62	1.95	Sist1001	1000	3.45
	1000		75				

