DELON®

MEDICAL ENDOSCOPIC RELEVANT PRODUCTS

Medical portable cold light source (LED100)



Art. No.:A0911.2

- ◆ Linear output: nominal working current of 850 mA
- ◆ Continuous illumination time is more than 3hours
- Maximum brightness output: 180 lm
- ◆ Lamp life:Up to 100000 hours

Medical head light



Art. No.: XXXX

- ◆ Light life: Minimum 100000 Hours
- ◆ Light Source: LED
- ♦ Color temperature: Minimum 5500 K
- ♦ Operating Distance: Minimum 0.4-5m
- ◆ Light Intensity: Minimum 1000 Lux
- ♦ Continuous time: 5 hours
- Charging: NiMH battery

Smartphone camera adaptor



- Otterbox are suitable for iPHONE 4/4s/5/5s/6/6plus
- ♦ Long focal lens of Optical Adapter provide more clear images and videos
- Universal design of optical adapter can connected any rigid endoscopes

Art.No

- ♦ 4X Optical magnification
- Good quality plastic molding of otterbox

Light guide bundles

ORDINARY TYPE

Art.No Specifications A0902.1 Ф4.5x3m

A0902.2 Ф3.5x2.5m

HIGH DENSITY TYPE (Germany optical fiber) Art.No Specifications

A0902.3H Ф4.5x3m

A0902.4H Ф3.5x2.3m

Conversion interface

A0902.3 Wolf/Stryker A0902.4



Olympus

OPTICAL ADAPTOR(F=14/18/20/25/27/32/35)-C-MOUNT

RIGID OPTICAL ADAPTOR, FOR UNIVERSAL APPLICATION

RIGID ENDOSCOPE ADAPTOR (STRAIGHT, PRISMATIC) For standard rigid endoscope







Art.No.: A9805

HD RIGID PARAFOCAL OPTICAL ADAPTOR, FOR UNIVERSAL APPLICATION

automatically adjust image big & small F14-25



HD RIGID PARAFOCAL OPTICAL ADAPTOR, FOR UNIVERSAL APPLICATION

automatically adjust image big & small F16-32



Art.No.:A0508.3

HD RIGID OPTICAL ADAPTOR, FOR UNIVERSAL APPLICATION

High resolution, with HD endoscope, Achieve the highest image effect



Art.No.:A0509

RIGID TO OLMPUS OPTIC AL ADAPTOR

OES ADAPTOR (STRAIGHT, PRISMATIC) For OLMPUS fiberscope



Art.No.:A0305



RIGID TO PENTAX OPTICAL ADAPTOR

For PENTAX fiberscope





Art.No.:A0807

RIGID TO OES SWITCH OPTICAL ADAPTOR

Rigid to OES adapter



to OES

Art.No.: A0309