



GRADUATE SCALE READING,  
MEASUREMENT TUBE  
WITH "LENS EFFECT"

#### TECHNICAL SPECIFICATIONS | EasyFLOW®

<b>SIZES (LxWxH)</b>	61x107x175 mm
<b>WEIGHT</b>	0.37 Kg
<b>GAS SUPPLY PRESSURE</b>	280÷600 kPa with an integrated pressure reducer for the stabilization of supplied pressure
<b>GASES OPTIONS</b>	O <sub>2</sub> • Air
<b>END OF SCALE VALUES</b>	5 L/min. • 10 L/min. • 15 L/min. • 30 L/min. • 40 L/min.
<b>ACCURACY</b>	±10% read value or ±0.5 L/min. (±0.2 L/min. for flows < than 1 L/min.) if greater
<b>STANDARD INLET CONNECTION</b>	ISO G 1/4" M. • 1/4"NPT M.
<b>STANDARD OUTLET CONNECTION</b>	Nipple with double thread, interchangeable by the end user: M12x1.25 M • 1/4" ISO 3253 M. 9/16" UNF EN 13544-2 M • 1/4" ISO 3253 M. M12x1.25 M • 9/16" UNF EN 13544-2 M.
<b>FLOW CALIBRATION DATA</b>	1013 mbar 23 °C