



### GRADUATED BEAKERS, LOW FORM, IN PP BICCHIERI GRADUATI FORMA BASSA, IN PP

In polypropylene, with a relief graduation in ml and oz. Suitable for all current laboratory purposes. Autoclavable up to +121 °C, continuous work at +100 °C. Excellent chemical resistance. In accordance with ISO 7056-1981 (E) and BS 5404 part 1 standards.

In polipropilene, con graduazione in ml e in once stampata in rilievo. Per tutti i comuni usi di laboratorio. Autoclavabili a +121 °C e resistono a +100 °C per uso continuato. Eccellente resistenza chimica. Realizzati secondo le norme ISO 7056-1981 (E) e BS 5404 parte 1.

COD.	VOL. ML	O.D. Ø MM	H. MM
12032	25	34	49
12033	50	41	60
12034	100	51	72
12035	250	71	95
12036	500	87	119
12037	1000	109	147
12038	2000	132	183.5
12039	3000	158	201
12040	5000	188.5	229

### GRADUATED BEAKERS, LOW FORM, IN TPX® BICCHIERI GRADUATI FORMA BASSA, IN TPX®

In TPX®, with a relief graduation in ml and oz. Suitable for all current laboratory purposes. Autoclavable up to +121 °C and resistant at +170 °C for short periods. Excellent chemical resistance. In accordance with ISO 7056-1981 (E) and BS 5404 part 1 standards.

In TPX®, con graduazione in ml e in once stampata in rilievo. Per tutti i comuni usi di laboratorio. Autoclavabili a +121 °C e resistono a +170 °C per brevi periodi. Eccellente resistenza chimica. Realizzati secondo le norme ISO 7056-1981 (E) e BS 5404 parte 1.

COD.	VOL. ML	O.D. Ø MM	H. MM
12062	25	34	49
12063	50	42	60
12064	100	52	72
12065	250	71	95
12066	500	88	119
12067	1000	110	146
12068	2000	133	184
12069	3000	159	200
12070	5000	190	228



### VOLUMETRIC FLASKS WITH SCREW CAP, IN PP MATRACCI TARATI CON TAPPO A VITE, IN PP

In translucent polypropylene. Calibrated gravimetrically at +20 °C. Autoclavable, they are supplied with stopper.

In polipropilene particolarmente trasparente. Tarati con metodo gravimetrico a +20 °C. Autoclavabili, forniti completi di tappo.



COD.	VOL. ML	H. MM	O.D. Ø MM	DIN STD
12301	25	121	36	GL 18
12302	50	143	46	GL 18
12303	100	174	58	GL 18
12304	250	225	82	GL 25
12305	500	265	100	GL 25
12306	1000	325	120	GL 25

### VOLUMETRIC FLASKS WITH SCREW CAP, IN TPX® MATRACCI TARATI CON TAPPO A VITE, IN TPX®

In perfectly transparent TPX®. Calibrated gravimetrically at +20 °C. Autoclavable, they are supplied with stopper.

In TPX®, perfettamente trasparenti. Tarati con metodo gravimetrico a +20 °C. Autoclavabili, forniti completi di tappo.

COD.	VOL. ML	H. MM	O.D. Ø MM	DIN STD
12311	50	143	46	GL 18
12312	100	174	58	GL 18
12313	250	225	82	GL 18
12314	500	265	100	GL 25
12315	1000	325	120	GL 25

