



GLE

→ Natural rubber insulating gloves



STANDARD(S)

EN 60903 / IEC 60903

USE

- Hand insulation according to class and nominal mains voltage
- To be used with a leather overglove for mechanical protection

SPECIFICATIONS

Natural rubber gloves beige, insulating, cut edges

ADVANTAGES

- Wide range of sizes from 7 to 11, depending on the class
- Ergonomically shaped glove with lightly powdered interior for easy donning and doffing
- The natural rubber structure provides high dielectric properties; its thickness protects while ensuring excellent dexterity

Reference	Description	Class	Max operating voltage	Length (cm)	Size	Catégories
GLE36 00	Gants Latex isolants classe 00	00	500 V AC	36	7-11	AZC
GLE36 0	Gants Latex isolants classe 0	0	1 000 V AC	36	7-11	AZC*
GLE36 1	Gants Latex isolants classe 1	1	7 500 V AC	36	7-11	RC
GLE36 2	Gants Latex isolants classe 2	2	17 000 V AC	36	8-11	RC
GLE41 4	Gants Latex isolants classe 4	4	36 000 V AC	41	8-11	RC

Document not contractually binding, errors and omissions excepted.



▶ TABLE LEGEND

Complete the reference with the desired size

Document not contractually binding, errors and omissions excepted.



815B, chemin de Razas - 26780 Malataverne - France
+33 (0)4 75 90 58 00 - www.sf-electric.com

