

Detalii specifice și standarde tehnice

LOT „Procurare de Termociclor”:

№	Name of product	Minimal technical specifications	Offered specifications; model, manufacturer.
1	Termociclor	The thermal cycler for PCR with 96 positions for 0.2 ml tubes. Power configurations: VAC 220-240V, 50 Hz. - Memory for minimum 5 PCR programs, that can be edited manually. - Temperature range: 04-100°C; - Real-time graphical display of actual and set block temperatures, - Real-time digital display of all sensor values; - Temperature accuracy: +/-0.5°C; - Heating rate: up to 6°C/s; - Cooling rate: Up to 3°C/s; - Calibrated to traceable international standards.	The thermal cycler for PCR with 96 positions for 0.2 ml tubes. Power configurations: VAC 220-240V, 50 Hz. - Memory for minimum 5 PCR programs, that can be edited manually. - Temperature range: 04-105°C; - Real-time graphical display of actual and set block temperatures, - Real-time digital display of all sensor values; - Temperature accuracy: ±0.1°C, at 55°C ±0.3°C. - Heating rate: 5°C/s; - Cooling rate: 5°C/s; - The thermal cycler has a serial number so it is traceable and comes calibrated from the factory.
	Mandatory requirements	- Original manufacturer packing for all items; - Quality Certificates (CE and/or DC) or any other equivalent; - ISO 9001-2015	- Original manufacturer packing for all items; - Quality Certificates (DC); - ISO 9001-2015

- **Toate bunurile vor fi testate de beneficiar. Acceptarea bunurilor și semnarea actelor de recepție va avea loc după testarea pozitivă efectuată de beneficiar.**

NUMELE FURNIZORULUI : Lokmera S.R.L.
Locul: or. Chișinău

Semnătura și ștampila autorizate: Nicolai Iașițaș, Director
Data: 24.08.2023

