

Specificații tehnice (F4.1)

Numărul licitației:	21009802 ocds-b3wdp1-MD-1562746948799	Data: 26.07.2019	Alternativa nr.: nu se aplică
Denumirea licitației:	Servere:	Lot: 1. Servere	Pagina: 1 din 3

Cod CPV	Denumirea bunurilor și/sau a serviciilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7	8
30200000-1	Servere	868703-B21	EU (Czech Republic)	HP Enterprise	Server	868703-B21 HPE ProLiant DL380 Gen10 8SFF Configure-to-order Server	Conform
					Rack mount, 2U, 19" rack mount	Rack mount, 2U, 19" rack mount	Conform
					Processor min. two (2 x) processors; min. 18 core; min 36 threads; min. 2.6 Ghz; min. cache 25Mb; memory 2400Mhz. Last generation at the moment	1x P02509-L21 HPE DL380 Gen10 Intel Xeon-Gold 6240 (2.6GHz/18-core/150W) FIO Processor Kit 1x P02509-B21 HPE DL380 Gen10 Intel Xeon-Gold 6240 (2.6GHz/18-core/150W) Processor KitLatest generation	Conform
					Memory min. 512 GB (8x 64Gb); DDR4 2933MHz; min 24 slots or more	8x HPE 64GB (1x64GB) Quad Rank x4 DDR4-2933 CAS-21-21-21 Load Reduced Smart Memory Kit 24x DIMM slots	Conform
					RAID controller Hardware Controller; RAID 0/1/5/10/50/60; Min. cache 4Gb.	1x 804338-B21 HPE Smart Array P816i-a SR Gen10 (16 Internal Lanes/4GB Cache/SmartCache) 12G SAS Modular Controller 1x P01366-B21 HPE 96W Smart Storage Battery (up to 20 Devices) with 145mm Cable Kit RAID 0, 1, 5, 6, 10, 50, 60, 1 ADM, 10 ADM (Advanced Data Mirroring)	Conform
					Drive bays min. 16x 2.5" SAS/SATA (front) with drive bays;	16x front drive bays 1x 8 SFF cage standard	Conform

					1x 826691-B21 HPE DL38X Gen10 SFF Box1/2 Cage/Backplane Kit	
				Hard drives: min. two (2x) 2,5"; min. 400 GB; Enterprise Performance SAS SSD; 12Gbps; hot-plug.	2x P04525-B21 HPE 400GB SAS 12G Mixed Use SFF (2.5in) SC Digitally Signed Firmware SSD	Conform
				Cooling system: Redundant hot plug	6x standard redundant hot plug fans	Conform
				Power supply: Redundant hot plug power supplies; min. 900W; Two (2x) Power cables, PDU connection	2x 830272-B21 HPE 1600W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit; with PDU power cables	Conform
				Expansion slots: 1x Full PCIe x16; min 6x Full PCIe x8	2x PCIe x16 full-height full-length; 2x PCIe x8 full-height full-length; 2x PCIe x8 full-height half-length Slots	Conform
				Network interfaces Two (2x) - Gigabit Ethernet NIC with four (4x) ports 100/1000	1x HPE 1Gb Ethernet 4-Port 331i Adapter standard 1x 665240-B21 HPE Ethernet 1Gb 4-port 366FLR Adapter	Conform
				Additional cards: Two (2x) - FC HBA cards with min one FC port, min. 8Gbit	2x P9D93AHPE StoreFabric SN1100Q 16Gb Single Port Fibre Channel Host Bus Adapter	Conform
				Porturi: 1x front VGA (15 pin/female); 1x back end VGA (15pin/female); 1x Management port; 8x RJ-45; min. 4x USB 2.0; min. 2x USB 3.0	1x front VGA/DisplayPort; 1x Rear VGA port; 1x iLO Remote Management Port; 1x Front iLO Service port; 5x USB 3.0: 3 front, 2 rear, 2 internal (secure); 1x Micro SD Slot; 8x RJ-45	Conform
				Server management (SM): Dedicated Ethernet NIC for management; Local and remote control of system resources (manage, diagnose and monitor); Remote power control, remote firmware updating, remote presence, capture of OS failure screen (BSOD) via web interface, virtual media attachment to a server of USB drive, CD/DVD drive; Serial over LAN, DHCP, IPMI V2.0, CIM, SNMP, email alerts; LDAP user authentication; Browser based administration with full control over the remote host server's display,	1x BD505A HPE iLO Advanced 1-server License Local and remote control of system resources (manage, diagnose and monitor). Remote power control, remote firmware updating, remote presence, capture of OS failure screen (BSOD) via web interface, virtual media attachment to server of USB drive, CD/DVD drive Serial over LAN, DHCP, IPMI V2.0, CIM, SNMP, email alerts LDAP user authentication	Conform

				keyboard, and mouse, including host OS graphical interface; Virtual media option that provides virtual CD drive and remote image mounting; SM & server diagnostics logging; SSL or SSH encryption.	Browser based administration with full control over the remote host server's display, keyboard, and mouse, including host OS graphical interface. Virtual media option that provides virtual CD drive and remote image mounting. SM & server diagnostics logging. SSL or SSH encryption.	
				Rack mounting rails: Rails with full extraction, Cable management arm	1x 733664-B21 HPE 2U Cable Management Arm for Easy Install Rail Kit 1x 733660-B21 HPE 2U Small Form Factor Easy Install Rail Kit	Conform
				Operating Systems Supported MS Windows Server 2016/2019, Microsoft Hyper-V Server 2016/2019, SUSE Linux Enterprise Server x86 (64-bit)	Windows Server 2016; Microsoft Hyper-V; VMware ESXi 6.0 U3; VMware ESXi 6.5 and U1; CentOS; Red Hat Enterprise Linux (RHEL) 6.9 and 7.3; SUSE Linux Enterprise Server (SLES) 11 SP4 and 12 SP2 (64-bit); Canonical Ubuntu; ClearOS	Conform
				Installation, cabling and configuration: Including all necessary parts and specialists	Included all necessary parts and specialists for Installation, cabling and configuration	Conform
				Warranty 5 years parts/labor/onsite, repair next business-day	1 H7J32A5 HPE 5Y Foundation Care NBD SVC 5 years support NBD included	Conform

Semnata: _____

Numele, Prenumele: Iurii Svera

În calitate de: Key Account Manager

Ofertantul: **BASS SYSTEMS SRL**

Adresa: Calea Ieşilor 8, Chişinău, MD-2069, Republica Moldova