

Model		Xtreme Inverter Pro 9000 BTU	Xtreme Inverter Pro 12000 BTU	Xtreme Lite Inverter 18000 BTU	Xtreme Lite Inverter 24000 BTU
Cod model		MSAGBU-09HRFN8-QRD1GW MOX230-09HFN8-QRD6GW	MSAGBU-12HRFN8-QRD1GW MOX230-12HFN8-QRD6GW	MSAGCU-18HRFNX-QRD0GW MOX301-18HFN8-QRD0GW	MSAGDU-24HRFN8-QRD0GW MOX401-24HFN8-QRD0GW
Capacitate (BTU/h)	Racire	9000 (3500-11000)	12000 (4700-14700)	18000 (6600-21400)	24000 (10300-30000)
	Incalzire	10000 (2800-11500)	13000 (3650-14950)	19000 (4400-23900)	25000 (5200-32300)
Putere consumata (W)	Racire	628 (80-1100)	1005 (130-1650)	1550 (150-2250)	2191 (340-3450)
	Incalzire	661 (70-990)	977 (160-1560)	1543 (220-2350)	2030 (300-3150)
SEER / SCOP (W/W)		8.80 / 4.60	8.50 / 4.60	7.00 / 4.00	6.40 / 4.00
Clasa de energie	Racire / Incalzire	A+++ / A++	A+++ / A++	A++ / A+	A++ / A+
	Racire	2.73 (0.3-4.78)	4.37 (0.5-7.2)	6.7 (0.7-9.8)	11.1 (1.4-15)
Curent nominal (A)	Incalzire	2.83 (0.32-4.32)	4.24 (0.5-6.4)	7.8 (0.95-10.2)	10.3 (1.3-13.7)
Alimentare (Ph-V-Hz)		(I Ph-220-240V-50Hz)	(I Ph-220-240V-50Hz)	(I Ph-220-240V-50Hz)	(I Ph-220-240V-50Hz)
Debit de aer (m3/h)	H / M / L	510 / 360 / 300	520 / 370 / 310	1150/1000/850	1150/1000/850
Interval temperatura exterioara de functionare (°C)	Racire	-15 - 50	-15- 50	-15 - 50	-15 - 50
	Incalzire	-20- 24	-20 - 24	-20 - 24	-20 - 24
Agent frigorific		R32	R32	R32	R32
Cantitate agent frigorific (kg)		0.62	0.62	1.1	1.45
Diametru teava lichid / gaz (mm)		Φ6.35 / Φ9.52	Φ6.35 / Φ9.52	Φ6.35 / Φ12.7	Φ9.52 / Φ15.9
Lungime maxima traseu frigorific(m)		25	25	30	50
Diferenta maxima de nivel traseu frigorific (m)		10	10	20	25
Suprafata de utilizare (m ²)		12-18	16-23	24-35	32-47
Unitate interioara					
Nivel de presiune acustica (dB/A)	H / M / L / S	37 / 32 / 22	37 / 32 / 22	41 / 37 / 31	46 / 37 / 34.5
Nivel de putere acustica (dB/A)		54	54.5	56	62
Dimensiune neta (mm)		LxIxH	835x208x295	969x320x241	1083x336x244
Dimensiune bruta (mm)		LxIxH	905x290x355	1045x405x315	1155x415x315
Greutate neta / bruta (kg)			8.7 / 11.5	112 / 14.6	136 / 173
Unitate exterioara					
Nivel de presiune acustica (dB/A)		55.5	55	57	60
Nivel de putere acustica (dB/A)		62	62	65	67
Dimensiune neta (mm)		LxIxH	765x303x555	805x330x554	890x342x673
Dimensiune bruta (mm)		LxIxH	887x337x610	915x370x615	995x398x740
Greutate neta / bruta (kg)			23.5 / 25.4	33.5 / 36.1	43.9 / 46.9