

Laboratory Refrigerator



BPR-5V50(G)



BPR-5V100(G)

Technical Parameters

Model	BPR-5V50(G)	BPR-5V100(G)
External Size(W*D*H)mm	495*548*683	495*548*934
Internal Size(W*D*H)mm	415*405*455	415*405*706
Capacity	50L	100L
Temperature Range	2-8℃	
Temperature Accuracy	0.1℃	
Control System	Microprocessor Control	
Alarm	Audible and visual alarm for: High and low temperature,Door Ajar, Thermostat failure	
Refrigeration Type	Forced air refrigeration system	
Refrigerant	R600a	
Climate Type	N, SN	
Glass Door	Toughened with electric heating function,no condensation	
Construction	Constructure	Polyurethane cyclopentane foams
	Internal material	Spraying steel plate
	External material	Spraying steel plate
Consumption	85W	95W
Power Supply	AC220V±10%, 50/60Hz; AC110V±10%, 50/60Hz	
Shelves	2pcs, cold drawn steel wire impregnated shelf	3 pcs,cold drawn steel wire impregnated shelf
Door Lock	1 pcs	
Accessory	Standard: USB Port, LED Lamp	
	Optional: temperature recorder, printer(usbport can not be selected at the same time)	
Package Size(W*D*H)mm	560*668*858	560*668*1109
Gross Weight(kg)	49	61

Laboratory Refrigerator



260L



360L

Technical Parameters

Model	BPR-5V260	BPR-5V360
External Size(W*D*H) mm	540*635*1900	660*655*1980
Capacity	260L	360L
Temp. Range	2℃~8℃	
Temp. Accuracy	0.1℃	
Control System	Microprocessor Control, Large Screen LED Display	
Alarm	Audible and visual alarm for: High temperature & sensor failure,door ajar, Power failure alarm, Low battery alarm.	
Refrigeration Type	Forced air refrigeration system	
Refrigerant	R134a, CFC Free	
Condenser & Evaporator	Bundy tube condenser	
Defrost	Frostless design	
Construction	Structure	Unibody design & mono-assembly foaming (Rigid polyurethane insulation material)
	Internal material	HIPS engineering plastics, abrasion and acid resistant
	External material	Cold-rolled steel coated with anti-bacteria powder
Shelves	Adjustable shelves made of high quality steel wire	
	4 pcs	5 pcs
Consumption	200W	350W
Power Supply	AC220V±10%, 50/60Hz	
Standard Accessory	LED lamp & shelves, USB, probe access port, door keys	
Package Size(W*D*H) mm	600*670*2150	720*750*2150
Gross Weight(kg)	87	124