

NISOTEC ANTIFRIZ S 40

NISOTEC ANTIFRIZ S 40 is a ready-to-use antifreeze with excellent performance based on monoethylene glycol with corrosion inhibitors. Provides excellent protection against freezing, corrosion, cavitation and overheating of engine cooling systems. It does not contain nitrites, amines, phosphates and borates. The proven formulation provides a period of application of up to 2 years in vehicle cooling systems. Ready to use with frost protection down to -38°C.

Applications:



- Engine cooling systems of older types of motor vehicles and machinery where antifreeze based on classic technology is required
- For application, it is poured directly into the radiator according to the engine manufacturer's instructions

Features	Advantages and Potential Benefits
Low freezing point	It protects against freezing up to -38°C
Excellent corrosion protection	The proven formulation provides effective protection against corrosion of all elements of the cooling system
Gasket compatibility	No leaks or damage to seals in the system

Specification:

- VW/Audi/Seat/Škoda TL 774-C (G11);
- DTFR 29D100 (MB 326.0);
- MAN 324 NF;
- BS 6580;
- ASTM D3306;
- SAE J1034;
- AFNOR NF R 15-601;
- CUNA NC 956-16;
- SRPS H.Z2.010 type III

Typical characteristics

Characteristics	Method	NISOTEC ANTIFRIZ S 40
Color	visual	blue
Freezing point, °C	ASTM D1177	-38
Boiling point, °C	ASTM D1120	108
Reserve alkalinity, mL HCl	ASTM D1121	7,0
pH	ASTM D1287	9,0
Density at 20°C, kg/m ³	ASTM D5931	1072,5

Health, Safety and Environment

Information on the safe handling, storage and disposal of the product, as well as information on precautionary measures and potential hazards, effects on human health and the environment can be found in the Product Safety Data Sheet (SDS). Store the product in its original packaging protected from atmospheric influences. Shelf life 3 years from the date of manufacture.

Available packaging

**1L****10L****220KG****1000L**