

## Bottletop dispenser LLG-uni*TOPDISPENS* 2

The combination of a springless PTFE valve and **PTFE piston** with chemically resistant ETP O-ring enables dispensing of both organic reagents as well as bases, thus, eliminating the need to buy different dispensers for different applications. The improved design of the uni*TOPDISPENS* 2 bottle top dispenser including a **re-circulation valve** allows a smooth, precise and reliable bubble free dispensing without any loss of reagent. The specially designed bottle adaptor which permits a 360° rotation of the unit, the easy volume setting as well as the flexible delivery nozzle underline the user friendliness of this bottletop dispenser. Available in six volume ranges.

- Springless PTFE valve, PTFE piston with chemically resistant ETP O-ring enables **high chemical compatibility**
- Glass cylinder from borosilicate glass 3.3
- Re-circulation valve enables easy priming and bubble free dispensing
- Smooth, reproducible and effortless dispensing
- 360° rotation possible due to specially designed bottle adapter
- Flexible and adjustable delivery nozzle provides **dispensing angle flexibility** to the user
- Specially designed volume adjustment knob for quick and easy volume setting
- **The telescopic extractable intake tube can be easily adjusted to varying bottle heights**
- Nozzle cap reduces contact with air and prevents drying and dripping if the tip cover is attached
- Five bottle adaptors included (28 mm, 32 mm, 37 mm, 40 mm and 45 mm). Standard thread: 30 mm.
- Fully autoclavable at 121 °C, 15 psi for 10 to 15 min
- Individually calibrated in accordance with ISO 8655 standards and each unit is supplied with an individual

### calibration certificate

- You can find the appropriate compatibility list on [www.llg-labware.com](http://www.llg-labware.com) in the Downloads section.
- 3 years warranty



*Bottletop dispenser LLG-uniTOPDISPENS 2*



<i>Description</i>	<i>Volume ml</i>	<i>Grad. ml</i>	<i>Accuracy max. vol. (<math>\pm</math> R%)</i>	<i>Precision max. vol. (<math>\leq</math> CV%)</i>	<i>PK</i>	<i>Cat. No.</i>
LLG- uniTOPDISPENS 2	0.25 - 2.5	0.05	0.6	0.2	1	6.282 275
LLG- uniTOPDISPENS 2	0.5 - 5	0.1	0.6	0.2	1	6.282 276
LLG- uniTOPDISPENS 2	1 - 10	0.2	0.6	0.2	1	6.282 277
LLG- uniTOPDISPENS 2	2.5 - 30	0.5	0.6	0.2	1	6.282 278
LLG- uniTOPDISPENS 2	5 - 60	1.0	0.6	0.2	1	6.282 279
LLG- uniTOPDISPENS 2	10 - 100	2.0	0.6	0.2	1	6.282 280