

32" outdoor wall mount screen



Product features

- Patented LED backlight, the brightness can reach as high as 2000nits under strong sunlight (roughly 3 times of other standard products)
- Broad working ambient temperature:-40° C to +50° C
- The LCD screen can resist condensation in low temperature and humid environment
- Outdoor all-weatherproof, dustproof designed + energy-saving fans cooling

Model No.	SK-HW32BG
Panel size	32" TFT-LCD
Display area(mm)/mode	698mm(H) x 392mm(V) 16:9
Maximum resolution	1920*1080
Display color	16.7M
Pixel Pitch(mm)	0.36mm(H) x 0.36mm(V) (mm)
Brightness (nits)	2000cd/m²
Contrast	3000:1
Visual angle	178°/178°
Response time	6.5ms
Grade	Commercial grade 24/7
Life(hrs)	>60,000(hrs)
Input and output	
VGA	1
DVI	1
HDMI	1
LAN	1 (100/1000 Mb)

Audio		1
Speaker		2×10W（8 ohm）
Video		
Color system		PAL/NTSC/SECAM
Remote controller		Included
OSD display(screen menu display)		
Menu language		English
Power		
Power supply		AC100~240V 50 /60 HZ
Maximum power consumption		≤280W
Standby power consumption		<5W
Temperature		
Working temperature		0℃～50℃
Storage temperature		－40℃~50℃
Working humidity		85%
Storage humidity		85%
Waterproof grade		Outdoor IP55
Temperature control		Fans cooling
Detailed functions		
Video format		MPEG1/MPEG2/MPEG4/DivX/ASP/WMV/AVI
Audio format		Wave/MP3/WMA/AAC
Image format		JPEG/BMP/TIFF/PNG/GIF
Image resolution		480P/720P/1080P
Split screen display		Editable
Running subtitle		Location, word size, color and backlight are editable
Appearance		
Panel color/appearance		White, black, customized
Panel material		Metal case SPCC
Installation		Wall mounted
Pricing and terms		
Version		Display with hdmi or dvi input