

Specificații tehnice (F4.1)

Numărul licitației:	<u>ocds-b3wdp1-MD-1602075084494</u>	Data: „05.” noiembrie 2020	Alternativa nr.: _____
Denumirea LP:	<i>Tehnica de calcul și a camerelor video, conform necesităților DÎTS a Primăriei mun.Bălți</i>	Lot: 1-18	Pagina: 1 din 8

Cod CPV	Denumirea bunurilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant
1	2	3	4	5	6	7
Lotul Nr.1 <i>LT</i> “D.Cantemir” 30213300-8	Calculator personal	i5-9400 THETA15 B365M H 1.0 8GB DDR4- 2666MHz M.2 NVMe SSD 256GB WD5000AZLX 24B2XH VP-600-RGB KB-S330C GAMEMAX	Statele Unite ale Americii China China Taiwan Taiwan Statele Unite ale Americii Hong Kong China Finlanda China	Intel Deepcool Gigabyte Apacer Apacer Western Digital AOC GAMEMAX SVEN GAMEMAX	Calculator personal (set compus din Desktop, Procesor, Mainboard, Memorie, SSD ; disk+Hard Disk, Monitor, Mouse, Tastatura prin fir):Procesor - Intel Core i5 Generatia a 8-a sau a 9-a, minimal 2.8 GHz sau echivalent;Placa de baza – Chipset B360 sau echivalent Memorie – 8Gb DDR4 2400MHz Mediu stocare - 256 Gb PCIe NVMe M.2 SSD + Min 500 Gb , 7200 rpm, SATA III Monitor - 24 inch cu retroiluminare LED, IPS, FullHD (rezolutie 1920x1080), cu tehnologie anti-glare, luminozitate tipică 250-300 niti Sursa de alimentare - 500 Watt, eficienta min. 85% la incarcare maxima, 80 Plus Bronze Certified, MTBF : > 100,000 hours Tastatura – 104 key, interfata USB Mouse – Optical, interfata USB Carcasa – de tip Tower sau Microtower Garanție echipament - Min. 24 luni	CPU Intel Core i5-9400 2.9-4.1GHz (6C/6T, 9MB, S1151, 14nm, Integrated UHD Graphics 630, 65W) Tray; AC Deepcool LGA115x/1200 "THETA15 PWM" (17.8-36dBA, 2000-2800RPM, 50.25CFM, 100mm, PWM, 95W, 290g.); MB Gigabyte B365M H 1.0 mATX; 8GB DDR4- 2666MHz Apacer PC21300, CL19, 288pin DIMM 1.2V; M.2 NVMe SSD 256GB Apacer AS2280P4 [PCIe 3.0 x4, R/W:1800/1100MB/s, 190/180K IOPS, 3D TLC]; 3.5" HDD 500GB Western Digital WD5000AZLX Caviar® Blue™, 7200rpm, 32MB, SATAIII, FR ; 23.8" AOC "24B2XH", Black (IPS, 1920x1080, 7ms, 250cd, LED20M:1, D-Sub+HDMI, Headphone-Out); Power Supply ATX 600W GAMEMAX VP-600-RGB, 80+ Bonze , Active PFC, 120mm RGB fan, Fan Control; Keyboard & Mouse SVEN KB-S330C, Fullsize layout, Splash proof, Fn key, Black, USB; Case mATX GAMEMAX Silent Hill, w/o PSU, 1x120mm, USB3.0, Sound dampening material, Black; Garanție echipament - 24 luni
Lotul Nr.2 <i>LT</i>	Unitate multifuncți	MF443dw	Japonia	Canon	Unitate multifuncțională cu funcții duplex (imprimanta/copiator/scaner)	MFD Canon i-Sensys MF443dw MFD, A4, 38ppm, DADF, Ethernet, WiFi

<p>“D.Cantemir” 30232110-8</p>	<p>onală cu funcții duplex</p>				<p>Funcții - Imprimare și copiere alb-negru, scanare color, trimitere digitală către aplicație de procesare electronică imaginilor și metadatelor Viteza - Minim 30 ppm la imprimarea Conectivitate - USB 2.0, 10/100/1000Base-T Ethernet Capacitate intrare - Dispozitiv automat de alimentare reversibil (față-verso) de documente (Reversing Automatic Document Feder RADF / Duplex Automatic Document Feder DADF) cu capac. de min. 50 coli. Casete hârtie - Tava manuala – minim 50 coli, Tava automata – minim 250 coli Opțiuni duplex- Da, automat la scanare, copier si imprimare. Cartuș de imprimare capacitatea standart - Min. 3000 pagini Cartuș de imprimare capacitatea extinsă - Min. 9000 pagini Garanție echipament - Min. 12 luni</p>	<p>Print, Copy and Scan Print speed: Single sided : Up to 38 ppm (A4), Up to 63.1 ppm(A5-Landscape) Double sided : Up to 31.9 ipm (A4) Print speed: Single sided : Up to 38 ppm (A4), Up to 63.1 ppm(A5-Landscape) Double sided : Up to 31.9 ipm (A4) Interface type: USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Double sided copying: 2-sided to 2-sided (Automatic) Paper input (Standard): 250-sheet cassette, 100-sheet multi-purpose tray, 50-sheet ADF Garanție echipament - . 24 luni</p>
<p>Lotul Nr.3 <i>LT</i> “D.Cantemir” 32333200-8</p>	<p>Registrator Video de Rețea</p>	<p>DHI-NVR608-32-4KS2</p>	<p>China</p>	<p>dahua</p>	<p>Registrator Video de Rețea: Numarul de canale: 32; Sistemul de operare: LINUX; Rezoluție înregistrare: 12M/8M/6M/5M/4M/3M/1080P/1.3M/720P; Compresie video: H.264 / H.265 / MJPEG; Viteză înregistrare: 384 Mbit/c; Mod înregistrare: Manual, Orar (Normal (continuu), Detecție de mișcare, Alarmă, IVS), Vacanțe/ sărbători, Stop; Interfețe: 2 x HDMI, 1 x VGA; Ieșiri alarma: 16/6; Audio intrari/ieșiri: 1 x RCA / 1 x RCA; Afișare ecran: 1/4/8/9/32; OSD; Detecție mișcare: 396 zone (22 x 18); Declanșare eviniment: inregistrare, PTZ, Tur, Alarmă, Video Push, Email, FTP, Snapshot, Buzzer & Screen Tips; Copierea de rezervă: USB/Rețea/extern DVD-RW; Interfață de rețea Ethernet: 2 x RJ-45 porturi (10/100/1000 Mbps); Suport acces de pe smartphon: iPhone, iPad, Android, Windows Phone; Maxim utilizatori: 128; Suport hard disc intern: 8 x SATA III pină la 48 Tb, 1 x eSata pină la 16 Tb;</p>	<p>DHI-NVR608-32-4KS2 System Main Processor Intel Dual-core Processor Operating System Embedded LINUX Audio and Video IP Camera Input 32 Channel Two-way Talk 1 Channel Input, 1 Channel Output, RCA Display Interface 2 HDMI (up to 3840 x 2160 , Different Source), 1 VGA Resolution 3840 x 2160 , 1920 x 1080 , 1280 x 1024, 1280 x 720 , 1024 x 768 Multi-screen Display 1st Screen: 1/4/8/9/16/25/36 2nd Screen: 1/4/8/9/16 OSD Camera title, Time, Video loss, Camera lock, Motion detection, Recording Recording Compression H.265/H.264/MJPEG Resolution 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P etc. Record Rate 384Mbps Bit Rate 16Kbps ~ 20Mbps Per Channel Record Mode Manual, Schedule (Regular, MD (Motion Detection), Alarm, IVS), Holiday, Stop Record Interval 1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec Video Detection and Alarm Trigger Events Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips</p>

					<p>Suport RAID 0/1/5/6/10/50/60; posibilitate hot-spare Interfață USB: 4 (2 x USB 2.0, 2 x USB 3.0); Interfețe auxiliare: 1 x RS232 (p/u comunicație PC & tastatură Dahua), 1 x RS485 (control PTZ); Interoperabilitate: ONVIF 2.4, CGI; Mediu de funcționare: -10°C ~ +55°C; Instalare: Rack; Garanție echipament - Min. 12 luni</p>	<p>Video Detection Motion Detection, MD Zones: 396 (22 × 18), Video Loss and Tampering Alarm input 16 Channel, Low Level Effective, Green Terminal Interface Relay Output 8 Channel, NO/NC Programmable, Green Terminal Interface Tracking Trigger Event Zoom, Tracking, Recording, Preset, Snapshot, Alarm, etc. Playback and Backup Playback 128 Mbps in Raid 5 Mode; 64 Mbps in single HDD Mode Search Mode Time /Date, Alarm, MD and Exact Search (accurate to second) Playback Function Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom Backup Mode USB Device/Network/eSATA Device Third-party Support Third-party Support Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more Network Interface 2 RJ-45 Ports (10/100/1000Mbps) Ethernet Port 2 Ethernet Ports Joint Working or 2 Independent 1000Mbps Ethernet Ports PoE N/A Network Function HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search (Support Dahua IP camera, DVR, NVS, etc.) Optical Fiber Interface N/A Max. User Access 128 users Smart Phone iPhone, iPad, Android Interoperability ONVIF 2.4, CGI Conformant Storage Internal HDD 8 SATA III Ports, Up to 8 TB capacity for each HDD HDD Mode Single, Raid 0/1/5/10(Enterprise-level HDDs are recommended), Support Global HDD Hot-spare eSATA 1 eSATA Port (Please contact technical engineer to confirm the compatible device) SAS N/A Auxiliary Interface Front Cover N/A USB 4 USB Ports (2 USB 2.0 , 2 USB 3.0) RS232 1 Port, for PC Communication and Keyboard RS485 1 Port, for PTZ Control Electrical Power Supply AC100V ~ 240V, 50 ~ 60 Hz</p>
--	--	--	--	--	---	---

						<p>Power Consumption <20W (Without HDD)</p> <p>Environmental Operating Conditions -10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa Storage Conditions -20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH</p> <p>Construction Dimensions 2U, 440mm x 451.08mm x 94.85mm (17.3" x 17.8" x 3.7") Net Weight 9kg (19.8 lb) (without HDD) Gross Weight 10.5kg (23.1 lb) Installation Rack-mounted</p> <p>Certifications CE EN55022, EN55024, EN50130-4, EN60950-1 FCC Part 15 Subpart B, ANSI C63.4-2014 UL UL 60950-1 and CAN/CSA C22.2 No.60950-1</p>
	Camera IP	DH-IPC-HDW1420S	China	dahua	<p>Camera IP: 1/2.8", 4 Megapixel, CMOS cu scanare progresivă; 4.0Mp@20fps(2688×1520), 3.0Mp @25fps (2048×1536 / 2304×1296) 1080P@25fps(1920×1080) PAL, Cameră de tip zi/noapte, cu filtru de absorbție IR autoretractabil Tip camera – interior; LED infraroșu ce permite o distanță de iluminare IR, de până la 30m (98 ft) Sistem de reducere al zgomotului 3D Compresie - Două fluxuri video (video streams) pe cameră, configurabile independent Algoritmi de compresie video - H264/H264+/MJPEG, Bit Rate: 32K ~ 8192Kbps; Mod coridor 9:16 (imaginea este rotită din format peisaj în format portret) Compatibilitate cu specificațiile ONVIF Protocol - L2TP,IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,PPoE,RTP,RTSP,Qos,NTP,FTP,HTTP,SNMP,SIP Toleranță mare la temperatura mediului de -30°C până la 60°C (-22°F până la 140°F) Toleranță mare pentru tensiunea de alimentare – ± 25% Nivel de protecție IP66 (etanș la praf și jeturi puternice de apă</p>	<p style="text-align: center;">DH-IPC-HDW1420S</p> <ul style="list-style-type: none"> · 1/3” 4Megapixel progressive CMOS · H.264+ & H.264 dual-stream encoding · 20fps@4M(2688×1520) &25/30fps@3M(2304×1296) · DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8 mm fixed lens (3.6mm optional) · Max IR LEDs Length 30m <ul style="list-style-type: none"> · IP67, PoE
Lotul Nr.4 <i>LT</i> “D.Cantemir,, 30237240-3	Camera Web	720p HD	Olanda	Trust	Camera Web (Mp): 720P HD	Trust Trino HD Video Webcam, 720p HD Webcam with convenient built-in microphone, 1,43m, USB
Lotul Nr.5	Switch	DH-PFS4226-	China	dahua	Switch retea tip PoE:	

<p><i>LT</i> "D.Cantemir" 32420000-3</p>	<p>retea tip PoE:</p>	<p>24GT-360</p>			<p>Tip – Layer 2 Managed Strat – L2 Numarul de porturi – 52 Tip Porturi Ethernet - 48 x 1000 Mbps (RJ45) + 4 x 1000 Mbps (SFP) Retea standart - IEEE 802.3,IEEE 802.3af,IEEE 802.3at,IEEE 802.3x Capacitate de comutare – 104 GBit/s; Packet Forwarding Rate: 77.4 Mbps; Buget total curent pe cablu net (PoE) – 384 W; Tabelă Adrese MAC: 16K; Jumbo Frame: 9KB</p>	<p>DH-PFS4226-24GT-360</p> <ul style="list-style-type: none"> · Layer 2 network management PoE switch · Support IEEE802.3af, IEEE802.3at standard · Support Hi-PoE 60W · Network Redundancy: STP/RSTP/MSTP · Support IPv4/IPv6, and DHCP · Network management based on SNMP · Configuration: Web, Telnet, CLI Command · QoS (IEEE802.1p/1Q), CoS/ToS to Increase Determinism · Enhanced Network Security with IEEE802.1X, SNMP v1/v2c/v3, HTTPS, and SSH/SSL · Large data cache(4M), real-time transmission · MAC auto study and aging, MAC address list capacity is 8K · EMC high protection design
<p>Lotul Nr.6 <i>LT</i> "D.Cantemir" 32572000-3</p>	<p>Cable UTP Cat 5e (cutia 305m)</p>	<p>Cat.5E CCAG</p>	<p>Statele Unite ale Americii</p>	<p>APC Electronic</p>	<p>Cable UTP Cat 5e (cutia 305m)</p>	<p>Cable UTP Cat.5E, 305m, CCAG, 24awg 4X2X1/0.50, gray color, APC Electronic</p>
<p>Lotul Nr.14 Contabilitatea Centralizată 30213300-8</p>	<p>Calculator</p>	<p>i3-8100 THETA21 B365M H 1.0 8GB DDR4-2666MHz SSD230 5908BG 24B1XH 170 Black KB-S330C</p>	<p>Statele Unite ale Americii China China Taiwan China China Hong Kong</p>	<p>Intel Deepcool Gigabyte Apacer Transcend Sohoo AOC SVEN SVEN</p>	<p>Calculator CPU-Intel i3 8100 3.6GHz (4C/4T, 6MB) M/B-MB S1151 Gigabyte B365M RAM-8 GB DDR4-2666MHz SSD-500 Gb Video- on board Case – 500 wt. 12 sm. Fan Monitor – 23.8” Keyboard, Mouse – USB AS-Sven USB Surge Protector Sven 5Sockets, 5.0 m</p>	<p>Intel® Core™ i3-8100, S1151, 3.6GHz (4C/4T), 6MB Cache, Intel® UHD Graphics 630, 14nm 65W, tray AC Deepcool LGA115x/1200 "THETA21 PWM" (17.8-33.4dBA, 900-2400RPM, 45.9CFM, 92mm, PWM, 95W, 370g.) MB Gigabyte B365M H 1.0 mATX .8GB DDR4- 2666MHz Apacer PC21300, CL19, 288pin DIMM 1.2V 2.5" SATA SSD 512GB Transcend "SSD230" [R/W:560/520MB/s, 85/85K IOPS, SM2258, 3D NAND TLC]</p>

			Finlanda Finlanda			Case ATX 500W Soho 5908BG, 2xUSB2.0, Black-Grey, ATX-500W-12cm 23.8" AOC "24B1XH", Black (IPS, 1920x1080, 7ms, 250cd, LED20M:1, D-Sub+HDMI, Headphone-Out) (23.8" IPS W-LED, 1920x1080 Full-HD, 0.275, 7ms GTG, 250 cd/m ² , DCR 20 Mln:1 (1000:1), 178°/178° @C/R>10, D-Sub + HDMI, HDMI Audio-In, Headphone-Out, External Power Adapter, Fixed Stand (Tilt - 3/+22°), Black Borderless) SVEN 170 Black (USB), 2.0 / 2x2.5W RMS, USB power supply, Volume control on the cable Keyboard & Mouse SVEN KB-S330C, Fullsize layout, Splash proof, Fn key, Black, USB
Lotul Nr.15 Contabilitatea Centralizată 30232110-8	Multifuncțional (echivalent modelului - Canon i- Sensys MF237W + CRG737)	MF237w	Japonia	Canon	Multifuncțional (echivalent modelului - Canon i-Sensys MF237W + CRG737) Funcții disponibile - Imprimanta/Scanner/Copiator/Fax Tehnologie de printare- monocrom Tehnologie de printare - laser Ciclu de utilizare, lunar - 15000 pagini Format - A4 Rezoluție printare alb/negru - 1200x1200 Viteza de printare alb/negru- 23 Ppm Viteza transmisie fax - 33.6 Kbps Zoom - 25-400 % Număr de culori -1 Număr de cartușe – 1 Capacitate memorie - 256 Mb Interfață de rețea- da Interfața Wi-Fi – da Interfețe- Wi-Fi, Ethernet (RJ-45), USB Nivel de zgomot- 66 Db Putere consumată- 1120 W Dimensiuni- 390x360x371 mm Greutate- 11.4 kg Garanție- 24 luni	MFD Canon i-Sensys MF237w MFD A4, 23 ppm, Wi-Fi, Network, Fax, ADF 35 sheet Print, Copy, Scan and Fax Single sided: Up to 23 ppm (A4) Print quality: Up to 1200 x 1200 dpi Print Resolution: 600 x 600 dpi Printer languages UFR II-LT Advanced Space features: Google Cloud Print Ready iOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app Multiple Copy: Up to 999 copies Reduction/Enlargement: 25-400% in 1% increments Scanner Type: ADF, Flatbed, Colour Scan Resolution Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi Scan speed Single sided mono: 20 ipm (300x300dpi) Single sided colour: 15 ipm (300x300dpi) Colour scanning depth: 24 bit/24 bit (input/output) Scan to PC: TIFF/JPEG/PDF/Compact PDF/Searchable PDF Fax : 33.6 Kbps (Up to 3 seconds/page)

						<p>Fax only, Fax/Tel Auto Switch, Answer Mode, Manual</p> <p>Paper input (Standard): 250-sheet cassette 1-sheet multi-purpose tray 35 sheet ADF</p> <p>Paper output: 100-sheet</p> <p>Interface type: USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX, Wireless 802.11b/g/n, Wireless Direct Connection</p> <p>Recommended Monthly Print Volume: 500 - 2,000 pages per month</p> <p>Duty cycle: Max. 15,000 pages per month</p> <p>Memory 256MB</p> <p>Control Panel: 6 lines B&W LCD Touch Screen</p> <p>Cartridge 737 (2,400 pages)</p> <p>Printer ships with Starter Cartridge (900 pages)</p> <p>Paper input (Standard): 250-sheet cassette 1-sheet multi-purpose tray 35 sheet ADF</p> <p>Paper output: 100-sheet</p> <p>Interface type: USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX, Wireless 802.11b/g/n, Wireless Direct Connection</p> <p>Recommended Monthly Print Volume: 500 - 2,000 pages per month</p> <p>Duty cycle: Max. 15,000 pages per month</p> <p>Memory 256MB</p> <p>Control Panel: 6 lines B&W LCD Touch Screen</p> <p>Cartridge 737 (2,400 pages)</p> <p>Printer ships with Starter Cartridge (900 pages) + Cartus de rezerva</p> <p>Laser Cartridge for HP CF283X (Canon 737H) black Compatible</p>
<p>Lotul Nr.18 Școala sportiva nr.1 30232110-8</p>	<p>Imprimantă</p>	<p>MF3010 AM/BM, 1.8 m</p>	<p>Japonia Finlanda</p>	<p>Canon SVEN</p>	<p>Imprimantă (echivalent modelului - Canon i-Sensys MF3010) Mono Printer/Copier/Color Scanner, A4, 18 ppm, 1200x600 dpi, 64 Mb, Scan 9600x9600dpi-24 bit, Paper Input (Standard) 250- sheet tray, USB 2.0, Cartridge 725 (1600 pages 5%) + cablu AMBM</p>	<p>MFD Canon i-Sensys MF3010 MFD A4, 18ppm Print, Copy and Scan Print Speed: Up to 18 ppm (A4) Print Quality: Up to 1200 x 600 dpi with Automatic Image Refinement Print Resolution: 600 x 400 dpi</p>

						<p>First Print Out Time: 7.8 secs Printer Languages: UFR II-LT Memory: 64 MB Control Panel: 1 digit LED</p> <p>Copy Speed: Up to 18 ppm (A4) Copy Resolution: Up to 600 x 600 dpi Reduction / Enlargement: 50-200% in 10% increments</p> <p>Scanner Colour Scan Resolution: Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi Colour Scanning Depth: 24 bit/24 bit (input/output) Scanner Type Flatbed Paper Input (Standard): 150-sheet tray Paper Output: 100-sheet Interface: USB 2.0 Hi-speed</p> <p>Cartridges: Cartridge 725 (1,600 pages) Ships with 700 pages starter cartridge + Cable USB, AM/BM, 1.8 m, USB2.0 SVEN</p>
--	--	--	--	--	--	---

Semnat: _____ Numele, Prenumele: Slobozean Alexandr În calitate de: vinzator

Ofertantul: Andix SRL Adresa: mun. Balti str. Lescico 18/49

Specificații de preț (F4.2)

Numărul licitației: <u>ocds-b3wdp1-MD-1602075084494</u>	Data: „05.” noiembrie 2020	Alternativa nr.: _____
Denumirea LP : <i>Tehnica de calcul și a camerelor video, conform necesităților DÎTS a Primăriei mun.Bălți</i>		Lot: Lot: 1-18
		Pagina: 1 din 2

Cod CPV	Denumirea bunurilor	Unitatea de măsură	Cantitatea	Preț unitar (fără TVA)	Preț unitar (cu TVA)	Suma fără TVA	Suma cu TVA	Termenul de livrare/prestare
1	2	3	4	5	6	7	8	9
Lotul Nr.1 <i>LT</i> “D.Cantemir” 30213300-8	Calculator personal	buc	15	8520,00	10224,00	127800.00	153360.00	în termen de pînă la 14 zile după înregistrarea contractului la MF-TR Nord
Lotul Nr.2 <i>LT</i> “D.Cantemir” 30232110-8	Unitate multifuncțională cu funcții duplex	buc	2	6550,00	7860.00	13100,00	15720,00	în termen de pînă la 14 zile după înregistrarea contractului la MF-TR Nord
Lotul Nr.3 <i>LT</i> “D.Cantemir” 32333200-8	Registrator Video de Retea	buc	1	61400,00	73680,00	61400,00	73680,00	în termen de pînă la 14 zile după înregistrarea contractului la MF-TR Nord
	Camera IP	buc	25	1500,00	1800.00	37500,00	45000,00	în termen de pînă la 14 zile după înregistrarea contractului la MF-TR Nord
Lotul Nr.4 <i>LT</i> “D.Cantemir,, 30237240-3	Camera Web	buc	30	560,00	672,00	16800,00	20160.00	în termen de pînă la 14 zile după înregistrarea contractului la MF-TR Nord
Lotul Nr.5 <i>LT</i> “D.Cantemir” 32420000-3	Switch retea tip PoE:	buc.	1	9950,00	11940,00	9950,00	11940,00	în termen de pînă la 14 zile după înregistrarea contractului la MF-TR Nord
Lotul Nr.6	Cable UTP Cat 5e (cutia	cutie	10	444,20	533.04	4442.00	5330,40	în termen de pînă la 14 zile după

LT "D.Cantemir" 32572000-3	305m)							înregistrarea contractului la MF-TR Nord
Lotul Nr.14 Contabilitatea Centralizată 30213300-8	Calculator	buc	3	7450,00	8940,00	22350,00	26820,00	în termen de pînă la 14 zile după înregistrarea contractului la MF-TR Nord
Lotul Nr.15 Contabilitatea Centralizată 30232110-8	Multifuncțional (echivalent modelului - Canon i-Sensys MF237W + CRG737)	buc	3	5500,00	6600,00	16500,00	19800,00	în termen de pînă la 14 zile după înregistrarea contractului la MF-TR Nord
Lotul Nr.18 Școala sportiva nr.1 30232110-8	Imprimantă	buc	1	3650,00	4380,00	3650,00	4380,00	în termen de pînă la 14 zile după înregistrarea contractului la MF-TR Nord
Total:						313492,00	376190.40	

Notă:

- transportarea, livrarea și instalarea/montarea cu materiale de instalare se face de către întreprinderea câștigătoare din contul acesteia, în instituțiile de învățămînt (Gimnaziu A.I.Cuza, LT „D.Cantemir”, LT „G.Coșbuc”, școala primară nr.21 „S.Vangheli”, DÎTS mun. Bălți, Școala sportivă nr.1).
- pentru perioada de garanție, asistența tehnică și reparație (după caz) se face de către întreprinderea câștigătoare, din contul acesteia, inclusiv fiind suportate și cheltuielile de deplasare. Deservirea tehnică și înlăturarea defectelor se va efectua în termen de 1-2 zile după recepționarea cererii.
- pentru fiecare poziție se prezintă certificat de calitate cu termen de garanție pentru cel puțin 12 luni.

Semnat: _____ Numele, Prenumele: Slobozean Alexandr În calitate de: vinzator

Ofertantul: Andix SRL Adresa: mun. Balti str. Lesecico 18/49