



江苏苏青水处理工程集团有限公司

Jiangsu Suqing Water Treatment Engineering Group Co., LTD.

电话 (TEL): 0510-86339038

传真 (FAX): 0510-86336655

电邮 (EMAIL): suqingcz@suqing.com

网址 (WWW): www.suqing.com

地址: 江苏江阴河塘长青路 89 号

邮编: 214419

ADD: No.89 Changqing Road, Hetang, Jiangyin, Jiangsu, P.R.China/214419

Material Safety Data Sheet for 201x4 OH⁻

Issued: 1, Jan. 2026

1. Material-/ Preparation- and company name Jiangsu Suqing Water Treatment Engineering Group Co., Ltd.		
2. Composition / Ingredients	Percentage (%)	CAS No.
Polyvinyl benzyl trimethyl ammonium Hydroxide	25 ~ 57	69011-18-3
Water	43 ~ 75	7732-18-5
3. Possible dangers		
4. First Aid measures SKIN Contact: Remove product mechanically. Rinse skin with a lot of water. EYE Contact: Rinse open eyes with a lot of water. Consult doctor. Consult doctor after inhalation. After swallowing rinse mouth and drink a lot of water. Do not administer anything in case of unconsciousness or cramp. Consult doctor in case of indisposition.		
5. Fire fighting Extinguishing agents: CO ₂ foam, extinguishing powder, in case of big fires use waterspraybeam During fire fighting wear respirator with independent oxygen supply		
6. Measure in case of unintended release Clean mechanically and store in labelled and closed containers. Spilled product causes danger of slipping. Wear personnel protection equipment during work.		
7. Handling and storage Storage temperature between 5° C and 40° C Prevent of drying. Apply protection measures against electrostatic loading according To the equipment, handling and packaging of the product. Static loading lets the Material form into a ball. Sufficient ventilation necessary.		
8. Exposure limits and personnel protection equipment Eye protection: protective glasses Hand protection: protective gloves Follow the common safety measure with handling chemicals. Change dirty cloths. Wash Hands before breaks and end of work.		
9. Physical and chemical features 201x4 OH ⁻ Form: Spherical particle Color: Light yellow		

Jiangsu Suqing Water Treatment Engineering Group Co., Ltd. Tel: 0086-510-86339038,86336700
Huazhai Road, Hetang Town, Jiangyin ,Jiangsu, China. Fax: 0086-510-86336655,86331113
Email: suqingcz@suqing.com Http://www.suqing.com



江苏苏青水处理工程集团有限公司

Jiangsu Suqing Water Treatment Engineering Group Co., LTD.

电话 (TEL): 0510-86339038

传真 (FAX): 0510-86336655

电邮 (EMAIL): suqingcz@suqing.com

网址 (WWW): www.suqing.com

地址: 江苏江阴河塘长青路 89 号

邮编: 214419

ADD: No.89 Changqing Road, Hetang, Jiangyin, Jiangsu, P.R.China/214419

Smell:	a little smell
Melting temperature:	
Density:	1.04-1.08 g/ml
Apparent density:	0.65-0.75 g/ml
Solubility in water:	Insolubility
Flashing point:	
Ignition temperature:	
10. Stability and reactivity	
Thermal decomposition:	No thermal decomposition in case of appropriate handling and Storage.
Dangerous decomposition products:	No dangerous decomposition products in case of appropriate handling and storage. In case of fire or thermal decomposition development of CO, CO ₂ , SO ₂ , NO ₂ , and other toxic gases.
Dangerous reactions:	With strong oxidising agents are dangerous reactions possible. No dangerous reactions, if used appropriate.
11. Information about toxicology	
12. Ecology	
Due to insolubility in water of the product	no data available regarding toxicology. Do not spill in sour or any kind of water.
13. Disposal	
According to the local regulations (e.g. controlled burning).	Uncleaned package Materials have to be treated like the product itself.
14. Transport	
IMO IMDG CODE:	No dangerous material for transport.
15. Regulations	
SARA 313 INFORMATION:	To the best knowledge, this product contains no chemical subject to SARA Title III Section 313 supplier notification requirements
SARA HAZARD CATEGORY:	This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:
Not to have met any hazard category	
16. Miscellaneous	
No dangerous material for transport.	Frost-resistant down to 5° C. Keep separate from food.

江苏苏青水处理工程集团有限公司
JIANGSU SUQING WATER-TREATMENT
ENGINEERING GROUP CO., LTD

Jiangsu Suqing Water Treatment Engineering Group Co., Ltd. Tel: 0086-510-86339038, 86336700
Huazhai Road, Hetang Town, Jiangyin, Jiangsu, China. Fax: 0086-510-86336655, 86331113
Email: suqingcz@suqing.com Http://www.suqing.com