



'MADAM CORINNE ' ULTRA PAD CERTIFICATE OF ANALYSIS

| | |
|----------------------------------|---|
| NAME OF MANUFACTURER | : ARKAN GRUP SAGLIK URUNLERI A.S. |
| COUNTRY OF MANUFACTURE | : TURKEY |
| NAME OF PRODUCT | : "MADAM CORINNE " ULTRA NORMAL 8x48 |
| PIECES OF PACK | : 8 |
| SIZE | : NORMAL |
| DATE OF PRODUCTION | : 08.05.2020 |
| EXPIRATION DATE | : 08.05.2025 |
| LOT NO | : U-8 |
| THE AMOUNT OF SAMPLE FOR TESTING | : 10 PACKAGE |
| DATE OF QUALITY TEST | : 08.05.2020 |
| LABORATORY NAME | : BABY DIAPER and SANITARY PAD - QUALITY CONTROL LABORATORY |

CERTIFICATE OF ANALYSES

As a result of the below analysis, it has been seen that "MADAM CORINNE " **NORMAL** Ultra Pads doesn't contain any harmful substance to human health and this product is produced following row materials.

| | | | | |
|--------------------------|-----------------|----------------------------|----------------|-------------------------------|
| 1- Airlaid (Contain SAP) | 3- Hot Melt | 5- Perforated Polyethylene | 7- Ink | 9- Hydrophilic Transfer Layer |
| 2- Closing Tape | 4- Polyethylene | 6- Silicon Paper | 8- Single Wrap | |

RESULT OF ANALYSES

| | TARGET | AVERAGE | TEST RESULT MAX. | TEST RESULT MIN. |
|-----------------------|--------------|---------|------------------|------------------|
| PAD GRAMAJ | 5,21 (±1 gr) | 5,25 gr | 5,80 gr | 5,20 gr |
| SANITARY PAD DIAMETER | 165 (± 5 mm) | 165 mm | 166 mm | 163 mm |
| SANITARY PAD LENGHT | 240 (± 5 mm) | 240 mm | 236 mm | 235 mm |

RESULT OF ANALYSES

| TEST PARAMETERS | ACCEPTANCE LIMITS | RESULT |
|---|--|-----------|
| Classification | All materials used in the sanitary pad manufacture shall have no harmful effect during normal use. | Approved |
| | shall be made of an absorbent material which gives a feeling of comfort during use. | Approved |
| Filling | shall be free of protrusions, oil spots, dirty, or any other foreign matter, and shall have no harmful effect. | Approved |
| | shall be arranged in a way to allow the distribution of menstrual flow in the absorbent material, and prevent it from leaking to any side. | Approved |
| Porous fabric | This fabric, if present shall be placed between the filling and outer layer. | Approved |
| Base layer | Shall be a thin layer of plastic or any other leak-proof material that is placed at the back side of the pad. | Approved |
| Adhesive tapes | One or several lines of adhesive substances shall be made on the backt of the pad to secure it in place on the underwear when used. The adhesive shall be covered with a protective cover. | Approved |
| | The adhesive shall leave no traces on clothes when the pad is removed. | Approved |
| ABSORBENCY (LIQUID) | Overall absorbency shall not be less than 30 ml /pad | 30 ml |
| ABSORPTION TIME | ≤15 seconds | 8 seconds |
| Absorbency Capacity (ml) | No Leakage | 30 ml |
| PH | Ph shall vary between 5,5 and 9,5 according to International Standart ISO 6588-1 | 6,5 |
| ANAEROBIC/AEOROBIC BACTERIA COUNT(cfu/mg) | ≤10 cfu/mg | Absent |
| STAOHYLOCOCCUS AUREUS(cfu/mg) | Not Found | Absent |
| CANDIDA ALBICANS(cfu/mg) | Not Found | Absent |
| PSEUDOMONAS AUREGINOSA(cfu/mg) | Not Found | Absent |
| E-COLI(cfu/mg) | Not Found | Absent |

ARKAN GRUP SAGLIK URUNLERI A.S.
QUALITY CONTROL DEPARTMENT