

Horizontal Pulse Vacuum Autoclave

Application:

It can be widely used in department of stomatology and ophthalmology, operating room and other medical institutions. It is suitable for all wrapped or unwrapped solid instrument, A-class cavity instrument (dental hand-pieces and endoscopes), implantable instrument, dressing fabric and rubber tubes, etc.

Features:

- * Built-in efficient steam generator, microcomputer temperature control.
- * Equipped with printer to print date, time and process parameters.
- * Perfect four-level authority management system to avoid mis-operation.
- * Sterilization programs for fabric, instrument, rubber, liquid, cavity, B&D test, PCD test and leakage test.
- * Intelligent drying system to guarantee the residual humidity of instrument and dressing no more than 0.2% and 1% respectively.
- * Over-heat auto protection device, dual door safety lock device, over pressure relief valve, short circuit protection, and overpressure protection.
- * LCD displays temperature, pressure, time, running status, failure and warning code.
- * Double door optional.



Technical Parameters:

Model	BKQ-Z100(H)	BKQ-Z150(H)	BKQ-Z200(H)	BKQ-Z300(H)
Capacity	100L	135L	185L	300L
Chamber Size(mm)	φ400*850	φ500*710	φ500*950	φ632*1000
Chamber Material	SUS304			
Max Working Pressure	0.25Mpa			
Vacuum Limit	-0.08MPa			
Working Temp.	115~138℃			
Temp Accuracy	±0.1℃			
Consumption	11KW	11.5KW		18KW
Power Supply	380V, 50Hz			
External Size(L*W*H) mm	1250*730*1660	1110*750*1742	1350*750*1742	1400*890*1780
Package Size(L*W*H) mm	1450*1000*1950	1370*890*2060	1510*890*2060	1700*1050*2090
Gross Weight(kg)	310	470	540	830