



\*

,  
-

;

,

**BKC-TL5M**

5000r/

4390xg

4\*500

± 1%

20 /

1 ~ 999

AC 220V, 50 /60

550w

65dB

( \*

620\*450\*350

\* )

( )

45

( )

60

**BKC-TL6M**

6000 /

5310xg

2000

± ± 1%

20 /

0 ~ 999

AC 220V, 50 /60

750W

65dB

±

560\*460\*390

54

70

**BIOBASE<sup>®</sup>**



- \* :  
centrifugal chamber.
- \* - -button programming , , .
- \* Alarm monitoring , f .
- \* Centrifugal speed, , .

BKC-TL4B

6\*50

4000 /

2250xg

1-99

± 2%

65dB

		150W	
		AC110/220	, 50/60
	( * * )	450*370*280	
	( )	18	
	( * * )	470*400*375	
	( )	22	
		6*50	
4M0001		15 , 20 , 5/7	
		4*50	
4M0002		15 , 20 , 5/7	
		: 12*20	
4M0003		5 , 10 , 5/7	
		: 12*15	
4M0004		1,5 , 5 , 5/7	
	Anqle	8*15	
4M0005		1,5 , 5 , 10ml,57	
		24*10	
4M0006		1,5 , 5 , 5/7	
		18*10	
4M0007		1,5 吋	5 , 5/7
		12*10	
4M0008		1,5 , 5 , 5/7	
4M0009		: 12*1,5/2	