

A5 EVO 50



Watch the video on youtube:
www.youtube.com/fasavideo

Standard equipment



• 5.511.1097
 PPL brush Ø 483 mm - 19"



• 4.508.X468
 Front squeegee blade L.830 mm Shore 40 Th. 2.5 mm
 • 4.508.X467
 Rear squeegee blade L.870 mm Shore 40 Th. 3 mm



• 0.108.0042
 On-board Battery charger CBHD1 24V 10A
 only for model code:
 8.527.0007 - 8.527.0008
 8.527.0013 - 8.527.0046



• 0.107.0054
 Maintenance free battery 12V 75Ah BT DC 5.5
 only for model code:
 8.527.0013 - 8.527.0046

Other available versions:

- 8.527.0007 - A5 Evo 50 B with battery charger
- 8.527.0013 - A5 Evo 50 B with batteries and battery charger
- 8.527.0046 - A5 Evo 50 BT with batteries and battery charger with traction.

A5 EVO 50

- Very compact scrubbing machines suitable to work for the maintenance cleaning of limited-size areas (up to 1.500 m²)
- Especially suitable for cleaning: car shops, sales points, gym, health care
- Control panel with operator presence safety system
- Low level battery indicator: brush/vacuum and traction progressive cut off
- Solution water filter and solenoid valve (battery model only)
- Easy access to the battery compartment
- Quick drain and easily inspectable recovery tank
- Non-marking wheels
- Roto-molded polyethylene tanks, shock and acid resistant
- The lower tank also serves as battery compartment
- Low noise operation thanks to the protected positioning of vacuum motor.

	A5 EVO 50 E	A5 EVO 50 B	A5 EVO 50 BT
Code	8.527.0005	8.527.0006	8.527.0008*
Power supply	230V~50Hz	24V DC	24V DC
Equipped with	-	-	Batt. charger
Scrubbing width	500 mm	500 mm	500 mm
Squeegee width	800 mm	800 mm	800 mm
Max working capacity	2000 m ² /h	2000 m ² /h	2000 m ² /h
Detergent tank capacity	44 l.	44 l.	44 l.
Recovery tank capacity	50/60 l.	50/60 l.	50/60 l.
Traction type	mechanical	mechanical	automatic
Brush/Vacuum motor power	550/1000 W	550/400 W	550/400 W



Powerful gearmotor; metal brush plate with integrated plastic splash guard/bumper.

The outflow of the detergent solution is controlled by a solenoid valve. The actuation of the solenoid valve is operated by the control lever, avoiding the detergent solution outflow when the brush is stopped during the interruptions of work.



Renovated squeegee with new pressure adjusting system. The squeegee blades are easily replaceable without the use of tools. Quick and easy squeegee coupling through the two large knobs; the squeegee is released without any damage in the

event of accidental impact. Easy and intuitive controls. The outflow of the cleaning solution is easily controlled using the mechanical lever placed on the control panel. Inspectable mesh filter to trap any existing solid body in the cleaning solution.



Optional accessories:



- 2 x 0.107.0002
Tubular battery Pb-acid
12V 118Ah C5



- 2 x 0.107.0063
GEL Battery 12 MFP 105
12V 105Ah C5



- 4.508.1178 Polyurethane
front blade L830 TH. 3
- 4.508.1177 Polyurethane
rear blade L870 TH. 4



- 5.511.1098
Synex brush Ø 483 mm-19"
- 5.511.1128
PPL 0,03 brush Ø 483 mm-19"
- 5.511.1206
PES brush Ø 483 mm - 19"



- 5.511.1099
EWU pad driver Ø 483
mm-19"



- 6.508.0034
Abrasive pad Ø 483 mm-19"
- beige (5 pcs.)
- 6.508.0041
Abrasive pad Ø 483 mm-19"
- green (5 pcs.)
- 6.508.0048
Abrasive pad Ø 483 mm-19"
- black (5 pcs.)



- 4.512.0068
Extension electric cord 15 m
with Schuko plug