

Karadenizliler Mah. Ordulu Cad. No: 82, 41140 PK334 Başıskele KOCAELi / TÜRKIYE Tel: 444 78 52 (444 - PTKB) +90 (262) 349 37 90 / 91 +90 (262) 349 25 50 / 51 Fax: +90 262 349 37 59

petekboru.com.tr info@petekboru.com.tr

MILLTEST CERTIFICATE EN 10204 3.1 Date/Tarih

: 23.03.2023

Certificate/Sertifika No : 5439

Customer/Müşteri: S.C. NIMFA - COM S.R.L.

Standart No/Norm:

TS EN 10217-5

Order No-LC No/Siparis No: 6681

Pipe Type/Boru Tipi: SAWH

| Item Pos. | Dimensions OdxWtxL | Pieces | Total Length |  |  |  |
|-----------|--------------------|--------|--------------|--|--|--|
| Sira No:  | Ölçüler            | Adet   | Metre        |  |  |  |
| 1         | 720.00 X 10.00     | 4      | 28.07        |  |  |  |

| BD | GBT | NDT | VD | US |
|----|-----|-----|----|----|
| 30 | OK  | OK  | OK | ОК |

| Item Pos. | Bant No-Heat No | ٧   | Cu   | Ni  | Cr  | Мо  | Al | Nb   | Ti     | S   | Р   | Mn    | Si   | C    | Steel Grade | HT      | Material  |           | S. Hill | Weld      |           |       |
|-----------|-----------------|-----|------|-----|-----|-----|----|------|--------|-----|-----|-------|------|------|-------------|---------|-----------|-----------|---------|-----------|-----------|-------|
| Sira No:  | Döküm No:       |     | 27.0 |     |     |     |    | X100 | 110.00 |     |     |       |      |      | Kalite      | bar/sec | Re(N/mm²) | Rm(N/mm²) | A (%)   | Re(N/mm²) | Rm(N/mm²) | A (%) |
| 1         | 235402          | 0,1 | 1,6  | 2,9 | 2,2 | 0,0 | -  | 0,0  | 0,1    | 0,3 | 1,6 | 108,7 | 18,5 | 15,7 | P265GH TC1  | 46/10   | 406,1     | 532,7     | 32,9    |           | 550,3     | -     |

OD: Dış Çap / Outside Diameter

Re: Akma dayanımı / Yield Stress

WT: Et Kalınlığı / Wall Thickness

Rm: Çekme Dayanımı / Tensile Strength

BD: Havşa Acısı / Bevel Degree

A%: Uzama / Elongation

VD: Goz/Ebat Kontrol / Visual Dimension

GBT:Eğme testi/Guided Bend Test

HT: Hidrotest / Hydrostatic Test

N.D.T.:Tahribatsız test / Non-Destructive Testing

US: Ultrasonic test as per TS EN ISO 10893-11







