Image Gallery


High quality imaging across a broad clinical range that includes abdominal, cardiac, and vascular applications.

See the full Image Gallery

http://www.hitachi.com/businesses/ healthcare/products-support/us/ arietta50/contents04.html








Dual CF

Free Angular M-mode (FAM)*







Doppler Auto Trace

Auto IMT*

Specifications

eFLOW

Dimensions	(W)531×(D)767×(H)1317-1567mm
Weight	64kg (Only for main body)
Display	21.5 inch LCD monitor
Power Requirement	AC100~120V, AC200~240V, 50/60Hz, Max. 470VA
Battery*	Available

Learn more about the **ARIETTA 50**

http://www.hitachi.com/businesses/ healthcare/products-support/us/ arietta50/index.html



*Option

Innovating Healthcare, Embracing the Future

For a society where all can enjoy a secure, safe, healthy way of life, Hitachi delivers innovation for implementing healthcare services tailored to individuals

- ARIETTA is a registered trademark or trademark of Hitachi, Ltd. in Japan and other countries.
 Specifications and appearance may be subject to change for improvement without notice.
- For proper use of the system, be sure to read the operating manual prior to placing it into service.









@Hitachi, Ltd.

www.hitachi.com/healthcare Printed in Japan 2019-01-XX-(H)

HITACHI Inspire the Next

ARIETTA 50



The Next Stage in Usability

This entry model of the ARIETTA series invites easy operation from beginners through experts. Its outstandingly easy-to-view 21.5 inch monitor and intuitive, user-friendly operability will bring you to the "Next Stage".





Simplified Operating Console

Minimalized layout includes only the necessary controls. Reduces time searching for the right button, offering a more pleasant operating experience.



Silky Image Processing (SIP)

This adaptive image filter has further evolved to reduce speckles and boost edge enhancement, generating clearer images for easier interpretation.





Carefree




User-friendly Interface

Select an examination area from the illustration to start operation.

Scan Using a Previous Setting

Choose a patient's previously-acquired image and the system will adjust to the same exam settings; invaluable for follow-up comparisons.



After Gain Adjustment

Auto Optimizer

Images can be adjusted with a single keystroke: B-mode gain, baseline position and velocity range of the Doppler waveform are all optimized.

Video Introduction of Features

Watch the video introduction now http://www.hitachi.com/ businesses/healthcare/ products-support/us/ arietta50/ contents05.html



Clear



21.5 inch Widescreen Monitor

The high contrast LCD monitor with a wide field of view displays images with high sensitivity and resolution, reducing patient-dependent image variability.

Palm Rest

Touch Screen Panel The touch screen panel is mounted at

Easy-to-use

a comfortable and convenient angle.

The screen's layout is customizable by clinical application, allowing for intuitive operation.

Gel Warmer*

The gel warmer is conveniently inclined for easy access.

Adjustable Panel Height/ Rotation

It is possible to adjust the height and rotation of the operating console to best suit the operator and examination to be performed.



Battery*

Battery operation enables the system to be moved to a new location without powering it down, so that operation can be resumed immediately.

