

Certificate of Analysis


(according to EN ISO 3452-2)

Product: NORD-TEST Penetrant U88
 Ref.-No.: 121.300.201 – 500 ml aerosol can
 Batch-No.: 39826
 Shelf life: 03/2026

Individual Quality	Determination acc. to the ISO 3452-2 Section:	Requirements	Results
Appearance	6.1	Shall be same as that of the type test material	Requirement met
Sensitivity	6.2	Penetrant system II A e / C2 e / E e NORD-TEST Reiniger U87, Ch. Nr.: R39838 NORD-TEST Entwickler U89, Ch. Nr.: R39998	Sensitivity level II
Density	6.3	Max. $\pm 5\%$ of the sample test material	0,8934 g/cm ³ requirement met
Viscosity	6.4	Max. $\pm 10\%$ of the sample test material	11,2 mm ² /s bei 20°C requirement met
Flash Point in a closed Cup	6.5	Max. 5°C below the sample test material	98°C, requirement met
Corrosive Performance	6.11	For Aluminium alloy AW 7075 Magnesium alloy AZ -31B and steel 30CrMo4: No stains, pitting, sings of corrosion (with a 10-fold magnification)	requirement met
Sulphur content	6.12	< (200 $\pm$ 10) ppm	20 ppm requirement met
Halogen content	6.12	< (200 $\pm$ 10) ppm	20 ppm requirement met

Heidgraben, 25.03.2022

Dipl.-Ing A. AL-Ajeel



Prof.h.c. Dr.h.c. N. Riess

