


Angiographic Syringe



COILED
Y-CONNECTING TUBE



QUICK FILL TUBE



SPIKE



COILED
CONNECTING TUBING

CE 0197 FCS

EN ISO: 13485: 2016/AC: 2012

REF	Model	Description
AT2201	CT-200-M	Used for CT: MEDRAD MCT&PLUS:OP-100; VCT610; ECT710
AT2202	CT-200-M2	Used for CT: MEDRAD STELLANT
AT2203	CT-200/200-M2	Used for CT: MEDRAD STELLANT D
AT2204	CT-200-L	Used for CT: LIBEL-FLARSHEIM CT9000&CT9000 ADV
AT2205	DSA-150-L	Used for DSA: LIBEL-FLARSHEIM ANGIOMAT 6000
AT2206	DSA-150-M	Used for DSA: MEDRAD MARK V MARK V PROVIS
AT2207	DSA-200-M	Used for DSA: MEDRAD MARK V MARK V PROVIS
AT2208	MRI-65/65-M	Used for MRI: MEDRAD SPECTRIS MR
AT2209	CT/DSA-150-L	Used for CT&DSA: LIBEL-FLARSHEIM CT&DSA:ANGIOMAT IIIUMENA
AT2210	MRI-60/200-MED	Used for MRI: MEDTRON MRI
AT2211	CT-200-MED	Used for CT: MEDTRON ACCUTRON CT
AT2212	CT-200-E	Used for CT: EZEM EMPOWER CT
AT2213	CT-100-N	Used for CT: NEMOTO KYORINDO A-25;A-60
AT2214	CT-200-N	Used for CT: NEMOTO KYORINDO A-25;A-60
AT2215	DSA-120-N	Used for DSA: NEMOTO KYORINDO NEMOTO 120S
AT2216	MRI-65/115-M	Used for MRI: MEDRAD SPECTRIS
AT2217	CT-200/200-M	Used for CT: MEDRAD MCT&PLUS:OP-100;VCT610;ECT710
AT2218	CT-200/200-L	Used for CT: LIBEL-FLARSHEIM OPTIVANTAGE DUAL-HEAD
AT2219	MRI-60/60-L	Used for MRI: LIBEL-FLARSHEIM OPTISTAR
AT2220	CT-100/100-N	Used for CT: NEMOTO KYORINDO A-25;A-60
AT2221	CT-100/200-N	Used for CT: NEMOTO KYORINDO A-25;A-60
AT2222	CT-200/200-MED	Used for CT: MEDTRON ACCUTRON CT-D

Angiographic Syringe



REF	Model	Description
AT2223	CT-200/200-E	Used for CT: EZEM EMPOWER D
AT2224	CT-190/190-M	Used for CT: MEDRAD SALIENT
AT2225	CT-190-M	Used for CT: MEDRAD SALIENT
AT2226	MRI-60/60-MED	Used for MRI: MEDTRON MRI
AT2227	DSA-150-M2	Used for DSA: MEDRAD MARK 7 ARTERION
AT2228	CT-200/200-N	Used for CT: NEMOTO KYORINDO A-25;A-60

ACCESSORIES

REF	Length (cm)	Description
AT2299	150	Pressure Connecting Tubing 150cm x 350PSI
AT2298	150	Pressure coiled tubing 150cm x350PSI with Y connector and 1 check valve
AT2297	150	Pressure coiled tubing 150cm x350PSI with Y connector and 2 check valve
AT2230	150	Pressure coiled tubing 150cm x350PSI with Y connector
AT2242	250	Pressure coiled tubing 250cm x350PSI with Y connector and 1 check valve
AT2105	150	High pressure tubing 1200PSI x150cm,used for DSA