

Specificații tehnice (F4.1)

[Acest tabel va fi completat de către ofertant în coloanele 3, 4, 5, 7, iar de către autoritatea contractantă – în coloanele 1, 2, 6, 8]

| |
|---|
| Numărul procedurii de achiziție_ ocds-b3wdp1-MD-1565355896335 din_20.08.2019 |
| Denumirea procedurii de achiziție: Tehnica de calcul pentru instituțiile din subordinea DETS Centru |

| Cod CP V | Denumirea bunurilor | Modelul articolului | Țara de origine | Producătorul | Specificarea tehnică deplină solicitată de către autoritatea contractantă | Specificarea tehnică deplină propusă de către ofertant | Standarde de referință |
|-----------------------|--|---------------------|-----------------|--------------|---|---|------------------------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| | Bunuri | | | | | | |
| 30200000 -1 | Tehnica de calcul pentru, instituțiile din subordinea DETS Centru | | | | | | |
| | Calculator | Computer de Birou | RM | Triomac SRL | Calculator: CPU socket S1151, min frecvența 3.7GHz (2C/4T), 4MB Cache, 14nm 54W, Cooler CPU up to 95W, 120x120x25mm, 1600rpm, 26.1dBA, 54.25CFM, 3 pin, Hydro Bearing, D.A.C MB Socket 1151, cipset min Z370, Dual 4xDDR4-4000, CPU Intel graphics, HDMI, 3xPCIe X16, 6xSATA3, RAID, 1xM.2, ALC887 HDA, GbE LAN, 6xUSB3.1, RGB Fusion, ATX; RAM DDR4 min8Gb PC19200, 2400MHz, CL17, 1.2V ; 2.5" SSD min 240Gb (R/W:550/540MB/s, Controller Phison PS3110-S10, NAND MLC) ; DVDRW | CPU Intel Pentium G5400 Gold, S1151, 3.7GHz (2C/4T), 4MB Cache, Intel UHD Graphics 610, 14nm 54W, DEEPCOOL Cooler "GAMMA ARCHER", Socket 775/1150/1151/1155 & AM4/FM2/AM3+, up to 95W, 120x120x25mm, 1600rpm, 26.1dBA, 54.25CFM, 3 pin, Hydro Bearing, D.A.C. (Double Airflow Channel) GIGABYTE Z370P D3, Socket 1151, Intel® Z370 (9th/8th Gen | STAS |

| | | | | | | | |
|--|------------------|------------------------|-------|----|--|---|------|
| | | | | | <p>Drive Internal, Super-Multi DVDR+24x/-24x, RW+8x/-6x, DL+8x, RAM12x, SATA; ATX Case, 24 pin, 2xSATA, 12cm fan, 1xUSB3.0, 2xUSB2.0 / HD Audio; PSU min500W, ATX 2.3.1, Passive PFC, 120mm fan,+12V (32A), 20+4 Pin, 4x SATA, 1xPCI-E 6+2 Pin, 2x Peripheral; Multimedia Keyboard cu eng si rus, black; Mouse Optical USB black (keyboard si Moue sa fie de acelasi producator); monitor min22.0" black min2ms, 20M:1, 250cd, 1920x1080, VGA, DVI, HDMI, Audio Line-out, Speakers 2 x 2W, VESA)</p> | <p>CPU), Dual 4xDDR4-4000, CPU Intel graphics, HDMI, 3xPCIe X16, 6xSATA3, RAID, 1xM.2, ALC887 HDA, GbE LAN, 6xUSB3.1, RGB Fusion, ATX 8GB DDR4-2400 GOODRAM, PC19200, CL17, 1.2V 2.5" SSD 240GB GOODRAM IRIDIUM GEN.2, SATAIII, Sequential Reads: 550 MB/s, Sequential Writes: 540 MB/s, Maximum Random 4k: Read: 61,000 IOPS / Write: 87,000 IOPS, Thickness- 7mm, Controller Phison S11, MLC NAND flash DVD-RW Drive LG "GH24NSD1" SATA Black, Bulk PSU XILENCE XP500R7, 500W, "RedWing R7" Series, ATX 2.3.1, Passive PFC, 120mm fan,+12V (32A), 20+4 Pin, 4x SATA, 1xPCI-E 6+2 Pin, 2x Peripheral, Black Carcasa Magnum H650R , Midi-Tower, USB2.0x2, HD Audio, ATX/mATX, black Tastatura Spacer QWERTY 104 keys+11 Multimedia keys, anti-spill, USB SPKB-169 Mouse optic Spacer SPMO-M11 22.0" AOC LED 22E1D Matte Black (2ms, 20M:1, 250cd, 1920x1080, VGA, DVI, HDMI, Audio Line-out, Speakers 2 x 2W, VESA)</p> | |
| | Multifunctionale | LaserJet Pro MFP M130a | China | HP | <p>MFD Mono Printer/Copier/Scanner, A4, 2400x600 dpi, 22ppm,128Mb, Scan 9600x9600dpi-24 bit, Paper Input (Standard) 150-sheet tray, USB 2.0, Max.10k pages per month + 1Cartus Original de rezerva adaugator</p> | <p>HP LaserJet Pro MFP M130a Print/Copy/Scan, White, up to 22ppm, 128MB, 2-line LCD, 600dpi, up to 10000 pages/monthly, HP ePrint, Hi-Speed USB 2.0, CF217A (~1600 pages 5%) HP CF217A TONER CARTRIDGE 17A BLACK (1600 pages) for M130 Series, M102 Series</p> | STAS |

| | | | | | | | |
|--|-------------------|---------------------------------|-------|------------------------|--|--|--|
| | | | | | <p>SET VIDEOPROIECTOR + SUPORT PROIECTOR (cu montare pe perete, Inaltime max de la tavan/perete 130, Inaltime min de la tavan/perete 77.2, cu inclinare verticala, culoare alba) + TABLA Interactiva + TAVITA + laptop+ Mouse fara fir(Grey, Optical Mouse for Notebooks, Nano receiver, bateria sa tina minm 12luni) "Cerinte tehnice proiector: Display technology DLP Resolution XGA (1024x768) Brightness 3,500 lumens Contrast ratio 22,000:1 Native aspect ratio 4:3 Aspect ratio - compatible 16:9 Keystone correction - vertical +/-40° Horizontal scan rate 15.38 ~ 91.15Khz Vertical scan rate 50 ~ 85(120 for 3D)Hz Uniformity 75% Lamp min watts 203 Lamp life (hours) min 6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+); Optical Projection distance (m) 0.4m - 3.1m Focal length (mm) 7.15 Native offset 115%: conectare inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A" Cerinte tehnice tabla interactiva: "Diagonala proiectiei: 85"" Raport de aspect: 4:3 Tehnologie optica cu 2 camere Dual Touch: 2 puncte de atingere simultana Tehnologia de touch OITT (Optical Imaging Touch Technology) Viteza 130fps Puncte de atingere 2 touch Acuratetea touch-ului 3.0 mm (suprafata sensibila la touch >95%) Timp de raspuns ≈ 8 ms; Actualizare firmware Da Tip dispozitiv Touch (cu suport pentru gesturi per OS) sau mouse (click, misca, dublu click, click dreapta) Calibrare 4-</p> | <p>SET VIDEOPROIECTOR + SUPORT PROIECTOR (cu montare pe perete, Inaltime max de la tavan/perete 130, Inaltime min de la tavan/perete 77.2, cu inclinare verticala, culoare alba) + TABLA Interactiva + TAVITA + laptop+ Mouse fara fir Logitech M185(Grey, Optical Mouse for Notebooks, Nano receiver, bateria sa tina 12luni) "Proiector Optoma X308STe: Display technology DLP Resolution XGA (1024x768) Brightness 3,500 lumens Contrast ratio 22,000:1 Native aspect ratio 4:3 Aspect ratio - compatible 16:9 Keystone correction - vertical +/-40° Horizontal scan rate 15.38 ~ 91.15Khz Vertical scan rate 50 ~ 85(120 for 3D)Hz Uniformity 75% Lamp min watts 203 Lamp life (hours) min 6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+); Optical Projection distance (m) 0.4m - 3.1m Focal length (mm) 7.15 Native offset 115%: conectare inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A" Tabla interactiva EVOBOARD IB85(language-RO): "Diagonala proiectiei: 85"" Raport de aspect: 4:3 Tehnologie optica cu 2 camere Dual Touch: 2 puncte de atingere simultana Tehnologia de touch OITT (Optical Imaging Touch Technology) Viteza 130fps</p> | |
| | Tablă interactivă | X308STe, IB85, Inspiron 15 3000 | China | Optoma, Evoboard, Dell | | STAS | |

| | | | | | | |
|--|--------------|--|--|--|---|---|
| | | | | | <p>puncte, 16-puncte, 25-puncte, fara alunecare Acuratetea touch-ului 3.0 mm (suprafata sensibila la touch >95%) Sistem de operare Windows XP/ Vista/ 7/8/8.1/10, Linux (V.2.4 sau mai sus), Android (V.4.0 sau mai sus), Max OS (V10.4 sau mai sus) ; Metoda de atingere Deget sau alt obiect opac Transmisiune 100% fara sticla (sau panou de tabla) Rezistenta touch-ului nelimitat; Rezolutie USB raportata 32768x32768 Tip de interfata USB 2.0 (viteza totala) Plug & Play Suportat HID Suportat Alimentare Prin USB Necesara de energie DC5V±5% @500mA Consum de energie 5V Consum mediu de energie <2.5W, @5V"</p> <p>Cerinte tehnice laptop minim 15.6" HD cpu min 4xCore, 1.1-2.7GHz, RAM min 4GB DDR4, SSDmin 128GB M.2 PCIe SSD,video Graphics 605, DVDRW, CardReader, WiFi-N/BT4.1, 3cell, HD720p Webcam, 2.2kg</p> | <p>Puncte de atingere 2 touch Acuratetea touch-ului 3.0 mm (suprafata sensibila la touch >95%) Timp de raspuns ≈ 8 ms; Actualizare firmware Da Tip dispozitiv Touch (cu suport pentru gesturi per OS) sau mouse (click, misca, dublu click, click dreapta) Calibrare 4-puncte, 16-puncte, 25-puncte, fara alunecare Acuratetea touch-ului 3.0 mm (suprafata sensibila la touch >95%) Sistem de operare Windows XP/ Vista/ 7/8/8.1/10, Linux (V.2.4 sau mai sus), Android (V.4.0 sau mai sus), Max OS (V10.4 sau mai sus) ; Metoda de atingere Deget sau alt obiect opac Transmisiune 100% fara sticla (sau panou de tabla) Rezistenta touch-ului nelimitat; Rezolutie USB raportata 32768x32768 Tip de interfata USB 2.0 (viteza totala) Plug & Play Suportat HID Suportat Alimentare Prin USB Necesara de energie DC5V±5% @500mA Consum de energie 5V Consum mediu de energie <2.5W, @5V"</p> <p>laptop DELL Inspiron 15 3000 Platinum Silver (3582), 15.6" HD (Intel® Pentium® Silver N5000, 4xCore, 1.1-2.7GHz, 4GB (1x4) DDR4, 128GB M.2 PCIe SSD, Intel® UHD Graphics 605, DVDRW, CardReader, WiFi-N/BT4.2, 3cell, HD720p Webcam, RUS, Ubuntu, 2.2 kg)</p> |
| | TOTAL | | | | | |

Semnat: _____ Numele, Prenumele: Constantin Alexandru În calitate de: director
Ofertantul: Triomac SRL Adresa: Orhei, str Stefan cel Mare 3, ap 16

Specificații de preț (F4.2)

[Acest tabel va fi completat de către ofertant în coloanele 5,6,7,8, iar de către autoritatea contractantă – în coloanele 1,2,3,4,9,10]

| |
|---|
| Numărul procedurii de achiziție _ocds-b3wdp1-MD-1565355896335 din 20.08.2019 |
| Denumirea procedurii de achiziție: Tehnica de calcul pentru instituțiile din subordinea DETS Centru |

| Cod CPV | Denumirea bunurilor | Unitatea de măsură | Cantitatea | Preț unitar (fără TVA) | Preț unitar (cu TVA) | Suma fără TVA | Suma cu TVA | Termenul de livrare | Clasificație bugetară (IBAN) |
|-------------------|--|--------------------|------------|------------------------|----------------------|---------------|-------------|--|------------------------------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| | Bunuri | | | | | | | | |
| 30200000-1 | Tehnica de calcul pentru, instituțiile din subordinea DETS Centru | | | | | | | 10-15 de la înregistrarea contractului | |
| | Calculator | buc | 19 | 7600.00 | 9120.00 | 144400.00 | 173280.00 | | |
| | Multifunctionale | buc | 6 | 3316.67 | 3980.00 | 19900.00 | 23880.00 | | |

| | | | | | | | | | |
|--|--------------------|-----|---|----------|----------|------------|------------|--|--|
| | Tablă interactivă, | set | 1 | 31200.00 | 37440.00 | 31200.00 | 37440.00 | | |
| | TOTAL | | | | | 195 500.00 | 234 600.00 | | |

Semnat: _____ Numele, Prenumele: Constantin Alexandru În calitate de: director
Ofertantul: Triomac SRL Adresa: Orhei, str Stefan cel Mare 3, ap 16