



# NetApp Solution Technical Report

Manually Designed Solution

Report Generated:

12-Jan-2026

**Project ID:**

fe24a7ac

# TABLE OF CONTENTS

- 1 Business Requirements..... 3**
- 2 Solution Summary ..... 4**
  - 2.1 Proposed Solution Summary .....4
- 3 Solution Details..... 5**
  - 3.1 System Details .....5
  - 3.2 Environmental Details .....6
  - 3.3 Storage Availability Zone: netapp1/netapp2.....7
  - 3.4 Storage Availability Zone .....9
  - 3.5 Drive Calculation Summary.....10
  - 3.6 Workload Descriptions .....11
- 4 Environmental Certifications ..... 12**
  - 4.1 Product Carbon Footprint.....12
  - 4.2 Statements & Certifications.....12
- 5 Copyright ..... 13**


# 1 Business Requirements

*[Use this section to document the customer's high-level business requirements]*

## 2 Solution Summary

### 2.1 Proposed Solution Summary

This is a summary of what the proposed solution will deliver.

|  |  |   |
|--|--|---|
| <b>THROUGHPUT</b>  | <b>RAW CAPACITY</b>                                      | <b>STORAGE EFFICIENCY***</b>  |
| 300,000 IOPS / 4,687.50 MB/s   | 275.4 TB   | 2 : 1   |
| <b>AVERAGE UTILIZATION</b>   | <b>USABLE CAPACITY</b>                                   | <b>EFFECTIVE CAPACITY***</b>  |
| 65.25%   | 197.51 TiB   | 395.0248 TiB  |
| <b>MAXIMUM THROUGHPUT*</b>   | <b>RAW CAPACITY HEADROOM**</b>                           | <b>USABLE VS EFFECTIVE</b>  |
| 460,148 IOPS / 7,189.81 MB/s   | 1,560.6 TB   |  197.51 TiB<br>395.0248 TiB  |
| *assumes best practice configuration of aggregates and workload to aggregate mapping | **assumes future expansion using drives of same capacity | ***assumes use of storage efficiency technologies like compression and deduplication<br><br>***Lowest efficiencies have been applied to unused capacity within the cluster. |

Note:Usable and effective capacity is calculated and reported in base-2 format which aligns with values reported in ONTAP CLI, Storage Manager, and Unified Manager. It should be noted that ONTAP CLI displays base-2 capacity values, but labels these values using base-10 descriptors (e.g. GB/TB/PB).

| CONFIGURATION            |                  |                              | ENVIRONMENTAL |                                 |
|--------------------------|------------------|------------------------------|---------------|---------------------------------|
| <b>Model:</b>            | ASA A50A         | <b>OnboardEthernetPorts:</b> | 0             | <b>Rack Units:</b> 2 U          |
| <b>Nodes:</b>            | 2                | <b>Onboard UTA2Ports:</b>    | 0             | <b>System Weight:</b> 59.00 lbs |
| <b>Total Drives:</b>     | 18               | <b>OnboardSASPorts:</b>      | 0             | <b>AC Power:</b> 854.47 W       |
| <b>Drive Type:</b>       | 15.3 TB NVMe SSD | <b>Expansion Slots:</b>      | 8             | <b>Current Draw:</b> 4.34 A     |
| <b>Cluster Switches:</b> | N/A              | <b>StgeSwitches:</b>         | N/A           | <b>BTU/hr:</b> 2916.23          |

### 3 Solution Details

#### 3.1 System Details

For rack elevation, please refer to the Storage Solution SVG Diagram

cluster1: netapp1/netapp2

| Bill Of Materials          |                                    |              |             | Total |
|----------------------------|------------------------------------|--------------|-------------|-------|
|                            | Description                        |              | Part Number | Qty   |
| Systems                    |                                    |              |             |       |
|                            | ASA A50A w/ 18x15.3TB NVMe SSD SED | 9.17.1 ONTAP | X4028A      | 1     |
|                            | Grand Total                        |              |             | 1     |
| Storage                    |                                    |              |             |       |
|                            | Grand Total                        |              |             | 0     |
| Adapter Cards/ Flash Cache |                                    |              |             |       |
|                            | Grand Total                        |              |             | 0     |

### 3.2 Environmental Details

Line Voltage: 220

| System Components  | Qty | Rack Units | Current (Amps) |       | AC Power (Watts) |          | AC Power (VA) |          | Thermal Rating (BTU/hr) |          | Power (kWh/year) |           |
|--|-----|------------|----------------|-------|------------------|----------|---------------|----------|-------------------------|----------|------------------|-----------|
|  |     |            | Typical        | Worst | Typical          | Worst    | Typical       | Worst    | Typical                 | Worst    | Typical          | Worst     |
| ASA A50A w/ 18x15.3 TB NVMe SSDX4028A( 2xControllers, 1xChassis) | 1   | 2          | 4.34           | 6.97  | 854.47           | 1,377.14 | 899.44        | 1,449.62 | 2,916.23                | 4,700.05 | 7,490.12         | 12,071.75 |
| Total  | 1   | 2          | 4.34           | 6.97  | 854.47           | 1,377.14 | 899.44        | 1,449.62 | 2,916.23                | 4,700.05 | 7,490.12         | 12,071.75 |

Median Power Usage

| System Components   | Qty | Median Current (Amps) | Median AC Power (Watts) | Median AC Power (VA) | Median Thermal Rating (BTU/hr) | Median Power (kWh/year) |
|---|-----|-----------------------|-------------------------|----------------------|--------------------------------|-------------------------|
| ASA A50A w/ 18x15.3 TB NVMe SSDX4028A(2xControllers, 1xChassis) | 1   | 4.34                  | 854.47                  | 899.44               | 2,916.23                       | 7,490.12                |
| Total   | 1   | 4.34                  | 854.47                  | 899.44               | 2,916.23                       | 7,490.12                |

Note: Median power is based on actual power numbers reported by install base systems of similar configuration and represent the midpoint where half of the similar configurations consume less power and the other half consume more power. Typical and Worst-case power numbers are calculated based on product specifications and spot checked for accuracy. Typical power values are used when median power values are not available.

### 3.3 Storage Availability Zone: netapp1/netapp2

The information below provides details on the layout of the physical storage of proposed systema and allocation of capacity.

| RAID Group | Devices          | Total | Data | Parity | Spare |
|------------|------------------|-------|------|--------|-------|
| raidgroup1 | 15.36TB NVMe SSD | 17    | 15   | 2      | 0     |
| Spare      | 15.36TB NVMe SSD | 1     | 0    | 0      | 1     |
|            |                  | 18    | 15   | 2      | 1     |

|        | Capacity (TiB) <sup>1</sup> | Capacity (TB) <sup>2</sup> | Percentage (%) |
|--------|-----------------------------|----------------------------|----------------|
| Usable | 197.51                      | 217.16                     | 78.85%         |
| Root   | 0.75                        | 0.82                       | 0.30%          |
| WAFL   | 10.48                       | 11.52                      | 4.18%          |
| Parity | 27.83                       | 30.60                      | 11.11%         |
| Spare  | 13.92                       | 15.31                      | 5.56%          |
| Total  | 250.49                      | 275.42                     | 100.0%         |

- Capacity values reported in this column are in base-2 format which aligns with values reported in ONTAP command line and System Manager.
  - Capacity values reported in this column are in base-10 format and will not match any values reported by ONTAP. Those are provided for convenience only.





### 3.4 Storage Availability Zone

| Zone   | Workloads  | Workload Type | Ratio | Storage Availability Usage | Usable (TiB) | Effective (TiB) |
|--------|------------|---------------|-------|----------------------------|--------------|-----------------|
| Zone 1 | workload 1 | custom        | 2:1   | 3.00%                      | 5.00         | 10.00           |
| Zone 1 | workload 2 | custom        | 2:1   | 3.00%                      | 5.00         | 10.00           |
| Zone 1 | workload 3 | custom        | 2:1   | 3.00%                      | 5.00         | 10.00           |
| Zone 1 | workload 4 | custom        | 2:1   | 3.00%                      | 5.00         | 10.00           |

### 3.5 Drive Calculation Summary

| Node    | Drives<br>(Qty) (#Partitions,<br>#Non-Partitioned) | Flash Pool Drives<br>(Qty) (#Partitions,<br>#Non- Partitioned) | Aggregates<br>(Qty) | Space<br>Utilization |
|---------|--|--|---------------------|----------------------|
| netapp1 | (0, 0)   | (0, 0)   | 0                   | N/A                  |
| netapp2 | (0, 0)   | (0, 0)   | 0                   | N/A                  |

3.6 Workload Descriptions

|               |        |                |                          |             |          |                   | IO Percentages |            |          |           | IO Block Sizes (KB) |            |          |           |              |
|---------------|--------|----------------|--------------------------|-------------|----------|-------------------|----------------|------------|----------|-----------|---------------------|------------|----------|-----------|--------------|
| Workload Name | Type   | TPut IOPS      | Effective Capacity (TiB) | Cold Data % | Protocol | Read Latency (MS) | Rand Read      | Rand Write | Seq Read | Seq write | Rand Read           | Rand Write | Seq Read | Seq Write | Working Set% |
| workload 1    | Custom | 75,000.00 IOPS | 10.00                    | N/A         | FC_NV Me | 1                 | 70             | 30         | 0        | 0         | 16                  | 16         | 64       | 64        | 5            |
| workload 2    | Custom | 75,000.00 IOPS | 10.00                    | N/A         | FC_NV Me | 1                 | 70             | 30         | 0        | 0         | 16                  | 16         | 64       | 64        | 5            |
| workload 3    | Custom | 75,000.00 IOPS | 10.00                    | N/A         | FC_NV Me | 1                 | 70             | 30         | 0        | 0         | 16                  | 16         | 64       | 64        | 5            |
| workload 4    | Custom | 75,000.00 IOPS | 10.00                    | N/A         | FC_NV Me | 1                 | 70             | 30         | 0        | 0         | 16                  | 16         | 64       | 64        | 5            |

## 4 Environmental Certifications

### 4.1 Product Carbon Footprint

- [NS224 Report](#)

### 4.2 Statements & Certifications

- [European Union WEEE and Battery Statement](#)
- [China and Taiwan Toxic and Hazardous Substances or Elements Table](#)
- [European Union RoHS Compliance Statement](#)
- [ISO 14001:2015 Certificate](#)
- [E-waste Program](#)
- [Environmental Policy and Certifications](#)
- [European Union REACH Compliance Statement](#)
- [China RoHS Compliance Statement](#)
- [US TSCA PBT Substances Declaration](#)
- [European Union REACH Article Notifications - Cords and Cables](#)
- [PSU 80+ Platinum Certificate DPS-1600AB-18 C](#)
- [PSU 80+ Platinum Certificate PS-2162-8F](#)
- [PSU 80+ Titanium Certificate TDPS-2000KB A](#)
- [PSU 80+ Titanium Certificate TDPS-1600GB A](#)

## 5 Copyright

Refer to the [Interoperability Matrix Tool \(IMT\)](#) on the NetApp Support site to validate that the exact product and feature versions described in this document are supported for your specific environment. The NetApp IMT defines the product components and versions that can be used to construct configurations that are supported by NetApp. Specific results depend on each customer's installation in accordance with published specifications.

### Copyright Information

Copyright © 1994-2026 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

### Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.

