



Wide circumferential and lateral grooves provide exceptional water drainage and reduce the risk of aquaplaning.

ALL SIZES PASSENGER CAR

12" 13" **14"** 15" 16"

- ☒ TIRE SIZE
 ☒ PR
 ☒ LOAD / SPEED INDEX
 ☐ 2 WHELED MAX.LOAD PER AXLE
- ☐ 4 WHELED MAX.LOAD PER AXLE
 ☒ SPEED LIMIT
 ☒ INFLATED PRESSURE
 ☒ RIM
- ☒ INFLATED DIMENSIONS
 ☒ M+S
 ☒ SNOW FLAKE

**RFT : Run Flat **RF : Reinforced

TIRE SIZE	PR	LOAD / SPEED INDEX	SPEED LIMIT	INFLATED PRESSURE	RIM		INFLATED DIMENSIONS		M+S	SNOW FLAKE	EU TIRE LABEL				
					RECOM.	PERMITTED	SECTION WIDTH	OUTER DIAMETER							
18S R14 C	8	102/100R	170	65	5 1/2 J	5J, 6J	188	650	✓	✓	E	A	72	A	LABEL
19S R14 C	8	106/104R	170	65	5 1/2 J	5J, 6J	198	666	✓	✓	D	A	72	A	LABEL