

HP

UHP

VAN

AS

HT

AT

MT

WINTER

ST



~ Three stepped longitudinal main groove design

Excellent drainage performance and firm grip on wet and dry roads.

~ Unique design of the block and the high-density sipe

Ensure the good heat dissipation of the block with great grip and traction.

~ Wide shoulder block design

Improve the robustness of the block and the durability and load capacity of the tire, enhance the steering performance.

~ Low noise pattern design




Close shoulder effectively prevent the noise spread; the tuned pattern extends the rear of the shoulders to allow for even wear and further noise elimination.

~ Innovative four-season tread compound

Compound features high grip performance and high temperature resistance, and improve the grip under low temperature conditions.

NEW

GREENTOUR A/S

Size	LI/SI	PR	Depth (mm)	Rim	S/W (mm)	O/W (mm)	Load Index (kg) (Lbs)		Max Pressure (Kpa/Psi)	UTQG	Sidewall			
175/65R14C	90/88T	6	8	5	177	584	600/560	1323/1235	375/54	-	BSW	E	C	0
175/70R14C	95/93T	6	8	5	177	602	690/650	1521/1433	375/54	-	BSW	E	C	70
195/70R15C	104/102R	8	8	6	201	655	900/850	1984/1874	450/65	-	BSW	E	C	70
205/70R15C	106/104R	8	8	6	209	669	950/900	2094/1984	450/65	-	BSW	E	C	70
215/70R15C	109/107R	8	8.5	6 1/2	221	683	1030/975	2271/2149	450/65	-	BSW	E	C	70
225/70R15C	112/110R	8	8.5	6 1/2	228	697	1120/1060	2469/2337	450/65	-	BSW	E	C	70
185/75R16C	104/102R	8	8	5	184	684	900/850	1984/1874	475/69	-	BSW	E	C	70
195/75R16C	107/105R	8	8	5 1/2	196	698	975/925	2149/2039	475/69	-	BSW	E	C	70
205/75R16C	113/111R	10	8	5.5	203	714	1150/1090	2535/2403	525/76	-	BSW	E	C	70
215/75R16C	113/111R	8	8.5	6	216	728	1150/1090	2535/2403	475/69	-	BSW	E	C	70
225/75R16C	121/120R	10	8.5	6	223	744	1450/1400	3197/3086	575/83	-	BSW	E	C	70
195/65R16C	104/102T	8	8	6	201	660	900/850	1984/1874	475/69	-	BSW	E	C	70
205/65R16C	107/105T	8	8	6	209	672	975/925	2149/2039	475/69	-	BSW	E	C	70
215/65R16C	109/107T	8	8.5	6 1/2	221	686	1030/975	2271/2149	475/69	-	BSW	E	C	70
225/65R16C	112/110R	8	8.5	6 1/2	228	698	1120/1060	2469/2337	475/69	-	BSW	E	C	70
235/65R16C	115/113R	8	8.5	7	240	712	1215/1150	2679/2535	475/69	-	BSW	E	C	70
195/60R16C	99/97H	6	8	6	201	640	775/730	1709/1609	375/54	-	BSW	E	C	70
215/60R16C	103/101T	6	8.5	6 1/2	221	664	875/825	1929/1819	375/54	-	BSW	E	C	70
215/60R17C	109/107T	8	8.5	6 1/2	221	690	1030/975	2271/2149	475/69	-	BSW	E	C	70



* New Developing Sizes / The Labeling Information Is Subject To Change Without Notice.