



PUSEN[®]



-  No Cross Infection
-  No Sterilization
-  No Maintenance

Uscope PU3022A Specifications

Optical System	
Field of view	90°
Line of vision	0°
Depth of field	3-50 mm
Illumination	Optical fiber
Insertion Portion	
Deflection of distal tip	270° up, 270° down
Nominal width of insertion cord	9.2 Fr
Maximum width of distal tip	9 Fr
Maximum width of insertion portion	9.6 Fr
Working length	650 mm
Channel	
Working channel	3.6 Fr

Eview Specifications

Image Processor PV210	
Max. Resolution	1920 x 1080
Connections	DVI, VGA, SDI, VIDEO
Dimensions	311 mm x 188 mm x 65 mm
Weight	2.3 kg
Image Processor UTV100	
Max. Resolution	1024 x 768
Orientation	Landscape
Display type	12.1" color TFT LCD
Storage capacity	8 GB
Connections	USB, RCA, HDMI
Dimensions	315 mm x 308 mm x 187 mm
Weight	4.3 kg


PUSEN®

Zhuhai Pusen Medical Technology Co., Ltd.
Address: 5/F, Building 1, No 33, Keji San Road, High-tech Zone,
Tangjiawan Town, Zhuhai, Guangdong, PRC.
Tel:0086 400 6882023 Fax:0086 756 6880401
http://www.pusenmedical.com Email:Pusen@pusenmedical.com



Version: A/2 201803
Note: Specifications indicated in the above table
are subject to change without any notice.

PUSEN®



Uscope

SINGLE-USE DIGITAL FLEXIBLE URETEROSCOPE