



CERTIFICATE OF EXCLUSIVE DISTRIBUTION

Issuer:

Risen Construction Machinery (Shanghai) Co., Ltd.
Address: Guo'an Road, Yangpu District, 200433, Shanghai, China

Recipient:

Contracting Authority
Agrotrac Prim SRL, Municipality of Chişinău

We hereby certify:

That **AGROTRAC PRIM S.R.L.**, located at MD-2002, Republic of Moldova, str. A. Mateevici 99.A, or. Stăuceni, is our official exclusive distributor for all sales and after-sales services.

Furthermore, it is authorized to fulfill warranty and post-warranty obligations for vehicles provided by our company within the territory of the Republic of Moldova.

This certificate is issued to confirm the exclusive distributor status and the authorization of the aforementioned activities.

Signed,

Risen Machinery
General Director
Andy Ding


Date of issuance: 09.12.2024

Number: RSJIT241209E

Official signature and stamp:



	Item			parameter
Size	Overall dimensions (length x width x height)		mm	11610×2500×3255
	Wheelbase		mm	4750
	Wheelbase (front/rear)		mm	2026/1840
	Front overhang/rear overhang		mm	2167/2320
Weight parameters	Maximum allowable total mass		kg	19200
	Axle load	Axis 1	kg	7100
		Axis 2	kg	12100
Power parameters	Engine model		—	YCDV4863-235
	Rated power/speed		kW/(r/min)	173/2300
	Maximum net power/speed		kW/(r/min)	168/2300
	Maximum output torque/speed		N.m/(r/min)	860/ (1200-1700)
行驶参数	Maximum speed		km/h	90
	Minimum stable speed		km/h	2.5 ~ 3
	Minimum turning diameter		m	≤18
	Minimum turning diameter of arm head		m	≤22.1
	Minimum ground clearance		mm	250
	Approach Angle		°	12
	Departure angle		°	13
	Braking distance (initial braking speed is 30km/h)		m	≤10
	Maximum climbing ability		%	≥45
Fuel consumption per 100 km		L	25	



	Item			Parameter	
Main performance parameters	Maximum rated total lifting weight		t	16	
	Minimum rated operating range		m	3	
	Turntable tail turning radius		mm	3250	
	Maximum lifting moment	Basic arm	kN.m	564	
		Longest main boom	kN.m	353	
	Outrigger span	Vertical	m	4.7	
		Horizontal	m	5.9	
	Lifting height	Basic arm	m	9.8	
		Longest main boom	m	37.8	
	Boom length	Basic arm	m	9.7	
Longest main boom		m	37.5		
Working speed parameters	Boom lifting time		s	≤38	
	Boom full extension time		s	≤50	
	Maximum rotation speed		r/min	2	
	Outrigger retraction time	Horizontal outriggers	Up	s	≤25
			Down	s	≤40
		Vertical legs	Up	s	≤25
			Down	s	≤40
Hoisting speed (single rope, fourth layer, no load)	Main lifting mechanism	m/min	≥130		
	Auxiliary lifting mechanism	m/min	≥130		













