



-  Optional Sensor
-  Optional Third Overflow Safety Bottle

LIFETIME SA01HT



Product Page

Designed to evacuate the fluid accumulated in the operated areas of the patients during the surgical operations.



LED Electronic User Panel

It allows all settings to be made electronically on a single panel.



Electronic Jar Replacement

It is now much easier to replace the jar electronically with its special design.



Automatic Shutoff Valve

When the jar is full, the device automatically shuts itself off and prevents liquid overflows.



Electronic Foot Switch

It provides a more comfortable use to the user without touching the device during the operation.



Autoclavable Jar

Thanks to its autoclavable polycarbonate jars at 121 degrees, it provides hygienic use for many times.



Low Noise Level

With a sound level of 42 dB, it is one of the lowest among competitors.

Technical Specifications

Compressor	Oilless Piston Pump
Voltage	230 VAC \pm 10% , 50 Hz
Max. Free Air Flow	90lt or 60lt/min \pm 10%
Max. Vacuum	-700 mmHg \pm 5%
Power Consumption	Max. 500W
Vacuum Setting	Yes
Collection Jar	2x (2-3-5 lt)
Float System	Yes
Hydrophobic Filter	Yes
Standard	ISO 10079 – 1 / CE
Device Dimensions	38x30x34 cm
Weight of Device	11 kg
Box Dimensions	44x38x40 cm
Gross Weight (Device)	13 kg
Box Dimensions (Stand)	50x48x72 cm
Weight (Stand)	12 kg
Gross Weight (Stand)	13 kg
Stock Code	HT01B000
Warranty Period	2 years