

# **Features**

- Measuring SpO2, Pulse Rate and Temperature(optional)
- 3.5 inch TFT display of PI%, plethysmograph and pulse bar
- · Adult, pediatric and neonate measurement
- Lithium battery up to 18 hours
- 500 hours SpO2 data storage
- PC software for data upload



# **Technical Specifications**

# SpO<sub>2</sub>

lechnique:	Dual-wavelength LED			
Display range:	0%~100%			
Measuring accuracy:	±3%(range from 70% to 100%)			
Pulse Rate				
Measuring range:	30~250bpm			

# Temperature(option)

Measuring range:	<b>32</b> ℃ <b>~43</b> ℃
Measuring accuracy:	± 0.2 °C
Measuring time:	≤ 5 seconds
Measuring probe:	Infrared ear probe

#### Perfusion Index

PI display range:	0.2%~20%
ri dispiay range.	0.2/0~20/0

#### Measuring Mode

Continuous or Spot check

# Data Storage

Up to 500 hours

## Display

3	5"	col	lor'	TFT	disp	lav
J	.၁	CO	IOI	$I \Gamma I$	GISD	ıay

## **Power Supply**

2000mAh lithium battery

# Charging

Charging stand or USB cable

#### Dimension

158mm x 73mm x 25mm

#### Net Weight

230g

#### Data Upload

USB cable or wireless

#### **Operating Environment**

Operating Temperature: 5 °C ~40 °C Operating Humidity: 15%-93%



Adult clip sensor



Pediatric soft sensor



Adult soft sensor



Neonate wrap sensor



Pediatric clip sensor



Infrared ear thermometer







**♥ C €**<sub>0123</sub> FDA 510(k)

#### Shenzhen Creative Industry Co., Ltd.

Floor 5, BLD 9, Baiwangxin High-Tech Industrial Park, Songbai Road, Xili Street Nanshan District, 518110 Shenzhen, PEOPLE'S REPUBLIC OF CHINA Tel: +86 755 2643 3514 Fax: +86 755 2643 0390 www.creative-sz.com info@creative-sz.com