

1.Air-cooled chiller parameter table 风冷式冷水机组参数表:			
Technical parameters of some specifications of Air-cooled chillerXR-60AG XR-60AG 风冷式冷水机组部分规格技术参数表			
NO.	NAME 名称	TYPE OF SPECIFICATION 规格类型	PERFORMANCE PARAMETERS 性能参数
1		Model 型号	XR-60AG
2	Refrigeration capacity 制冷量	KW	181.68
		Kcal/h	156249
3	Power supply 电源	V	3N-380-50HZ
4	Power of the whole machine 整机功率	KW	68.8
5	Current of the whole machine 整机电流	A	143.1
6	Compressor 压缩机	Type 型式	Fully enclosed vortex type 全封闭涡旋式
		Refrigeration input power (kW) 制冷输入功率 (kW)	7.5*6
		Refrigeration operation current (A) 制冷运转电流 (A)	99
7	风机	Type 型式	External rotor axial fan 外转子轴流风机
		Windm3/h 风量 m3/h	60000
8	水泵	Type 型式	Centrifugal pipeline pump 离心式管道泵
		Pump lift 扬程 MH2O	20
		Volume of flow 流量 m3/h	36
9	Condenser 冷凝 器	Type 型式	Aluminum finned sleeve type 铝翅片套管式

		Heat exchange (kw) 换热量 KW	280.68
10	蒸发器 Evaporator 蒸发器	Type 型式	Shell tube type 壳管式
		Heat exchange 换热量 KW	181.68
		Volume of flow 流量 m³/h	30.52

11	Piping 配管	Export of frozen water media 冷冻水媒体出口	DN80 (according to coustomer' s need) DN80(根据客户要求)
		Frozen water media entrance 冷冻水媒体入口	DN80 (according to coustomer' s need) DN80(根据客户要求)
12	温度数显微电脑控制器	Display the status 显示状况	Light-touch digital tube display 轻触式数码管显示器
		Exert oneself 出力	Gw532A
		Output selection 出力器选择	Relay output 继电器输出
		Temperature control range℃ 温控范围℃	-20 ~ +35
		Temperature control accuracy℃ 温控精度℃	± 2.0
13	Alarming device 警报装置	Abnormal temperature 温度异常	Alarming if the circulating water temperature is too low and cut off the compressor. 循环水温度过低警报并切断压缩机
		Power supply reverse phase 电源逆相	Power phase detection prevents pump and compressor from reverting 电源相位检测防止泵浦、压缩机反转
		High and low voltage failure 高低压故障	Pressure switch to detect the pressure state of the refrigerant system 压力开关检测冷媒系统压力状态
		Compressor overload 压缩机过载	Thermal relay protection compressor 热继电器保护压缩机
		Compressor overheating 压缩机过热	Internal protector protects the compressor 内保护器保护压缩机

		Pump overload 泵浦过载	Thermal relay protection pump 热继电器保护泵
		Low water alarm 低水位警报	Water level switch 水位开关
		Short-circuit 短路	Air switch 空气开关
		Cold media 冷媒体	Tap water/Coolant 自来水/冷冻液
Performance Type 外型尺寸	L*W*H 长*宽*高 (MM)		3800*1800*2180
Whole machine weight 整机重量	KG		1420

