

Specificații tehnice (F 4.1)

Numărul procedurii de achiziție : ocds-b3wdp1-MD-1705502538213 din 17.01.2024
Obiectul achiziției : : „Echipament tehnic pentru producția TV și Radio”, CPV: 32300000-6”: Receptoare de televiziune și de radio și aparate de înregistrare sau de redare a sunetului sau a imaginii , Cererea ofertelor de prețuri (bunuri)

Denumirea bunurilor/serviciilor or	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Bunuri/servicii						
Lotul 1						
1.1. Camera Video	PXW-Z190 4K 3- CMOS 1/3" Sensor XDCAM Camcorder	PRC	Sony	Imaging Sensor Resolution Effective: 8.3 Megapixel Image Sensor 1/3"-Type 3-Chip CMOS Built-In ND Filter Mechanical Filter Wheel with Clear, 2-Stop (1/4), 4-Stop (1/16), 6-Stop (1/64) ND Filters and a 2 to 7 Stop Electronic ND Filter Capture Type Video Only Exposure Control Shutter Type Electronic Rolling Shutter Shutter Type Electronic Rolling Shutter Shutter Speed 1/8000 to 1/24 Second Minimum Illumination 0.02 Lux Lens Focal Length 3.7 to 92.5mm (35mm Equivalent: 28.8 to 720mm) Optical Zoom Ratio 25x Maximum Aperture f/1.6 Minimum Aperture f/11 Filter Size 82 mm (included 10 transparent filters) Control Rings Focus Zoom Iris Focus Control Autofocus, Manual Focus	Imaging Sensor Resolution Effective: 8.3 Megapixel Image Sensor 1/3"-Type 3-Chip CMOS Built-In ND Filter Mechanical Filter Wheel with Clear, 2-Stop (1/4), 4-Stop (1/16), 6-Stop (1/64) ND Filters and a 2 to 7 Stop Electronic ND Filter Capture Type Video Only Exposure Control Shutter Type Electronic Rolling Shutter Shutter Type Electronic Rolling Shutter Shutter Speed 1/8000 to 1/24 Second Minimum Illumination 0.02 Lux Lens Focal Length 3.7 to 92.5mm (35mm Equivalent: 28.8 to 720mm) Optical Zoom Ratio 25x Maximum Aperture f/1.6 Minimum Aperture f/11 Filter Size 82 mm (included 10 transparent filters) Control Rings Focus Zoom Iris Focus Control Autofocus, Manual Focus Video Capture Internal Recording Modes XAVC-L 3840 x 2160 at 23.98/25/29.97/50/59.94 fps [150 Mb/s]	

			<p>Video Capture Internal Recording Modes XAVC-L 3840 x 2160 at 23.98/25/29.97/50/59.94 fps [150 Mb/s] 1920 x 1080p at 23.98/25/29.97/50/59.94 fps [35 to 50 Mb/s] 1920 x 1080i at 50/59.94 fps [25 to 50 Mb/s] 1280 x 720 at 50/59.94 fps [50 Mb/s] DV 720 x 480i at 59.94 fps 720 x 480p at 29.97 fps 720 x 576i at 50 fps 720 x 576p at 25 fps Built-In Microphone Type Stereo Audio Recording XAVC: 4-Channel 24-Bit 48 kHz LPCM Audio Interface Media/Memory Card Slot Dual Slot: SD/SDHC/SDXC Video I/O 1 x BNC (3G-SDI) Output 1 x HDMI Output Audio I/O 2 x XLR 3-Pin Mic/Line (+48 V Phantom Power) Input 1 x 3.5 mm TRS Stereo Headphone Output Other I/O 1 x BNC (Timecode) Input/Output, 1 x Micro-USB, 2 x USB-A 1 x RJ45 (LAN) 1 x 2.5 mm Sub-Mini (LANC) Control Wireless 2.4 / 5 GHz Wi-Fi 5 (802.11ac), NFC Monitor Display Type Articulating LCD Display Size 3.5" Resolution 1,560,000 Dot Viewfinder Type Built-In Electronic (LCD) Size 0.39" Resolution 2,360,000 Dot Focus Focus Type Auto and Manual Focus Focus Mode Automatic, Manual Focus General Battery Type BP-U Series (5200 mAh / 74.88Wh 8 x Piece included) Accessory Mounting Thread 1 x <i>Include</i></p>	<p>1920 x 1080p at 23.98/25/29.97/50/59.94 fps [35 to 50 Mb/s] 1920 x 1080i at 50/59.94 fps [25 to 50 Mb/s] 1280 x 720 at 50/59.94 fps [50 Mb/s] DV 720 x 480i at 59.94 fps 720 x 480p at 29.97 fps 720 x 576i at 50 fps 720 x 576p at 25 fps Built-In Microphone Type Stereo Audio Recording XAVC: 4-Channel 24-Bit 48 kHz LPCM Audio Interface Media/Memory Card Slot Dual Slot: SD/SDHC/SDXC Video I/O 1 x BNC (3G-SDI) Output 1 x HDMI Output Audio I/O 2 x XLR 3-Pin Mic/Line (+48 V Phantom Power) Input 1 x 3.5 mm TRS Stereo Headphone Output Other I/O 1 x BNC (Timecode) Input/Output, 1 x Micro-USB, 2 x USB-A 1 x RJ45 (LAN) 1 x 2.5 mm Sub-Mini (LANC) Control Wireless 2.4 / 5 GHz Wi-Fi 5 (802.11ac), NFC Monitor Display Type Articulating LCD Display Size 3.5" Resolution 1,560,000 Dot Viewfinder Type Built-In Electronic (LCD) Size 0.39" Resolution 2,360,000 Dot Focus Focus Type Auto and Manual Focus Focus Mode Automatic, Manual Focus General Battery Type BP-U Series (5200 mAh / 74.88Wh Include : 8 x Digital Power BP-U60 Li-Ion 5200mAh accumulator pentru SONY (8 pieses) : Mount / Series Type : Sony BP-U Series Chemistry : Lithium-Ion Battery Capacity : 5200 mAh / 74,9 Wh Output Voltage : 14.4 VDC Dimensions (W x H x D) : 50 mm x 40 mm x 50 mm Weight : 0.9 lb / 0.396 kg Accessory : Mounting Thread 1 x 10 x SanDisk 64GB Extreme PRO UHS-I SDXC Memory Card 170 MB/s V30 : Tip card SDXC Capacitate 64 Gb</p>	
--	--	--	--	--	--

				10 x SDXC 64Gb Write speed 90MB/S, Speed Class 10 UHS Speed Class U3 Video Speed Class V30 10 x Card Reader All-in-1 (included) USB3.0/3.1 SD XC UHS-II Garanție 24 luni	Tip Bus UHS-I Clasa Viteza 10 Clasa Viteza UHS U3 Interfata Viteza Bus UHS Class I Clasa Viteza Video V30 Transfer de date Viteza de citire 170 MB/s Maximum Viteza de scriere 90 MB/s Maximum (10 pieses) 10 x Transcend RDF9 UHS-II Card Reader USB3.0/3.1, UHS-II SD Cards, Read/Write speeds up to 260MB/s/190MB/s (10 pieses) Garanție 24 luni	
Lotul 4						
4.1 Microfon	AVX-835 SET Digital Camera-Mount Wireless Cardioid Handheld Microphone System (1.9 GHz)	Germania Romania	Sennheiser	System Wireless Technology Digital 1.9 GHz Included Transmitters 1 x Handheld Diversity Antenna Diversity RF Frequency Band 1920 to 1930 MHz RF Bandwidth 10 MHz RF Channel Scanning Auto-Scan Max Operating Range 29.9 m (Line of Sight) Max Transmitters per Band 8 Sample Rate/Resolution 48 kHz / 24-Bit Latency 19 ms Dynamic Range >120 dBA Encryption AES 256 Modulation GFSK (with Back Channel) Receiver Receiver Type Camera-Mount Mounting Options- Plug-In, Shoe-Mount(with Included Hardware) Antenna 1 x External, Fixed (Top-Mount) Number of Audio Channels 1 Audio I/O 1 x XLR 3-Pin Male Balanced Mic Output Audio Output Level - XLR Output:-30 to 0 dB (Balanced) Frequency Response 20 Hz to 20 kHz USB/Lightning Connectivity 1 x Micro-USB Female (Bus Power, Charging) Power Requirements Battery, Bus Power (USB) Battery Type 1 x Battery Pack (Included)	System Wireless Technology Digital 1.9 GHz Included Transmitters 1 x Handheld Diversity Antenna Diversity RF Frequency Band 1920 to 1930 MHz RF Bandwidth 10 MHz RF Channel Scanning Auto-Scan Max Operating Range 29.9 m (Line of Sight) Max Transmitters per Band 8 Sample Rate/Resolution 48 kHz / 24-Bit Latency 19 ms Dynamic Range >120 dBA Encryption AES 256 Modulation GFSK (with Back Channel) Receiver Receiver Type Camera-Mount Mounting Options- Plug-In, Shoe-Mount(with Included Hardware) Antenna 1 x External, Fixed (Top-Mount) Number of Audio Channels 1 Audio I/O 1 x XLR 3-Pin Male Balanced Mic Output Audio Output Level - XLR Output:-30 to 0 dB (Balanced) Frequency Response 20 Hz to 20 kHz USB/Lightning Connectivity 1 x Micro-USB Female (Bus Power, Charging) Power Requirements Battery, Bus Power (USB) Battery Type 1 x Battery Pack (Included) Approx. Battery Life - 4 Hours (Lithium Rechargeable) Display & Indicators - 1 x LED (Battery Status,	

				<p>Approx. Battery Life - 4 Hours (Lithium Rechargeable)</p> <p>Display & Indicators - 1 x LED (Battery Status, Level)</p> <p>Housing Metal</p> <p>Transmitter</p> <p>Transmitter Type Handheld</p> <p>RF Output Power Up to 250 mW</p> <p>Muting Mute Switch</p> <p>Frequency Response 50 Hz to 20 kHz (Mic)</p> <p>Antenna 1 x External, Fixed (Handheld)</p> <p>Power Requirements- Battery, Bus Power (USB)</p> <p>Battery Type 1 x Battery Pack (Included)</p> <p>Approx. Battery Life - 15 Hours (Lithium Rechargeable)</p> <p>USB/Lightning I/O 1 x Micro-USB (Bus Power, Charging)</p> <p>Display & Indicators 1 x LCD (Battery Status, Signal Strength)</p> <p>Housing Metal</p> <p>Microphone</p> <p>Microphone Type Handheld Capsule</p> <p>Color Black</p> <p>Sound Field Mono</p> <p>Capsule Dynamic</p> <p>Polar Pattern Cardioid</p> <p>Maximum SPL 154 dB SPL Peak</p> <p>Sensitivity 2.1 mV/Pa</p> <p>Garanție 24 luni</p>	<p>Level)</p> <p>Housing Metal</p> <p>Transmitter</p> <p>Transmitter Type Handheld</p> <p>RF Output Power Up to 250 mW</p> <p>Muting Mute Switch</p> <p>Frequency Response 50 Hz to 20 kHz (Mic)</p> <p>Antenna 1 x External, Fixed (Handheld)</p> <p>Power Requirements- Battery, Bus Power (USB)</p> <p>Battery Type 1 x Battery Pack (Included)</p> <p>Approx. Battery Life - 15 Hours (Lithium Rechargeable)</p> <p>USB/Lightning I/O 1 x Micro-USB (Bus Power, Charging)</p> <p>Display & Indicators 1 x LCD (Battery Status, Signal Strength)</p> <p>Housing Metal</p> <p>Microphone</p> <p>Microphone Type Handheld Capsule</p> <p>Color Black</p> <p>Sound Field Mono</p> <p>Capsule Dynamic</p> <p>Polar Pattern Cardioid</p> <p>Maximum SPL 154 dB SPL Peak</p> <p>Sensitivity 2.1 mV/Pa</p> <p>Garanție 24 luni</p>	
4.2 Microfon	ECM-W3 Dual-Channel Wireless Microphone System	China	Sony	<p>Microphone Channel Audio Output 2ch</p> <p>Shoe type Multi Interface Shoe</p> <p>Power Supply from Main Unit Multi Interface Shoe</p> <p>Battery Type Built-in lithium-ion battery</p> <p>Number of Battery Required 1</p> <p>Monaural / Stereo Monaural</p> <p>Directivity omni-directional</p> <p>Frequency Response 20 Hz to 20 000 Hz</p> <p>Front sensitivity -20 dBFS (0.1 Pa, 1 kHz)* * Acquired while "10dB" is selected by the ATT switch.</p> <p>Intrinsic noise 16 dB SPL or less (0 dB = 2×10⁻⁵ Pa)* *</p>	<p>Microphone Channel Audio Output 2ch</p> <p>Shoe type Multi Interface Shoe</p> <p>Power Supply from Main Unit Multi Interface Shoe</p> <p>Battery Type Built-in lithium-ion battery</p> <p>Number of Battery Required 1</p> <p>Monaural / Stereo Monaural</p> <p>Directivity omni-directional</p> <p>Frequency Response 20 Hz to 20 000 Hz</p> <p>Front sensitivity -20 dBFS (0.1 Pa, 1 kHz)* * Acquired while "10dB" is selected by the ATT switch.</p> <p>Intrinsic noise 16 dB SPL or less (0 dB = 2×10⁻⁵ Pa)* * Acquired while "10dB" is selected by the ATT switch. *</p>	

				<p>Acquired while "10dB" is selected by the ATT switch. * Acquired while "DIGITAL" is selected by the slide switch.</p> <p>Maximum Input Sound Pressure Level 120 dB SPL* * Acquired while "10dB" is selected by the ATT switch. * Equivalent sound pressure level value converted from the input level value that is acquired when 1% waveform distortion is produced by 1 kHz output signals from the microphone. (0 dB = 2×10^{-5} Pa)</p> <p>Microphone out jack (3.5 mm mini jack (stereo)) External microphone input jack(3.5 mm mini jack (monaural)) USB Type-C® Terminal Garanție 24 luni</p>	<p>Acquired while "DIGITAL" is selected by the slide switch.</p> <p>Maximum Input Sound Pressure Level 120 dB SPL* * Acquired while "10dB" is selected by the ATT switch. * Equivalent sound pressure level value converted from the input level value that is acquired when 1% waveform distortion is produced by 1 kHz output signals from the microphone. (0 dB = 2×10^{-5} Pa)</p> <p>Microphone out jack (3.5 mm mini jack (stereo)) External microphone input jack(3.5 mm mini jack (monaural)) USB Type-C® Terminal Garanție 24 luni</p>	
4.3 Microfon	SM7dB Vocal Microphone	China	Shure	<p>Form Factor Stand/Boom Mount Intended Sound Sources Vocals, Speech/Voice-Over Sound Field Mono Operating Principle Pressure Operated Element Type Dynamic Polar Pattern Cardioid</p> <p>Performance Frequency Range 50 Hz to 20 kHz Sensitivity -59 dBV/Pa at 1 kHz</p> <p>Physical Color Gray Mounting Thread Size 5/8"-27 Female Garanție 24 luni</p>	<p>Form Factor Stand/Boom Mount Intended Sound Sources Vocals, Speech/Voice-Over Sound Field Mono Operating Principle Pressure Operated Element Type Dynamic Polar Pattern Cardioid</p> <p>Performance Frequency Range 50 Hz to 20 kHz Sensitivity -59 dBV/Pa at 1 kHz</p> <p>Physical Color Gray Mounting Thread Size 5/8"-27 Female</p> <p>Include: RODE PSA1 Studio Boom Arm for Broadcast Microphones Garanție 24 luni</p>	
4.4 Set de Lavalieri wireless	EW 112P G4 Camera-Mount Wireless Omni Lavalier Microphone System (A: 516 to 558 MHz)	Germania Romania	Sennheiser	<p>System Wireless Technology Analog UHF Number of RF Channel Frequencies 1680 Included Transmitters 1 x Bodypack with Microphone Diversity Antenna Diversity RF Frequency Band A: 516 to 558 MHz RF Bandwidth 42 MHz Frequency Step Size 25 kHz Max Operating Range 100.6 m (Line of Sight) Max Transmitters per Band 12 Deviation 48 kHz (Peak) Modulation Wideband FM</p> <p>Receiver</p>	<p>System Wireless Technology Analog UHF Number of RF Channel Frequencies 1680 Included Transmitters 1 x Bodypack with Microphone Diversity Antenna Diversity RF Frequency Band A: 516 to 558 MHz RF Bandwidth 42 MHz Frequency Step Size 25 kHz Max Operating Range 100.6 m (Line of Sight) Max Transmitters per Band 12 Deviation 48 kHz (Peak) Modulation Wideband FM</p> <p>Receiver</p>	

			<p>Receiver Type Camera-Mount Mounting Options Shoe-Mount (with Included Hardware) Antenna 1 x Flexible Whip, Fixed Number of Audio Channels 1 Audio I/O 1 x 3.5 mm TRS Female Unbalanced Output (Lockable) Gain Range 42 dB (6 dB Steps) Audio Output Level +12 dBu Squelch 5 to 25 dBμV Adjacent Channel Isolation >65 dB Power Requirements Battery Battery Type 2 x AA (Included) Approx. Battery Life 8 Hours (Alkaline) Display & Indicators 1 x Backlit LCD (Battery Status, Output Level, RF Level) Housing Metal</p> <p>Transmitter Transmitter Type Bodypack RF Output Power 30 mW Audio I/O 1 x 3.5 mm TRS Female Unbalanced Input (Lockable) Muting Mute Switch Audio Input Level 3 V RMS (Max) Gain Range 60 dB (3 dB Steps) Frequency Response 80 Hz to 18 kHz (Mic) 25 Hz to 18 kHz (Line) Sync Method IR Antenna 1 x Flexible Whip, Fixed (Beltpack) Power Requirements Battery Battery Type 2 x AA (Included) Approx. Battery Life 8 Hours (Alkaline) Display & Indicators 1 x Backlit LCD (Audio Level, Battery Status, Signal Strength) Housing Metal</p> <p>Microphone Microphone Type Lavalier Sound Field Mono Capsule Electret Condenser Polar Pattern Omnidirectional Frequency Range 50 Hz to 18 kHz Equivalent Noise Level 36 dB Maximum SPL 130 dB SPL Peak Sensitivity 20 mV/Pa Output Connectors 1 x 3.5 mm TRS Male Unbalanced (Lockable)</p>	<p>Receiver Type Camera-Mount Mounting Options Shoe-Mount (with Included Hardware) Antenna 1 x Flexible Whip, Fixed Number of Audio Channels 1 Audio I/O 1 x 3.5 mm TRS Female Unbalanced Output (Lockable) Gain Range 42 dB (6 dB Steps) Audio Output Level +12 dBu Squelch 5 to 25 dBμV Adjacent Channel Isolation >65 dB Power Requirements Battery Battery Type 2 x AA (Included) Approx. Battery Life 8 Hours (Alkaline) Display & Indicators 1 x Backlit LCD (Battery Status, Output Level, RF Level) Housing Metal</p> <p>Transmitter Transmitter Type Bodypack RF Output Power 30 mW Audio I/O 1 x 3.5 mm TRS Female Unbalanced Input (Lockable) Muting Mute Switch Audio Input Level 3 V RMS (Max) Gain Range 60 dB (3 dB Steps) Frequency Response 80 Hz to 18 kHz (Mic) 25 Hz to 18 kHz (Line) Sync Method IR Antenna 1 x Flexible Whip, Fixed (Beltpack) Power Requirements Battery Battery Type 2 x AA (Included) Approx. Battery Life 8 Hours (Alkaline) Display & Indicators 1 x Backlit LCD (Audio Level, Battery Status, Signal Strength) Housing Metal</p> <p>Microphone Microphone Type Lavalier Sound Field Mono Capsule Electret Condenser Polar Pattern Omnidirectional Frequency Range 50 Hz to 18 kHz Equivalent Noise Level 36 dB Maximum SPL 130 dB SPL Peak Sensitivity 20 mV/Pa Output Connectors 1 x 3.5 mm TRS Male Unbalanced (Lockable)</p>	
--	--	--	---	---	--

				Cable Length 1.6 m Garanție 24 luni	Cable Length 1.6 m Garanție 24 luni	
Lotul 5						
5.1 Boxe active	S1000MKII, Hi-Res 2.0/ 120W (2x60W) RMS, Bluetooth 5.0 with aptX HD Decoding	PRC	Edifier	Device type speakers, loudspeaker Diffuser Bass unit MATERIAL Wood Frequency band 42 Hz - 40,000 Hz Model S1000MKII Principal edifying The type of connection With fir tree Color Wood Signal-to-noise ratio, dB(A) 90 Manufacturer code null In the set Audio connection cables, Remote control Input sensitivity Line in 1 Number of acoustic channels 2.0 Power, W 120 (2 x 60) Wireless connection Bluetooth 5.0 Inputs Audio outputs 2 x RCA Coaxial Optical Choice null Noise level, dB null Garanție 12 luni	Device type speakers, loudspeaker Diffuser Bass unit MATERIAL Wood Frequency band 42 Hz - 40,000 Hz Model S1000MKII Principal edifying The type of connection With fir tree Color Wood Signal-to-noise ratio, dB(A) 90 Manufacturer code null In the set Audio connection cables, Remote control Input sensitivity Line in 1 Number of acoustic channels 2.0 Power, W 120 (2 x 60) Wireless connection Bluetooth 5.0 Inputs Audio outputs 2 x RCA Coaxial Optical Choice null Noise level, dB null Garanție 12 luni	
Lotul 6						
6.1 Acumulator	V-mount BP-150W Li-Ion 14.8V / 150Wh	China	Digital Power	Mount Type: V – Mount (V-lock holder) Power Meter : Blue Color 4-LED Power Monitor (Display 100%, 75%, 50%, or 25% SOC capacity) Product Color : Dark Grey Bat. Cell Model : LG High Load Stand 18650 x 16 Bat. Cell Chemistry : Lithium-Ion Capacity : 10400 mAh / 150 Wh Maximum Load : 13A / 190W USB Output : 5V, 12W / 2.4A max (Dust Protection Cover) D-Tap Output : 14.8V, 100W / 6.8A max	Tip acumulator V-mount/BP-150W Li-Ion Voltaj : 14.8 V Capacitate 10400 mAh / 150 Wh Acumulatorul integreaza un afisaj cu leduri in 4 nivele pentru nivelul de incarcare : 100%, 75%, 50%, or 25% SOC capacity) Cell Chemistry : Lithium-Ion USB Output : 5V /2,1 A (2.4A max) D-Tap Output : 14.8V, 100W / 6.8A max Dimensiuni 96 mm x 152 mm x 53 mm Greutate 880 g Garanție 12 luni	
6.2 Încărcător	Dual Slot Charger for BP-U30 / BP-U60 Sony Batteries	China	Digital Power	Battery Charger Charger Compatibility BP-U Series Number of Battery Bays 2 Multi-Bay Charging Modes Simultaneous Charger Power Source AC Power (Cable	Tip incarcator Incarcator dual cu display LCD Numărul de compartimente pentru baterii : 2 Alimentare AC: 100-240 V, 50/60 Hz; DC: 12-24 V 3000 mA (max) Voltaj iesire : DC 8.4 V /12.6 V / 16.8 V Iesire USB 5 V cu 2100 mAh	

				<p>Included) Charger Power I/O 1 x Barrel/Coax Female Output • 12 VDC at 3 A (36 W) Charger Included Adapter / Cable 1 x Barrel/Coax Male to Barrel/Coax Male Cable 1 x USA Type-A Plug to IEC Male Cable</p>	<p>Caracteristici Pe modul High incarca o baterie cu 1500 mAh sau 2 x baterii simultan cu 800 mAh Pe modul Low incarca o baterie cu 1000 mAh sau 2 x baterii simultan cu 500 mAh Jack pentru cablu alimentare camera Charger Included Adapter / Cable 1 x Barrel/Coax Male to Barrel/Coax Male Cable 1 x USA Type-A Plug to IEC Male Cable Garanție 12 luni</p>	
6.3 Baterie	AA Rechargeable Battery 4 Pack, 2500mAh series	China	Verbatim	<p>Battery type Rechargeable batteries Rechargeable Battery size AA Battery type Ni-MH Battery capacity 2500 mAh Quantity included: 4 pcs.</p>	<p>Battery type Rechargeable batteries Rechargeable Battery size AA Battery type Ni-MH Battery capacity 2500 mAh Quantity included: 4 pcs. Garantie : 12 luni</p>	
6.4 Încărcător	BQ-CC65E	PRC	Panasonic	<p>Power supply Type Charger Charging compartments 4 Charging voltage 5 Power supply AC outlet Compatibility Battery size AA/AAA Battery type Ni-MH Peculiarities Charger Operating Modes Charging, Updating & Testing Indicator type LCD display with backlight Plug Design Built-in plug</p>	<p>Input current: AC 100-240V 50-60Hz Input connector structure: AC cable Charging control: Smart charge USB output: DC 5.0V 1A / USB-A 1 slot Indication: LCD display (indication of battery capacity, battery life, discharge mode) Rechargeable batteries: AA x 1-4 / AAA x 1-4 cells Charging time: AA: 4 batteries 3 hours, 2 batteries 1.5 hours Dimensions (mm) (W x H x D): 147 x 88 x 40 mm Garanție 12 luni</p>	
6.5 Încărcător Type - C	65W Standard USB-C AC Adapter	China	Lenovo	<p>General Power Output 65 W Number of Tips 1 Tip Type USB-C Plug Type 2-Prong USB I/O 1 x USB-C</p>	<p>General Power Output 65 W Number of Tips 1 Tip Type USB-C Plug Type 2-Prong USB I/O 1 x USB-C Garanție 12 luni</p>	
Lotul 7						
7.1 Tehnică de stocare SSD	4TB ESD380C USB 3.2 Gen 2x2 Portable SSD (Military Green)	PRC	Transcend	<p>Interface USB 3.2 Gen 2x2 Speed 2000 MB/s (read), 2000 MB/s (write) NAND 3D memory Capacity 4TB Housing material Metal + plastic Includet rubber case and one USB-C to USB-C cable</p>	<p>Host Connection : USB-C 3.2 Gen 2x2 Storage Capacity : 4 TB SSD USB Type : USB Type C to USB Type A/ USB Type C to USB Type C Read Speed (Max.) : Up to 2,000 MB/s Write Speed (Max.) : Up to 2,000 MB/s Flash Type : 3D NAND flash Supports USB 3.2 Gen 2x2 (USB 20Gbps).</p>	

				Garanție 12 luni	Default OS Support : Windows & macOS Dimensions : 96.5 mm x 53.6 mm x 12.5 mm Garanție 12 luni
7.2 Tehnică de stocare HDD	StoreJet 35T3	PRC	Transcend	Interface USB Type USB Type Micro-B to USB Type A Connection Interface USB 3.1 Gen 1 (USB 5Gbps) Storage Capacity 4 TB/8 TB Storage Media 3.5" HDD Garanție 12 luni	Storage Capacity : 8 TB SATA III (6 Gb/s) 3.5" HDD (7200 rpm) USB Type USB : Type Micro-B to USB Type A Connection Interface : USB 3.1 Gen 1 (USB 5Gbps) Capacity : 8 TB Storage Media: 3.5" HDD Garanție 12 luni
Lotul 8					
8.1 Căști dinamice	DT-770 Pro 80 Ohm	Australia	Beyerdyna mic	Transducer type Dynamic Operating principle Closed Nominal frequency response 5 - 35,000 Hz Nominal impedance 80 Ω Nominal SPL 96 dB Nominal T.H.D < 0.2% Power handling capacity 100 mW Sound coupling to ear Circumaural Ambient noise isolation 80 Ω / 250 Ω version approx. 18 dBA Nominal headband pressure approx. 3.5 N Length and type of cable 3 m / straight cable Connection Gold plated mini stereo jack plug (3.5 mm) & adapter (6.35 mm)	Transducer type Dynamic Operating principle Closed Nominal frequency response 5 - 35,000 Hz Nominal impedance 80 Ω Nominal SPL 96 dB Nominal T.H.D < 0.2% Power handling capacity 100 mW Sound coupling to ear Circumaural Ambient noise isolation 80 Ω / 250 Ω version approx. 18 dBA Nominal headband pressure approx. 3.5 N Length and type of cable 3 m / straight cable Connection Gold plated mini stereo jack plug (3.5 mm) & adapter (6.35 mm) Include : Screw-on adapter to 6.3 mm stereo jack Garantie : 12 luni
Lotul 9					
9.1 Lumini bicolor	S-2241 Bi-color SMD On-camera LED light	PRC	SWIT	153pcs ultra bright long-life LEDs Surface mounted LED technology 120°(half-declined 68°) wide beam angle 3200K-5600K continuously adjustable 20W power, 640Lux @ 1 meter center 10%-100% flick-free dimming Super high CRI Ra≥93, TLCI≥97 Interchangeable various DV battery plates (included 1 S-7004F, included 1 S-7004U) Support DC 6-17V input from D-tap Provide ball head, diffuser, and bag Garanție 12 luni	153pcs ultra bright long-life LEDs Surface mounted LED technology 120°(half-declined 68°) wide beam angle 3200K-5600K continuously adjustable 20W power, 640Lux @ 1 meter center 10%-100% flick-free dimming Super high CRI Ra≥93, TLCI≥97 Interchangeable various DV battery plates Support DC 6-17V input from D-tap Provide ball head, diffuser, and bag Include : 1.S-7004F DV Battery Mount Plate, 2.S-7004U : DV Battery Mount Plate, 3. Provide ball head, diffuser, and bag Garanție 12 luni
9.2 Lumini	KNOWLED F400Bi Bi-Color LED	PRC	Godox	Item Type 1 x LED Flexible Light Included Light Modifier 1 x Softbox Included Filters Diffusion	Item Type 1 x LED Flexible Light Included Light Modifier 1 x Softbox Included Filters Diffusion

	<p>Light Panel (2.1 x 4')</p>		<p>Included Storage Case 1 x Case Photometrics 2700K: 11,500 Lux at 1 m 3200K: 12,600 Lux at 1 m 4300K: 14,200 Lux at 1 m 5600K: 14,700 Lux at 1 m 6500K: 14,300 Lux at 1 m 8500K: 13,800 Lux at 1 m Color Temperature 2700 to 8500K Color Modes Daylight, Tungsten Color Accuracy Standard CRI 96; TLCI 96 Connectivity Wireless Remote Control Type Bluetooth; Wi-Fi; Wireless DMX 1 x XLR 5-Pin Locking Male Wireless Range 300 m (included) Wireless Frequency 2.4 GHz Wireless Range 30 m (Bluetooth); 60 m (Wi-Fi) Max DMX Control Channels 512 Power & I/O Power Source AC Power (Cable Included); Power Supply/Controller (Included) Inputs/Outputs Light Fixture To Power Supply/Controller: 1 x Built-In Cable with Proprietary Power Input Power Supply/Controller 1 x Unspecified AC Power Input 1 x XLR 5-Pin DMX Input 1 x XLR 5-Pin DMX Output 1 x USB-A Power/Remote Input/Output Battery Plate Type 2 x V-Mount (Built-In) Battery 2 x V-Mount Rechargeable (Included) Included Adapter / Cable : 1 x Unspecified to Unspecified Garanție 12 luni</p>	<p>Included Storage Case 1 x Case Photometrics 2700K: 11,500 Lux at 1 m 3200K: 12,600 Lux at 1 m 4300K: 14,200 Lux at 1 m 5600K: 14,700 Lux at 1 m 6500K: 14,300 Lux at 1 m 8500K: 13,800 Lux at 1 m Color Temperature 2700 to 8500K Color Modes Daylight, Tungsten Color Accuracy Standard CRI 96; TLCI 96 Connectivity Wireless Remote Control Type Bluetooth; Wi-Fi; Wireless DMX 1 x XLR 5-Pin Locking Male Wireless Range 300 m (included) Wireless Frequency 2.4 GHz Wireless Range 30 m (Bluetooth); 60 m (Wi- Fi) Max DMX Control Channels 512 Power & I/O Power Source AC Power (Cable Included); Power Supply/Controller (Included) Inputs/Outputs Light Fixture To Power Supply/Controller: 1 x Built-In Cable with Proprietary Power Input Power Supply/Controller 1 x Unspecified AC Power Input 1 x XLR 5-Pin DMX Input 1 x XLR 5-Pin DMX Output 1 x USB-A Power/Remote Input/Output Battery Plate Type 2 x V-Mount (Built-In) Include : 2buc - Digital Power BP-VL99 99W 14.4V PD65W USB-C V-Mount Battery Tensiune standard 14.4V Capacitate 7000mAh /99Wh Iesiri 1 x D-TAP 16.8V-3.4A, rapid 16.8V6.8A 1 x USB Type-C (DC5V/3A, DC9V/3A, DC12V/3A, DC15V/3A, DC20V/3.25A) 1 x USB Type-A (DC5V/3A, DC9V/2A, DC12V/1.5A, DC4.5V/3A, DC5V/4.5A) Intrari USB Type-C PD65W (DC5V/3A, DC9V/3A, DC12V/3A, DC15V/3A, DC20V/3.25A) 1 x D-TAP Curent maxim 10A Included Adapter / Cable : 1 x Unspecified to Unspecified Garanție 12 luni</p>	
<p>Lotul 10</p>					

10.1 Tripod	Tripod Ace XL Tripod System with CF Legs & Mid-Level Spreader	Germania /China	Sachtler	Payload Capacity Fluid Head: 2 to 8 kg Tripod: 20 kg, with appropriate head Height Range Complete System: 79 to 170 cm Folded Length Complete System: 86 cm Counterbalance 8 steps Pan / Tilt Drag 3 steps + zero Sliding Balance Plate Travel 10.4 cm Tilt Range +90 to -75° Head Attachment Fitting 75 mm bowl, integrated flat base Leveling Bubble Illuminated Material of Construction Fluid Head: Aluminum Tripod: Carbon fiber Feet: Rubber	Payload Capacity Fluid Head: 2 to 8 kg Tripod: 20 kg, with appropriate head Height Range Complete System: 79 to 170 cm Folded Length Complete System: 86 cm Counterbalance 8 steps Pan / Tilt Drag 3 steps + zero Sliding Balance Plate Travel 10.4 cm Tilt Range +90 to -75° Head Attachment Fitting 75 mm bowl, integrated flat base Leveling Bubble Illuminated Material of Construction Fluid Head: Aluminum Tripod: Carbon fiber Feet: Rubber Garanție 12 luni	
10.2 Stativ pentru microfon	HM-6	PRC	Superlux	Table Stand For microphones Height: 15 - 20 cm Colour: Nickel / black Including micro-clamp	Table Stand For microphones Height: 15 - 20 cm Colour: Nickel / black Including micro-clamp Garanție 12 luni	
10.3 Suport lumini	Air Cushioned (Pneumatic) HEAVY DUTY LIGHT STAND 2.9 M	PRC	Impact	Maximum Working Height 285 cm Load Capacity min 10 kg General Number of Sections 4 Leg Shape Round Finish Black Material Metal	Sarcina maxima sustinuta 10 kg Inaltime maxima 290 cm Inaltime minima 123 cm Inaltime strans 107 cm Alcatuire 3 x segmente / 4 x sectiuni Diametru segmente 3 segmente cu diametrul profilelor 35.6 mm, 31.5 mm si 28 mm Amprenta la sol 132 cm Greutate 2 kg Montura Prevazut cu spigot de 5/8 (16 mm) cu dublu filet 1/4 si 3/8 Material Aluminiu anodizat negru Garanție 12 luni	

Semnat: _____ Numele, Prenumele: Cîrlig Ion În calitate de: director

Ofertantul: WEST BUY SRL Adresa: mun.Chisinau bd.Mirecea cel Batrin 39 ap 143

Data : 25.01.2024