



	<p>LABORATORY OF FIRE EXTINGUISHING AGENTS AND EQUIPMENT</p> <p>Scientific and Research centre for fire protection</p>	
	<p>Nadwiślańska Street 213, 05-420 Józefów phone numbers: telephone exchange: +48 22 769 32 00, www.cnbop.pl; secretariat: +48 22 769 33 00, e-mail: cnbop@cnbop.pl fax: +48 22 769 33 56</p>	CNBOP - PIB

TECHNICAL OPINION NO 172/BU/17

13 pages

PRINCIPAL (name and address)	BOHAMET - ARMATURA Sp. J Kościelna Street 2, Ciele 86-005 Białe Błota
TEST SAMPLE'S (product, object), description and identification	UNDERGROUND HYDRANT DN 100 PN 10/16 type HP - M
PRODUCT MANUFACTURER (testing object)	BOHAMET - ARMATURA Sp. J Kościelna Street 2, Ciele 86-005 Białe Błota

Copy of the technical opinion	1
----------------------------------	---

ZA ZGODNOŚĆ Z ORYGINALEM
„BOHAMET-ARMATURA” SP.J.

Henryk Bogusz

“BOHAMET-ARMATURA” SP.J. 11.03.2018 DATA PODPIS... wspólnik „BOHAMET-ARMATURA” s.j.

Specjalista ds. kontroli jakości i nadzoru BHP
Tomasz Chodera

Józefów, 12 of May 2017



PROGRAM REGIONALNY
NARODOWA STRATEGIA SPÓŁNOŚCI




WOJEWÓDZTWO
KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
EUROPEJSKI FUNDUSZ
ROZWOJU REGIONALNEGO



Jarosław Halarewicz, Henryk Bogusz
„BOHAMET-ARMATURA” SP.J.
Ciele, ul. Kościelna 2, 86-005 Białe Błota
NIP 554-23-42-840 • REGON 092535146
KRS 0000109728

Mój region w Europie



CNBOP - PIB	TECHNICAL OPINION nr 172/BU/17	2/13
----------------	--------------------------------	------

1. FORMAL BASIS FOR THE EXAMINATION OF TESTS

The ordering letter of 17 of March 2017.

The agreement no 172/BU/17 of 26 of April 2017.

współnik „BOHAMET-ARMATURA” s.j.

Jarosław Halarewicz, Henryk Bogusz
 „BOHAMET-ARMATURA” SP.J.
 Ciele, ul. Kościelna 2, 86-005 Białe Błota
 NIP 554-23-42-840 • REGON 092535146
 KRS 0000109728

2. TESTING SAMPLES / OBJECTS

2.1. Product/object name, type, size and other indications.

Single-closed underground hydrant DN 100 PN 10/16 type HP
 (optional with extra ball seal).

The single-closed underground hydrant DN 100 PN 10/16 type HP (optional with extra ball seal) is intended for the water abstraction with the general purpose pipeline with a diameter of minimum 100 mm.

Hydrants are equipped with single closure (the mushroom valve) and dehydration (drainage) device, located in the valve body.

The upper part of hydrant has a connection in the form of thread 6 ", which is made of brass and secure the rubber guard with EPDM.

(picture))

ZA ZGODNOŚĆ Z ORYGINALEM
 „BOHAMET-ARMATURA” SP.J.

14.03.2018
 DATA

“BOHAMET-ARMATURA” SP.J.

Specjalista ds. kontroli jakości i nadzoru BHP

Tomasz Chodera

2.3. The manner of accepting the sample for the test and the method of its storage.

The principal took 1 sample for testing of parti of 1, by the sampling protocol PS/33/30.04.2014 and delivered by forwarding into the lab. According to the sampling protocol, it is representative of the current production process.

The samples were received in the laboratory by the delivery and acceptance protocol on 4 of April 2017.

The manufacturer attached to the samples:

- list of parts and materials
- technical description of the DN 100PN 10 type HP/M underground hydrant B24
- manufacturer's declaration for underground hydrant type HP-M DN 100



PROGRAM REGIONALNY
 NARODOWA STRATEGIA SPÓŁNOŚCI



WOJEWÓDZTWO
 KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
 EUROPEJSKI FUNDUSZ
 ROZWOJU REGIONALNEGO



Mój region w Europie



CNBOP - PIB	TECHNICAL OPINION nr 172/BU/17	3/13
-------------	--------------------------------	------

3. TEST AND METHODS OF TESTING

3.1. Methods of testing for single-closed underground hydrant DN 100 PN 10/16 type HP-M

Specjalista ds. kontroli jakości i nadzoru BHP
 Tomasz Chodera

Accepted Standard	GOST P53961 – 2010 underground fire hydrants	
L.p.	Feature tested	Technical requirements. Testing methods. ⁽¹⁾
1	General technical requirements.	5.1
2	Basic parameters and characteristics.	5.2.1, 5.2.2
3	Construction requirements.	
4	Ergonomics requirements	
5	Mechanical strength of the hydrants.	
6	Requirements for materials and semi-finished products	
7	Completeness.	
8	Marking (signing)	
9	Packaging, storage and transport	

ZA ZGODNOŚĆ Z ORYGINAŁEM
 „BOHAMET-ARMATURA” SP.J.
 PODPIS.....
 14.03.2018
 DATA

Verification of the requirements on the basis of documentation and declarations provided by the manufacturer.

Henryk Bogusz

¹⁾ The tests for this Technical Opinion are non-accredited by PCA.

3.3 The date of the test.

Tests were done on days 09-12 of May 2017.

Współnik „BOHAMET-ARMATURA” s.j.
 Jarosław Halarewicz, Henryk Bogusz
 „BOHAMET-ARMATURA” SP.J.
 Ciele, ul. Kościelna 2, 86-005 Białe Błota
 NIP 554-23-42-840 • REGON 092535146
 KRS 0000109728



PROGRAM REGIONALNY
 NARODOWA STRATEGIA SPÓŁNOŚCI



WOJEWÓDZTWO
 KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
 EUROPEJSKI FUNDUSZ
 ROZWOJU REGIONALNEGO



Moj region w Europie



CNBOP - PIB	TECHNICAL OPINION nr 172/BU/17	4/13
----------------	--------------------------------	------

4. TESTS RESULT.

Single-closed underground hydrant DN 100 PN 10/16 type A.

L.P.	FEATURE TESTED	Equirements according to GOST P 53961-2010	Result	statement of compliance/non-compliance with the requirements
1	Hydrant produced in accordance with the requirements of this standard.	5.1.	positive	compatible
2	1. Operating pressure P_p' Mpa ($\text{kgf}^*\text{cm}^{-2}$), no more than 2. the height of the hydrant H , mm 3. Inner diameter of the body DN 4. Valve adaptors, mm 5. shank clearance based on by the axis, no more than 6. number of spindle revolutions to fully open the hydrant 7. hydraulic resistance in a hydrant S , $c_2^*m^{-5}$, no more than*, with $H=1000$ mm 8. hydrant mass at $H=1000$ mm, kg, not more	5.2.1	PN 10 till PN 16 from 500 to 3500 inclusive 107 from 24 to 30 inclusive 0,4 14 35	compatible
	Change of hydraulic resistance for every 250 mm of height, no more than $0,05^*103^*c_2^*m^{-5}$ The weight change for every 250 mm height - no more than 10 kg			<i>Henryk Bogusz współnicy "BOHAMET-ARMATURA" S.A.</i>
	The hydrant corresponds to the following reliability indicators: full work period - preservation of parameters during storage throughout the period fixed quantity of efficient work feasibility (cycles of action)	5.2.2	10 years not less than a year not less than 200 cycles	compatible <i>ZGODNOŚĆ Z ORYGINAŁ "BOHAMET-ARMATURA" S.A. 14.03.2018... PODPIS</i>
3.	The hydrant body construction provides durability at hydraulic pressures exceeding 1.5 times the working pressure	5.3.1	positive no signs of cracking	compatible <i>"BOHAMET-ARMATURA" S.A. Tomasz Chodera</i>



PROGRAM REGIONALNY
 NARODOWA STRATEGIA SPÓJNOŚCI




WOJEWÓDZTWO
 KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
 EUROPEJSKI FUNDUSZ
 ROZWOJU REGIONALNEGO



Mój region w Europie



CNBOP
 - PIB

TECHNICAL OPINION nr 172/BU/17

5/13

	The hydrant construction in place keeps hermetic connections and seals under operating pressure	5.3.2	no signs of leakage or dripping of liquids through the walls of the body parts, as well as in places of movable connections and by sealing the stem/ positive result	compatible
	Hydrant construction	5.3.3	ensures its opening and closing during the whole working pressure range	compatible
	Hydrant equipped with a device for draining water left after work	5.3.4	quantity remaining water 0,00 ml / positive result	compatible
	hydrant valve and hydrant drive	5.3.5	can withstand axial force not less than 3*104 H (3*103kgf)	compatible
	construction and fixing of the hydrant connector	5.3.6	excludes turning the fitting when screwing in the fire rack in accordance with the National Standard P 53250 positive result	compatible
	threaded part of the hydrant connector	5.3.7	Equipped with a hinged lid. The construction of the lid does not interfere with the free installation of the fire protection rack positive result	compatible

"BOHAMET-ARMATURA" SP.J.
 Specjalista ds. kontroli jakości i nadzoru BHP
 Tomasz Chodera



PROGRAM REGIONALNY
 NARODOWA STRATEGIA SPOJNOŚCI



WOJEWÓDZTWO
 KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
 EUROPEJSKI FUNDUSZ
 ROZWOJU REGIONALNEGO
 NIP 554-23-42-840 • REGON 092535149
 KRS 0000109728

ZA ZGODNOŚĆ Z ORYGINALEM
 "BOHAMET-ARMATURA" SP.J.

14.03.2018
 DATA

PODRS

Henryk Bogusz

Jarosław Halarewicz, Henryk Bogusz
 "BOHAMET-ARMATURA" SP.J.



CNBOP - PIB	TECHNICAL OPINION nr 172/BU/17	6/13
----------------	--------------------------------	------

	The square of stem for connecting the hydrant with the fire rack key	5.3.8	22 x 22 mm; square dimensions - accurate to the 12th degree of accuracy of the State Standard 25347. The square surface has a hardness of ~28HRC.	compatible
4.	Controls for closing devices.	5.4.1	The hydrant moves smoothly when working within a set range. Positive result.	compatible
	Open / close force of the hydrant valve with the fire rack key (or threaded valve with a special key).	5.4.2	Does not exceed 90 Nm. Positive result.	compatible
5.	Production under specific climatic conditions.	5.5.1	Temperate and cold climate, State Standard 15150 category 1.1. Positive result.	compatible
	Sets and parts of a hydrant: the cycle should be understood as: full opening of the hydrant; work within no less than 1 min at operating pressure; full hydrant closure; draining the water through the drain valve.	5.5.2	Manufactured from materials with mechanical and anti-corrosive properties that ensure the ability to work with water when operating under specified operating conditions. Positive result.	compatible
	The hydrant valve ring.	5.5.3	Manufactured from frost-proof NBR rubber with an increased hardness of 70 ± 5 Sh according to the State Standard 7338. Positive result.	compatible

"BOHAMET-ARMATURA" SP.J.

Specjalista ds. kontroli jakości i nadzoru PIB
 Tomasz Chodera



PROGRAM REGIONALNY
 NARODOWA STRATEGIA SPÓŁNOŚCI

Z ZGODNOŚĆ Z ORYGINALEM
 "BOHAMET-ARMATURA" SP.J.

DATA

14.03.2018

PODPIS



Jarosław Halarewicz, Henryk Bogusz
 "BOHAMET-ARMATURA" SP.J.
 Ciele, ul. Kościelna 2, 86-005 Białe Błota
 NIP 554-23-42-840 • REGON 092535146
 KRS 0000109728

Henryk Bogusz
 Współnik "BOHAMET-ARMATURA" s.j.

UNIA EUROPEJSKA
 EUROPEJSKI FUNDUSZ
 ROZWOJU REGIONALNEGO



Mój region w Europie

WOJEWÓDZTWO
 KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
 EUROPEJSKI FUNDUSZ
 ROZWOJU REGIONALNEGO



CNBOP - PIB	TECHNICAL OPINION nr 172/BU/17	7/13
----------------	--------------------------------	------

	Arrangements with the orderer.	5.5.4	The manufacturer does not use additional protective coatings (painting with powder varnish).	compatible
	Varnish coatings of the external surface of the hydrant.	5.5.5	In accordance with National Standard 9.032, with a class not lower than VI for operating conditions in temperate and cold climates, 4 according to the State Standard 9.104. Preparation of metal surfaces before painting - according to the National Standard 9.402. Positive result.	compatible
	Welding of hydrant flanges. Other welded joints of steel structures	5.5.6	In accordance with State Standard 16037, In accordance with State Standard 5264 and Manufacturer's Technical Documentation Sticking, spouts of welds, flooding, arson, shifting of welded parts, as well as other defects that affect the quality and reliability of hydrants do not occur. Positive result.	compatible

"BOHAMET-ARMATURA" SP.J.
 Specjalista ds. kontroli jakości i nadzoru BHP
 Tomasz Chodera

ZA ZGODNOŚĆ Z ORYGINALEM
 "BOHAMET-ARMATURA" SP.J. Jarosław Halarewicz, Henryk Bogusz
 "BOHAMET-ARMATURA" SP.J. Ciele, ul. Kościelna 2, 86-005 Białe Błota
 NIP 554-23-42-840 • REGON 092535146
 KRS 0000109728

Henryk Bogusz



PROGRAM REGIONALNY
 NARODOWA STRATEGIA SPÓŁNOŚCI



WOJEWÓDZTWO
 KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
 EUROPEJSKI FUNDUSZ
 ROZWOJU REGIONALNEGO



Mój region w Europie



CNBOP - PIB	TECHNICAL OPINION nr 172/BU/17	8/13
----------------	--------------------------------	------

6.	Supplied materials and products used in the production of hydrant parts.	5.6.1	Accepted by the input control with checking their quality and necessary documentation. Positive result.	compatible
	Materials used. Chemical-physical properties of starting materials, hardness and roughness of their surface.	5.6.2	They have certificates or labels confirming their compliance with standards, technical conditions or other normative documentation. They correspond to the standards, technical conditions of their production, as well as the purpose and conditions of work of the parts of hydrants produced from them. Positive result.	compatible
	Moulding (casting) hydrant. Deviations in the dimensions and weight of gray cast iron castings	5.6.3	According to the State Standard 26358. According to the 3rd class accuracy of State Standards P 53464. Positive result.	compatible
	On the friction surfaces are machined die-cast parts (flanges, bodies, connector, valve body).	5.6.4	No occurrence of dentures, slag impurities, cracks and other defects of the cast.	compatible

"BOHAMET-ARMATURA" SP.J.

Specjalista ds. kontroli jakości i nadzoru BHP

Tomasz Chodera

ZA ZGODNOŚĆ Z ORYGINALEM

"BOHAMET-ARMATURA" SP.J.

Jarosław Halarewicz, Henryk Bogusz

"BOHAMET-ARMATURA" SP.J.

Ciele, ul. Kościelna 2, 86-005 Białe Błota

NIP 554-23-42-840 • REGON 092535146

KRS 0000109728

Henryk Bogusz

Współnik "BOHAMET-ARMATURA" s.j.

14.03.2018

DATA

LEOPIST



WOJEWÓDZTWO
KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
EUROPEJSKI FUNDUSZ
ROZWOJU REGIONALNEGO



PROGRAM REGIONALNY
NARODOWA STRATEGIA SPÓŁNOŚCI

Mój region w Europie



**CNBOP
- PIB**

TECHNICAL OPINION nr 172/BU/17

9/13

	Mechanical and anti-corrosion properties, material of the threaded part of the junction.	5.6.5	They have the same good properties as the "LK1" brass properties of the State Standard or the "Br 05C5S5" bronze of the State Standard. Positive result.	compatible
	Material of the hydrant stem.	5.6.6	Steel 1.4021 is just as good as marji steel 30x13 State Standard 5632.	compatible
	Valve seals (bead seat).	5.6.7	Made of a material with basic properties not lower than that of the "LK1" brand of the State Standard or bronze standard brand "Br 05C5S5" of the State Standard.	compatible
	Production technology of hydrantes with one typical size.	5.7	It secures full volatility of its assembly units and parts.	compatible
	Hydrants's components.	5.8	No traces of corrosion, dents, dints, cracks and other mechanical damage. Acute angles and the edges of the parts are polished.	compatible

"BOHAMET-ARMATURA" SP.J.

Specjalista ds. kontroli jakości i nadzoru BHP
 Tomasz Chodera

ZA ZGODNOŚĆ Z ORYGINALEM
 "BOHAMET-ARMATURA" SP.J.

14.03.2018
 DATA

Jarosław Halarewicz, Henryk Bogusz
 "BOHAMET-ARMATURA" SP.J.
 Ciele, ul. Kościelna 2, 86-005 Białe Błota
 NIP 554-23-42-840 • REGON 092535Współnik "BOHAMET-ARMATURA" s.j.
 KRS 0000109728

Henryk Bogusz



PROGRAM REGIONALNY
 NARODOWA STRATEGIA SPÓŁNOŚCI



WOJEWÓDZTWO
 KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
 EUROPEJSKI FUNDUSZ
 ROZWOJU REGIONALNEGO



Mój region w Europie



CNBOP
 - PIB

TECHNICAL OPINION nr 172/BU/17

10/13

	Metric threads: Internal threads – 7H External threads -8 g; (trapezoidal threads)	5.9	Made in accordance with the 24705 State Standard with tolerance fields according to the 16093 State Standard. Made in accordance with the 24705 State Standard with tolerance fields according to the 16093 State Standard. Made in accordance with the 24738 State Standard. Cracks, local interruptions and irregularities on the surface of the threads do not occur if their depth goes beyond the limits of the average thread diameter and their overall length exceeds half the length of the convolution.	compatible
	Fastening of individual parts, assembly units.	5.10	Excludes their automatic loosening and unscrewing when using a hydrant.	compatible
7.	The complete delivery of the hydrant includes:	5.11	Assembly products, provided for in the Product Technical Documentation, certificate, technical description, operating manual or one document replacing them, prepared in accordance with the State Standard. Positive result.	compatible



PROGRAM REGIONALNY
 NARODOWA STRATEGIA SPÓŁNOŚCI




WOJEWÓDZTWO
 KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
 EUROPEJSKI FUNDUSZ
 ROZWOJU REGIONALNEGO



Mój region w Europie



CNBOP
- PIB

dział handlowy: tel. +48 (52) 581 67 51 / 53 / 54
TECHNICAL OPINION nr 1672/BW/17

+48 (52) 581 67 52

11/13

ISO 9001

	Labeling.	5.12.1	The hydrants's labeling corresponds to the requirements of the manufacturer's Technical Documentation. Positive result.	compatible
8.	The label should contain the following information: Manufacturer's name or trade mark; contractual hydrant designation, according to the prudent system; Serial number; Height of the hydrant, mm; Inner diameter of the DN body; Year of production; Producer's country name	5.12.2	<p>BOHAMET - ARMATURA</p> <p>UNDERGROUND HYDRANT DN 100 PN 10/16 type HP - M</p> <p>cat. no 11.291.100-1250</p> <p>1250 mm</p> <p>DN 100</p> <p>2017</p> <p>Poland</p>	<p>Henryk Bogusz współnik "BOHAMET-ARMATURA" s.j.</p> <p>Jarosław Halarewicz, Henryk Bogus "BOHAMET-ARMATURA" SP. Ciele, ul. Kościelna 2, 86-005 Białe Błota NIP 554-23-42-840 • REGON 092535 KRS 0000109728</p>
	Cleansing and drying.	5.13.1	Before packaging, the hydrant is cleaned, the flue linings are dried.	compatible
9.	Exposed threads and unpainted surfaces of metal parts.	5.13.2	<p>Covered with Press-Solidol, in accordance with the 4366 State Standard, variant of protection B3-I, B3-2.</p> <p>The period of validity of the hydrant maintenance is 24 months.</p> <p>The usage documentation should include: date of maintenance, set period of protection without re-maintenance and degreasing method.</p>	<p>ZA ZGODNOŚĆ Z ORYGINALEM "BOHAMET-ARMATURA" SP. 14.03.2018 DĄBPIŚ</p>
			Positive result.	compatible



PROGRAM REGIONALNY
NARODOWA STRATEGIA SPÓŁNOŚCI



WOJEWÓDZTWO
KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
EUROPEJSKI FUNDUSZ
ROZWOJU REGIONALNEGO



Mój region w Europie



CNBOP
- PIB

TECHNICAL OPINION nr 172/BU/17

12/13

Maintenance.	5.13.3	The top hole is covered with a plug and the bottom opening remains open for easier assembly.	compatible
Packing.	5.13.4	<p>The hydrant is wrapped in a scrim foil, sealed with tape, and then placed on a pallet with wooden spacers.</p> <p>Other packaging may be used to ensure product safety during transport and storage.</p> <p>Packing is done to exclude shifting of the hydrant in the packaging during loading, transport and unloading.</p>	compatible
Package.	5.13.5	It has the labeling in accordance with the requirements of the 14192 State Standards.	compatible
Technical and operational documentation.	5.13.6	Placed in a watertight container with a hydrant with the inscription: "Documentation".	compatible

"BOHAMET-ARMATURA" SPŁĄCZALNOŚĆ Z ORYGINALEM
 "BOHAMET-ARMATURA" SP.J.
 Specjalista ds. kontroli jakości i nadzoru BHP. 03.2018
 DATA
 Tomasz Chodera

Jarosław Halarewicz, Henryk Bogusz
BOHAMET-ARMATURA SP.J.
 Ciele, ul. Kościelna 2, 86-005 Białe Błota
 NIP 554-23-42-840 REGON 092535146
 KRS 0000109728

Henryk Bogusz

współnik "BOHAMET-ARMATURA" s.j.



PROGRAM REGIONALNY
 NARODOWA STRATEGIA SPÓŁNOŚCI



WOJEWÓDZTWO
 KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
 EUROPĘSKI FUNDUSZ
 ROZWOJU REGIONALNEGO



Mój region w Europie



CNBOP
- PIB

TECHNICAL OPINION nr 172/BU/17

13/13

5. DECLARATIONS AND RESERVATIONS

The test results refer only to the tested sample of the product / test object. Without the written permission of the Laboratories Team, the report may not be reproduced (copied), otherwise than in its entirety.

The test report has been prepared in 3 copies.

THE END.

Technical documentation was prepared by:	tech. Krzysztof Bocian	12.05.2017
	qualification, name and surname	date and signature
The person approving the technical opinion:	inż.. Daria Kubis	12.05.2017
	qualification, name and surname	date and signature

"BOHAMET-ARMATURA" SP.J.

Specjalista ds. kontroli jakości i nadzoru BHP
Tomasz Chodera

ZA ZGODNOŚĆ Z ORYGINALEM
"BOHAMET-ARMATURA" SP.J.

14.03.2018
DATA

PODPIŚ

Jarosław Halarewicz, Henryk Bogusz
„BOHAMET-ARMATURA” SP.J.
 Ciele, ul. Kościelna 2, 86-005 Białe Błota
 NIP 554-23-42-840 • REGON 092535146
 KRS 0000109728

Henryk Bogusz
 Współnik „BOHAMET-ARMATURA” s.j.



PROGRAM REGIONALNY
NARODOWA STRATEGIA SPÓŁNOŚCI



WOJEWÓDZTWO
KUJAWSKO-POMORSKIE

UNIA EUROPEJSKA
EUROPEJSKI FUNDUSZ
ROZWOJU REGIONALNEGO



Mój region w Europie