

## General information

<b>Global Commercial Alias:</b>	PSTX570-600-70
<b>Extended Product Type:</b>	PSTX570-600-70
<b>Product ID:</b>	1SFA898117R7000
<b>ABB Type Designation:</b>	PSTX570-600-70
<b>EAN:</b>	7320500508992
<b>Catalog Description:</b>	PSTX570-600-70 Softstarter
<b>Long Description:</b>	Softstarter PSTX570-600-70 for max 600V main voltage and 100 - 250V 50/60Hz control supply voltage.

## Category

Produkter » Lavspenningsprodukter » Startapparater » Mykstartere » Mykstartere

## Interactive Guide

**Kategorirelaterede guider:** [ABB improves mining industry efficiency - Softstarter PSTX](#)

## Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85369095

## Popular Downloads

**Data Sheet, Technical Information:** 1SFC132012C0201

## Dimensions

<b>Product Net Width:</b>	361.000 mm
<b>Product Net Height:</b>	493.000 mm
<b>Product Net Depth:</b>	282.000 mm
<b>Product Net Weight:</b>	27.00 kg

## Technical

<b>Rated Operational Voltage:</b>	Main Circuit 208 ... 600 V AC
<b>Rated Control Supply Voltage (Us):</b>	100 ... 250 V
<b>Rated Control Circuit Voltage (Uc):</b>	DC Operation 24 V
<b>Rated Frequency (f):</b>	Main Circuit 50/60 Hz
<b>Rated Operational Power - In-Line (400 V)</b>	315 kW
<b>Connection (Pe):</b>	
<b>Rated Operational Current - In-Line</b>	570 A
<b>Connection (Ie):</b>	
<b>Rated Operational Power - Inside</b>	at 400 V 540 kW
<b>Delta Connection:</b>	
<b>Rated Operational Current - Inside</b>	987 A
<b>Delta Connection:</b>	
<b>Service Factor Percentage:</b>	100 %
<b>Overload Protection:</b>	Build-in electronic overload protection
<b>Integrated Electronic Overload:</b>	Yes
<b>Adjustable Rated Motor Current Ie:</b>	30 ... 100 %
<b>Starting Capacity at Maximum</b>	4xIe for 10s
<b>Rated Current Ie:</b>	
<b>Ramp Time:</b>	1 ... 120 second [unit of time]
<b>Initial Voltage During Start:</b>	10 ... 99 %
<b>Step Down Voltage Special Ramp:</b>	100 ... 10 %
<b>Current Limit Function:</b>	1.5 ... 7.5 xIe
<b>Switch for Inside Delta Connection:</b>	Yes
<b>Run Signal Relay:</b>	Yes
<b>By-pass Signal Relay:</b>	Yes
<b>Fault Signal Relay:</b>	Yes
<b>Overload Signal Relay:</b>	Yes
<b>Analog Outputs:</b>	0...10 V, 0...20 mA, 4...20 mA
<b>Signal indication ready to start/standby ON (LED):</b>	Green
<b>Signal indication running R (LED):</b>	Green
<b>Signal indication protection (LED):</b>	Yellow

<b>Signal indication fault (LED):</b>	Red
<b>Communication:</b>	Built in Modbus interface, Anybus, FieldBusPlug (with adapter).
<b>Terminal Type:</b>	Main Circuit: Bars
<b>Connecting Capacity Main Circuit:</b>	Hole Diameter 8.5 mm
<b>Connecting Capacity Control Circuit:</b>	Rigid 1x2.5 mm <sup>2</sup>
<b>Connecting Capacity Supply Circuit:</b>	Rigid 1x2.5 mm <sup>2</sup>
<b>Tightening Torque:</b>	Main Circuit 25 N·m
<b>Product Main Type:</b>	PSTX570

## Environmental

<b>Ambient Air Temperature:</b>	Storage -40 ... +70 °C Operation -25 ... +60 °C
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Certificates and Declarations (Document Number)

<b>Declaration of Conformity - CE:</b>	2CMT005209
<b>Environmental Information:</b>	2CMT005232
<b>Instructions and Manuals:</b>	1SFC132081M0201
<b>RoHS Information:</b>	2CMT005210

## Container Information

<b>Package Level 1 Width:</b>	470 mm
<b>Package Level 1 Length:</b>	381 mm
<b>Package Level 1 Height:</b>	650 mm
<b>Package Level 1 Gross Weight:</b>	31.00 kg
<b>Package Level 1 EAN:</b>	7320500501535
<b>Package Level 1 Units:</b>	1 piece

## Classifications

<b>Object Classification Code:</b>	Q
<b>E-number:</b>	3302088
<b>ETIM 4:</b>	EC002572 - Electronic motor control and protection device
<b>ETIM 5:</b>	EC002572 - Electronic motor control and protection device

