



Cassette Laser Printer

KF-UE-006

PRODUCT FEATURES



Application Circumstance

Batch Printing and Single Quick Printing.



Strong Software Function

Simple to operate, drag-and-drop control interface, real-time preview of printed content, compatible with LIS, HIS, and PIS.



High-Stability System

Adopts LINUX system, safe and reliable, high-speed operation, support USB, network port, and WIFI interface connection.



High-Speed Printing





Contact Us

Tel/WhatsApp/Wechat: +86 186-7233-4799
Email: info@kfbio.cn

· Web: kfbiopathology.com



Technical Specifications

- 1. Cassette Compatibility: Supports printing on cassettes with closed lid or without lid, and cassette of different colors
- 2. Hopper Capacity: 6 hoppers × 75 cassettes, 450 cassettes in total
- 3. Loading Method: Six-position automatic rotating loading
- 4. Output Slot Capacity: Continuous and uninterrupted collection of no less than 120 cassettes
- 5. Printing Resolution: 2500 dpi
- 6. Printing Speed: 15 cassettes per minute
- 7. Print Content: Capable of printing English letters, symbols, graphics, and QR codes
- 8. Printing Method: Non-contact laser printing technology
- 9. Laser Configuration: Equipped with a low-energy cold light source laser
- 10. Internal Structure: High-density aluminum alloy construction for durability and stability
- 11. Operating System: LINUX system
- 12. Operating Interface: 10-inch color touchscreen embedded in the front panel for easy operation
- 13. Interface Display: Full English interface
- 14. System Interface: Supports HIS, LIS, and PIS system integration
- 15. Connectivity: Supports network interface and USB communication
- 16. Template Editing: Printing software allows users to independently adjust and modify template content. Supporting year, pathology number, QR code, DM code, etc. It also supports editing functions for text size and position, deformation, printing parameters, filling parameters, and other parameters.
- 17. Automatic Printing: Automatically prints when new data is added or received from system interfaces
- 18. Real-Time Preview: Supports real-time display of print data with options to cancel or pause printing
- 19. Dust Removal: Equipped with a professional dust removal system with replaceable filters for effective dust and odor removal
- 20. Working Voltage: 100-240VAC, 50/60Hz
- 21. The laser and screen are controlled by the same control card, which controls all internal systems and laser marking functions, without issues such as disconnection.
- 22. The labeling of cassettes is performed with one-dimensional and two-dimensional barcodes, using alphanumeric, Roman, or graphic characters
- 23. It allows cassette labeling on writing surfaces inclined at both 35 ° and 45 °