



1. Toate imbinarile prin sudura se vor efectua cu electrozi tip З-42 ГОСТ 9467-75., imbinarea de sudura cu inaltimea h=4mm., lungimea - pe toata lungimea imbinarii.
2. Dupa executarea lucrarilor de sudura imbinarile trebuie curatite si executata grunduirea.
3. Protectia anticoroziva a constructiilor din metal se va efectua in corespundere cu СНУП 2.03.11-85 "Защита строительных конструкций от коррозии". Constructiile din metal trebuie sa fie grunduite cu 1 strat de grund ГФ-021 (ГОСТ 25125-82), urmata de vopsirea cu vopsea emailata ПФ-133 (ГОСТ 926-82) cu grosimea 100 мкм.
4. Plansa data se citește cu pl. - 11.

						OBIECTIV NR. - 14.05-D/21-4-SAC			
						Amenajarea teritoriului si reparatia capitala a incaperilor separate Liceul Teoretic "L.Bлага" din str. Alexandr Puskin nr. 69, mun. Balti			
Mod.	Can.	Foai	Nr.d.	Semnat.	Data				
						Inprejmuire transparenta	faza	plansa	planse
ASP		Mihaila V.		05.21			PE	12	
ISP		Hihlat E.		05.21		Nod I, II, III; Element inglobat EI-1; Sectiunea a-a, b-b, c-c, d-d	SRL "Geo-Cad-Proiect" mun. Balti		
Elaborat		Ciobanu V.		05.21					