



Application

For medical and pharmaceutical units to sterilize medical liquids, surgical instruments, dressings and fabrics, etc.



Product Features

- O Professional and systematic cycles configuration with sterilization cycles such as fabric, instrument, rubber, quick, liquid, lumen; and BD, PCD, leak test and other
- O LCD display of temperature, pressure, time, operation status and fault alarm
- O Intelligent drying system, residual humidity does not exceed 0.2% after instrument drying, and residual humidity does not exceed 1% after beddings drying
- O Built-in steam generator, microcomputer temperature control technology, saving time and energy
- Equipped with printer to print date, time and process parameters
- O Automatic over-temperature protection device, two-way safety interlock device for door pressure and temperature, safety valve for over-pressure automatic pressure relief, short-circuit protection, over-voltage protection
- O Perfect four levels of authority management system, effective prevention of mis-operation



Technical Parameters

- O Design pressure: -0.1/0.25MPa (plateau area: -0.1/0.28MPa)
- ⊙ Sterilization working temperature: 115~138°C
 ⊙ Accuracy of pressure display: 1KPa

O Vacuum lower limit: -0.080MPa

Temperature display accuracy: 0.1°C

Order No.	Chamber size (Φ×L)	Net weight	Overall dimensions (L×W×H)	Power supply	Rated Power (KW)
XG1.U-100D	400×850mm	295Kg	1250×730×1660mm	AC380V, 50Hz	11
XG1.U-100S	400×780mm	300Kg	1264×730×1660mm	AC380V, 50Hz	11
XG1.U-135D	500×710mm	350Kg	1110×750×1750mm	AC380V, 50Hz	11.5
XG1.U-135S	500×620mm	400Kg	1140×750×1750mm	AC380V, 50Hz	11.5
XG1.U-185D	500×950mm	430Kg	1350×750×1750mm	AC380V, 50Hz	11.5
XG1.U-185S	500×860mm	500Kg	1365×750×1750mm	AC380V, 50Hz	11.5
XG1.U-300D	632×1000mm	610Kg	1415×890×1780mm	AC380V, 50Hz	18
XG1.U-300S	632×890mm	800Kg	1438×890×1780mm	AC380V, 50Hz	18
XG1.U-300S	632×890mm	800Kg	1438×890×1780mm	AC380V, 50Hz	18

^{*} Voltage and frequency of some Model can be customized according to user demands. The actual voltage and frequency of the equipment is subject to the actual order.

SHINVA MEDICAL INSTRUMENT CO., LTD

Address:Xinhua Medical Scientific Zone, Zibo New & Hi-Tech Industrial Development Zone, Shandong Province, P.R. China Sales Tel: +86 533 3587720 / 3587719

Email: sales@shinva.com Website: www.shinva.com

^{*} Standard chamber marterial is 304 stainless steel, 316 stainless steel is optional.

^{*}Version: 2022. 01



XG1.U Pulse Vacuum Sterilizer

