

CATALOGUE 2021



COMPANY PROFILE

Located nearby Parma, in the North of Italy, CA-MI is an Italian family-run factory founded in the early 80's and committed in the production of electromedical equipments, namely SURGICAL SUCTION UNITS for the aspiration of human and animal fluids, used by home-care, hospital, emergency, veterinary and aesthetic professionals. With presence in over 90 countries, and listed in international organizations such as UN, UNICEF, UNFPA, CA-MI offers a comprehensive line to meet the various requirements, including a variety of designs from compact tabletop (ASKIR's), to portable with battery back-up (BR's), to professional units on castors (HOSPIVAC's). Characterized by a great versatility of applications with easy interchange of accessories, all CA-MI suction pumps are manufactured in Italy with flame retardant PC/ABS in compliance with the latest normatives and constitute a solid support whenever electric suction is required. Special attention is paid to liquid collecting jars to offer operators all options. Whether reusable or disposable, different materials and sizes are available, and can be easily replaced with the new Multi Purpose Rail system. CA-MI suction pumps are indicated for use in various specialities, finding applications in OT, ICU, General Surgery, Gastroenterology, Obstetrics, Endoscopy, ENT, Liposuction, Patient Transfer, Rescue, Ambulance Car, Veterinary, Dentistry, just to mention a few.

CA-MI is also addressing to medical and pharmacy retailers with a vast line of medical devices for home use and is one of the most preferred partners in the marketplace for OEM-basis supplies. Visitors are welcome to meet the members of the CA-MI Export Team on occasion of the major international exhibitions such as Medica in Dusseldorf (D) or Arab Health in Dubai (UAE), where we are costantly present with our entire range of medical devices.

QUALITY

Relying on in-house R&D and design departments, all CA-MI suction devices are manufactured in Italy using state-of-the-art and wear resistant materials, in compliance with: UNI EN ISO 9001:2015 and EN ISO 13485:2016 normatives and carry relevant CE 0123 number certified by German Notified Body TÜV SÜD Product Service GmbH.

CLASSIFICATIONS (MDD 93/42/EEC and subsequent changes)
Class IIa Medical Devices
All Suction Units
Class Im with function of measure

Flovac Liners and Containers

INDEX

| | SURGICAL SUCTION UNITS | |
|----|---|--|
| | OVERVIEW NEW ASPIRET NEW ASKIR 20 NEW ASKIR 30 NEW ASKIR 30 PROXIMITY ASKIR 36 BR NEW ASKIR 36 LI-ION NEW ASKIR 118 NEW ASKIR 118 NEW ASKIR 118 BASIC NEW ASKIR 230/12V BR NEW EMIVAC NEW ASKIR 30 12V ASKIR C30 BR ASKIR C30 NEW HOSPIVAC 350 NEW HOSPIVAC 400 NEW HOSPIVAC 400 NEW HOSPIVAC 350 400 - CONFIGURATIONS NEW HOSPIVAC BR JARS INTERCHANGE - MPR system JARS - REUSABLE and FLOVAC® DISPOSABLE LINERS & CONTAINERS ACCESSORIES and CONSUMABLES ALL CODES | 04 07 08 09 10 11 12 13 14 15 16 17 17 18 19 20 21 22 23 24 25 27 28 29 30 31 |
| | | MADEINTAN |
| 00 | ASKIR IIB SUCTION CONTROL | O STEER SHARE ON THE PROPERTY SHARE |
| | CR.III | |

INTRODUCTION

Intended Use

Electric suction units are medical devices used in wards, theaters, ambulances, home-care and other fields for aspirating human or animal fluids from the mouth, the airways and from operation sites by sucking the material through a cannula into a collection jar. Mobile electric suction units offer a convenient alternative to central vacuum systems.

CA-MI suction units are divided into 3 main categories:

DESK-TYPE

Portable suction units with reduced size and weight that can be easily displaced. Trolley on castors available as an option.

BATTERY-OPERATED

Suction units that besides standard operation by mains have autonomy by internal rechargeable battery.

ON CASTORS

Professional suction units on antistatic castors, offering a great choice of accessories for various applications.



Fields of application

CA-MI suction units find application in a variety of different fields, such as ENT, Tracheostomy, Endoscopy, Gastroenterology, General Surgery, Obstetrics, Veterinary, Dental, Emergency, Crash Carts, Ambulance and many others.

Configurations

All CA-MI suction units are all provided with a number of standard accessories, along with optional accessories to facilitate the operation of medical staff, professionals and lay people.

- Vacuum pump
- Vacuum regulator footswitch
- Jar for liquid collection with overflow valve to prevent liquid from going into the pump
- Hydrophobic/bacterial filter to avoid contaminations and liquid passage
- Vacuum regulator and gauge
- Suction tubes
- Wall mount for ambulances

A number of optional accessories / functions is also available

- Foot-pedal switch with double-mode operation
- Change-over function to quickly switch suction from one jar to the next
- Antistatic castors with brakes and 360° swivel for easy displacement
- Built-in rechargeable battery for operation without mains



INTRODUCTION

MAIN CHARACTERISTICS

Antibacterial/Hydrophobic Filter Single-patient filters to avoid cross contaminations and liquid passage to the pump.

Vacuum Gauge -

Analogic display in different diameters with graduated scale in mmHg and kPa (interval by 5) or digital LCD.

Liquid Collection Jar -


Single or multiple containers in different sizes and materials, reusable or disposable. Provided with cover and overflow valve system.

ON/OFF Switch –

Mechanical or digital switch.

Conical Connector -

Different diameters to connect any type of cannula.



Pump (main unit)

Oiless pumps for non-stop operation with different suction capacities, from 15 l/min to 90 l/min.

Handle for easy displacement and rear compartment for accessory storage.

Safety Trap Bottle constitutes an additional protection of the pump besides the overflow valve system inside every jar.

MPR System(Multi-Purpose Rail)
Easy interchange of CA-MI
accessories, such as rings of
various diameters to
accommodate jars of different
sizes and types, safety trap
bottles, cannula holders or a
standard medical rail where
to hook any accessory by
means of standard clamps.



4 x twin antistatic castors Ø75mm with brakes with 360° swivel.

MAIN FEATURES

| DESK-TYPE suction units | NEW ASPIRET | NEW ASKIR 20 | NEW ASKIR 30 | NEW ASKIR 30 PROXIMITY |
|---------------------------------------|-----------------------------------|-------------------|-----------------------------------|---------------------------|
| Power Feeding | 230V / 50-60Hz 120-127V / 60Hz | 230V / 50-60Hz | 230V / 50-60Hz 110-127V / 60Hz | 230V / 50-60Hz |
| Max Air Flow (wtihout accessories) | 15 l/min | 16 l/min | 40 l/min | 40 l/min |
| Max Vacuum | -563 mmHg | -563 mmHg | -600 mmHg | -600 mmHg |
| Operation | Non-stop approved | Non-stop approved | Non-stop approved | Non-stop approved |
| Proximity (touchless ON/OFF) | | | | YES |

| DESK-TYPE BATTERY | ************************************** | | | 0 × Q 6 | |
|---|--|-------------|--------------------|------------------------------------|---------------------------|
| OPERATED suction units | ASKIR 230/12V BR | ASKIR 36 BR | ASKIR 36 LI-ION | ASKIR 118 ASKIR 118 WM BASIC | ASKIR 118 ASKIR 118 WM |
| AC/DC Universal adapter 100-240V / 50-60Hz | YES | YES | YES | YES | YES |
| Car Adapter 12V | YES | YES | YES | YES (except WM model) | YES (except WM model) |
| Ambulance wall mount (12V 4A) with support and recharge functions | | | | YES (WM model only) | YES (WM model only) |
| Wall mount with support function only | Optional | Optional | Optional | | |
| Type of battery | Lead | Lead | Lithium-lon | Lithium-lon | Lithium-Ion |
| Battery Autonomy | 80 min | 60 min | 70 min | 70 min | 70 min |
| Recharge Time | 240 min | 240 min | 360 min | 360 min | 360 min |
| Max Air Flow (wtihout accessories) | 16 l/min | 36 l/min | 36 l/min | 36 l/min | 26 l/min |
| Max Vacuum | -563 mmHg | -600 mmHg | -600 mmHg | -563 mmHg | -563 mmHg |
| 10G certified | | | | YES (WM model only) | YES (WM model only) |
| Energy-saving | | | YES | YES | YES |
| Proximity (touchless ON/OFF) | | | YES | YES | YES |
| Carrying bag | Optional | Optional | Optional | YES | YES |

MAIN FEATURES



Power Feeding



NEW ASKIR 12V

12V CAR ADAPTER



NEW EMIVAC

FOOT OPERATED





| suction units | ASKIR C30 | NEW HOSPIVAC 350 | NEW HOSPIVAC 400 |
|--|--------------------|---------------------------------------|------------------------|
| Power Feeding | 220-230V / 50-60Hz | 220-230V / 50-60Hz 110-127V / 60Hz | 220-230V / 50-60Hz |
| Max Air Flow (wtihout accessories) 40 l/min | | 60 l/min | 90 l/min |
| Max Vacuum -600 mmHg | | -675 mmHg | -675 mmHg |
| Operation Non-stop approved | | Non-stop approved | Non-stop approved |
| Options | Footswitch | Footswitch Change-Over | Footswitch Change-Over |





MAIN APPLICATIONS

ENT

Home Care

Room/Ward

Tracheostomy

C€0123

NEW ASPIRET is suitable for nasal, oral and endotracheal aspiration of bodily fluids (mucus or catarrh) from adults and children. Indicated for tracheotomized patients, minor surgical applications and post-operative therapy, NEW ASPIRET finds application in out-patient and in-patient care, elderly care and in private care.

ACCESSORIES INCLUDED

- Liquid Collection Jar with overflow valve system (different options, see below)
- Silicone Tubes ø 6x10mm (autoclavable) Patient Tube length 140cm
- Conical Connector ø 8-9-10mm
- Antibacterial & Hydrophobic Filter (single-patient)
- CH20 Canula
- Power Cord with Schuko plug

OPTIONS

- Stand on 5 Castors Ø 50mm with Brakes
- (antistatic upon request) REF 27731
- Carrying Bag (for 1000ml jar) SP 0207/02
- Carrying Bag (for 2000ml jar) SP 0207
- Yankauer Handle Flat Tip with Hole 2044403
- Yankauer Handle Crown Tip with Hole 2044401
- Yankauer Tube L= 180 204413018

TECHNICAL FEATURES

 Oiless and maintenance-free piston pump Motor -Power Feeding — ____ 220-230V / 50-60Hz or 120-127V / 60Hz ISO 10079-1 Classification — HIGH VACUUM / LOW FLOW

-0.75 bar -75 kPa -563 mmHg (value at sea level - different altitudes may affect it) Max Vacuum (adjustable) —

Max free air flow rate ______ 15 l/min _____ 59,6 dBA Noise Level ———

——— Non-stop operation Duty cycle —

---- IP21 IP Code —

Weight kg 2.95 (unit packed with all accessories)

Size -___ cm 19 x 23 x 15

Years of Warranty — Shipping carton — Place of Manufacturing -



| RE 310001 | NEW ASPIRET with 1000ml Autoclavable Jar in Makrolon® (max 121°C) |
|--------------|---|
| RE 310001/01 | NEW ASPIRET with 2000ml Autoclavable Jar in Makrolon® (max 121°C) |
| RE 310001/19 | NEW ASPIRET with 1000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 310001/20 | NEW ASPIRET with 2000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 310002 | NEW ASPIRET with 1000ml Flovac®Disposable Liner |
| RE 310002/01 | NEW ASPIRET with 2000ml Flovac® Disposable Liner |





ENT

Home Care

Room/Ward

Tracheostomy





NEW ASKIR 20 is suitable for nasal, oral and endotracheal aspiration of bodily fluids (mucus or catarrh) from adults and children. Indicated for tracheotomized patients, minor surgical applications and post-operative therapy, NEW ASKIR 20 finds application in out-patient and in-patient care, elderly care and in private care.

ACCESSORIES INCLUDED

- Liquid Collection Jar with overflow valve system (different options, see below)
- Silicone Tubes ø 6x10mm (autoclavable) Patient Tube length 140cm
- Conical Connector ø 8-9-10mm
- Antibacterial & Hydrophobic Filter (single-patient)
- CH20 Canula
- Power Cord with Schuko plug

OPTIONS

- Stand on 5 Castors Ø 50mm with Brakes (antistatic upon request) REF 27730
- Carrying Bag (for 1000ml jar) SP 0207/02
- Carrying Bag (for 2000ml jar) SP 0207
- Wall Mount 27736
- Yankauer Handle Flat Tip with Hole 2044403
- Yankauer Handle Crown Tip with Hole 2044401
- Yankauer Tube L= 180 204413018

TECHNICAL FEATURES

Motor — Oiless and maintenance-free piston pump

Power Feeding — 220-230V / 50-60Hz

ISO 10079-1 Classification — HIGH VACUUM / LOW FLOW

Max Vacuum (adjustable) — -0.75 bar -75 kPa -563 mmHg (value at sea level - different altitudes may affect it)

Max free air flow rate ______ 16 l/min Noise Level _____ 60,5 dBA

Duty cycle _____ Non-stop operation

IP Code ______ IP21

Weight _____ kg 3.49 (unit packed with all accessories)

Size _____ cm 35 x 18 x 21

Years of Warranty ______ 2
Shipping carton _____ 3
Place of Manufacturing _____ Italy



MADE IN ITALY

| RE 310100/12 | NEW ASKIR 20 with 1000ml Autoclavable Jar in Makrolon® (max 121°C) |
|--------------|--|
| RE 310100/13 | NEW ASKIR 20 with 2000ml Autoclavable Jar in Makrolon® (max 121°C) |
| RE 310100/64 | NEW ASKIR 20 with 1000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 310100/70 | NEW ASKIR 20 with 2000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 310101/12 | NEW ASKIR 20 with 1000ml Flovac® Disposable Liner |
| RE 310101/13 | NEW ASKIR 20 with 2000ml Flovac® Disposable Liner |



MAIN APPLICATIONS

Endoscopy

Gastroenterology

General Surgery

Home-Care

Obstetrics

Room / Ward

Veterinary

C€0123

NEW ASKIR 30 is suitable for nasal, oral and endotracheal aspiration of bodily fluids (mucus or catarrh) from adults and children. Indicated for tracheotomized patients, surgical applications and post-operative therapy, NEW ASKIR 30 finds application in out-patient and in-patient care, elderly care, in private care and at professional level due to its powerful suction capacity of 40 l/min. The newly-designed ergonomic handle ensures a comfortable and secure grip.

ACCESSORIES INCLUDED

- Liquid Collection Jar with overflow valve system (different options, see below)
- Silicone Tubes ø 6x10mm (autoclavable) Patient Tube length 140cm
- Conical Connector ø 8-9-10mm
- Antibacterial & Hydrophobic Filter (single-patient)
- CH20 Canula
- Power Cord with Schuko plug

OPTIONS

- Stand on 5 Castors Ø 50mm with Brakes (antistatic upon request) REF 27730
- Carrying Bag (for 1000ml jar) SP 0207/02
- Carrying Bag (for 2000ml jar) SP 0207
- Footswitch SP 0068/01
- Wall Mount 27736
- Yankauer Handle Flat Tip with Hole 2044403
- Yankauer Handle Crown Tip with Hole 2044401
- Yankauer Tube L= 180 204413018

TECHNICAL FEATURES

Motor - Oiless and maintenance-free piston pump Power Feeding — — 220-230V / 50-60Hz or 110-127V / 60Hz

ISO 10079-1 Classification — HIGH VACUUM / HIGH FLOW

Max Vacuum (adjustable) — -0.80 bar -80 kPa -600 mmHg (value at sea level - different altitudes may affect it)

Max free air flow rate ______ 40 l/min ____ 60,5 dBA Noise Level -

Non-stop operation Duty cycle -

IP Code ___

kg 4.15 (unit packed with all accessories) Weight —

_____ cm 35 x 18 x 21 Size -

Years of Warranty — 2 3 Shipping carton -

Place of Manufacturing —



MADE IN ITALY

| RE 310100/02 | NEW ASKIR 30 with 1000ml Autoclavable Jar in Makrolon® (max 121°C) |
|--------------|--|
| RE 310100/03 | NEW ASKIR 30 with 2000ml Autoclavable Jar in Makrolon® (max 121°C) |
| RE 310100/74 | NEW ASKIR 30 with 1000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 310100/63 | NEW ASKIR 30 with 2000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 310101/02 | NEW ASKIR 30 with 1000ml Flovac® Disposable Liner |
| RE 310100/53 | NEW ASKIR 30 with 2000ml Flovac® Disposable Liner |

The warranty lapses immediately if the unit is used without all the required accessories or with non-original CA-MI accessories)

NEW ASKIR 30 Proximity

MAIN APPLICATIONS

Endoscopy

Gastroenterology

General Surgery

Home-Care

Obstetrics

Room / Ward

Veterinary

C€0123



NEW ASKIR 30 Proximity is suitable for nasal, oral and endotracheal aspiration of bodily fluids (mucus or catarrh) from adults and children. Indicated for tracheotomized patients, surgical applications and post-operative therapy, NEW ASKIR 30 Proximity finds application in out-patient and in-patient care, elderly care, in private care and at professional level due to its powerful suction capacity of 40 l/min. The newly-designed ergonomic handle ensures a comfortable and secure grip.

ACCESSORIES INCLUDED

- Liquid Collection Jar with overflow valve system (different options, see below)
- Silicone Tubes ø 6x10mm (autoclavable) Patient Tube length 140cm
- Conical Connector ø 8-9-10mm
- Antibacterial & Hydrophobic Filter (single-patient)
- CH20 Canula
- Power Cord with Schuko plug

OPTIONS

- Stand on 5 Castors Ø 50mm with Brakes

(antistatic upon request) REF 27730

- Carrying Bag (for 1000ml jar) SP 0207/02

- Carrying Bag (for 2000ml jar) SP 0207

- Footswitch SP 0068/01

- Wall Mount
- Yankauer Handle Flat Tip with Hole
- Yankauer Handle Crown Tip with Hole
2044401

- Yankauer Tube L= 180 204413018

TECHNICAL FEATURES

Motor — Oiless and maintenance-free piston pump

Power Feeding — 220-230V / 50-60Hz

ISO 10079-1 Classification — HIGH VACUUM / HIGH FLOW

Max Vacuum (adjustable) — -0.80 bar -80 kPa -600 mmHg (value at sea level - different altitudes may affect it)

Max free air flow rate ______ 40 l/min Noise Level _____ 60,5 dBA

Duty cycle ______ Non-stop operation

IP Code ______ IP21

Weight _____ kg 4.16 (unit packed with all accessories)

Size _____ cm 35 x 18 x 21

Years of Warranty ______ 2
Shipping carton ______ 3
Place of Manufacturing _____ Ital



MADE IN ITALY

| RE 310100/02 | NEW ASKIR 30 Proximity with 1000ml Autoclavable Jar in Makrolon® (max 121°C) |
|--------------|--|
| RE 310100/03 | NEW ASKIR 30 Proximity with 2000ml Autoclavable Jar in Makrolon® (max 121°C) |
| RE 310100/75 | NEW ASKIR 30 Proximity with 1000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 310100/62 | NEW ASKIR 30 Proximity with 2000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 310101/02 | NEW ASKIR 30 Proximity with 1000ml Flovac® Disposable Liner |
| RE 310100/53 | NEW ASKIR 30 Proximity with 2000ml Floyac® Disposable Liner |

ASKIR 36 BR



MAIN APPLICATIONS Emergency Dept. Home-Care Patient Transfer Room / Ward Tracheostomy



Veterinary

C€0123

ASKIR 36BR is a portable suction unit for professional use and with a powerful aspiration of max 36 l/min, conceived to be lightweight for easy transport. Three different options for operation: AC/DC adapter, internal lead or lithium-ion rechargeable battery and 12V make it a versatile suction unit approved for NON-STOP operation without overheating. Provided with visual and acoustic alarm indicating low battery level. The newly-designed ergonomic handle ensures a comfortable and secure grip.

ACCESSORIES INCLUDED

BATTERY-OPERATED SUCTION UNIT

- Liquid Collection Jar with overflow valve system (different options, see below)
- Silicone Tubes ø 8x14mm (autoclavable) Patient Tube length 150cm
- Conical Connector ø10-11-12mm
- Antibacterial & Hydrophobic Filter (single-patient)
- Internal rechargeable Lead Battery
- Universal switching power adapter and Cable + 12V Car Adapter

OPTIONS

- Stand on 5 Castors Ø 50mm with Brakes (antistatic upon request) REF 27730

- Carrying Bag (for 1000ml jar) SP 0207/02

- Carrying Bag (for 2000ml jar) SP 0207 - Wall Mount Brackets 27736

- Footswitch SP 0068/01 - Yankauer Handle Flat Tip with Hole 2044403

- Yankauer Handle Crown Tip with Hole 2044401

- Yankauer Tube L= 180 204413018

TECHNICAL FEATURES

| | — Oiless and maintenance-free piston pump — 14V 4A by AC/DC Universal Adapter 100-240V / 50-60Hz - 100VA | (model LIE60-140429SPA1) |
|-------------------------------|---|--------------------------|
| - | 12V 4A by AC/BC Officesal Adapter 100-240V / 30-00112 - 100VA | |
| | 12V 4A Car adapter | |
| ON/OFF Switch — | Mechanical switch | |
| ISO 10079-1 Classification —— | — HIGH VACUUM / HIGH FLOW | |
| Max Vacuum (adjustable) ——— | — -0.80 bar -80 kPa -600 mmHg (value at sea level - different altitude | es may affect it) |
| Max free air flow rate — | 36 l/min | 1.1 |
| Noise Level — | — 65,5 dBA (with jar) / 68,5 dBA (without jar) | Italian |
| Duty cycle — | — Non-stop operation (by mains only) | |
| IP Code — | IP21 | Medical |
| Weight — | — kg 5.31 (unit packed with all accessories) | ivicalcal |
| Size | cm 35 x 18 x 21 | Tollch |
| Years of Warranty — | 2 | IOUCII |
| Shipping carton — | 3 | AAADE IN ITALY |
| Place of Manufacturina ——— | — Italy | MADE IN ITALY |

| <u>-</u> | |
|--------------|--|
| RE 410200/03 | ASKIR 36BR with 1000ml Autoclavable Jar in Makrolon® (max 121°C |
| RE 410200/09 | ASKIR 36BR with 2000ml Autoclavable Jar in Makrolon® (max 121°C) |
| RE 410200/10 | ASKIR 36BR with 1000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 410200/12 | ASKIR 36BR with 2000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 410201 | ASKIR 36BR with 1000ml Flovac®Disposable Liner |
| RE 410201/01 | ASKIR 36BR with 2000ml Flovac® Disposable Liner |

PROXIMIT

MAIN APPLICATIONS

Emergency Dept.

Home-Care

Patient Transfer

Room / Ward

Tracheostomy

Veterinary



C€0123



NEW ASKIR 36 LI-ION is a portable suction unit for professional use and with a powerful aspiration of max 36 I/min, conceived to be lightweight for easy transport. Three different options for operation: AC/DC adapter, internal lead or lithium-ion rechargeable battery and 12V make it a versatile suction unit approved for NON-STOP operation without overheating. Provided with Li-lon battery, this model is equipped with a pressure sensor placed in the PCB reduces the speed of the motor when no vacuum is detected and therefore no aspiration is taking place, and with PROXIMITY function to switch ON/OFF without touch. The newly-designed ergonomic handle ensures a comfortable and secure grip. The newly-designed ergonomic handle ensures a comfortable and secure grip.

ACCESSORIES INCLUDED

- Liquid Collection Jar with overflow valve system (different options, see below)

Italy

- Silicone Tubes ø 8x14mm (autoclavable) Patient Tube length 150cm
- Conical Connector ø10-11-12mm
- Antibacterial & Hydrophobic Filter (single-patient)
- Internal rechargeable Lithium-ion Battery
- Universal switching power adapter and Cable + 12V Car Adapter

OPTIONS

- Stand on 5 Castors Ø 50mm with Brakes (antistatic upon request) REF 27730

- Carrying Bag (for 1000ml jar) SP 0207/02 SP 0207 - Carrying Bag (for 2000ml jar) - Wall Mount Brackets 27736

SP 0068/01 - Footswitch - Yankauer Handle Flat Tip with Hole 2044403

- Yankauer Handle Crown Tip with Hole 2044401

- Yankauer Tube L= 180 204413018

TECHNICAL FEATURES

| Motor — | — Oiless and maintenance-free piston pump | |
|-------------------------------|---|-------------------------|
| Power Feeding — | 14V == 4A by AC/DC Universal Adapter 100-240V / 50-60Hz - 100VA | (model UE60-140429SPA1) |
| _ | 14,8V == 5,2A Li-lon rechargeable battery - Autonomy 70 min Rec | charging Time 6 hours |
| _ | 12V 4A Car adapter | |
| ISO 10079-1 Classification —— | — HIGH VACUUM / HIGH FLOW | |
| Max Vacuum (adjustable) ——— | | es may affect it) |
| Max free air flow rate | 36 l/min | |
| Noise Level ————— | 60 dBA | |
| ON/OFF Switch — | — Soft-Touch switch | Italian |
| Duty cycle — | — Non-stop operation (by mains only) | HAHAH |
| IP Code — | IP22 | Medical |
| Weight — | — kg 4.31 (unit packed with all accessories) | Medical |
| Size — | cm 35 x 18 x 21 | Touch |
| Years of Warranty — | 2 | 100011 |
| Shipping carton ———— | 2 | MADE IN ITALY |
| Place of Manufacturing | Italy | MADE IN HALI |

AVAILABLE CONFIGURATIONS

Place of Manufacturing

| RE 410205 | NEW ASKIR 36BR LI-ION with 1000ml Autoclavable Jar in Makrolon® (max 121°C) |
|--------------|---|
| RE 410205/01 | NEW ASKIR 36BR LI-ION with 2000ml Autoclavable Jar in Makrolon® (max 121°C) |
| RE 410205/04 | NEW ASKIR 36BR LI-ION with 1000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 410205/05 | NEW ASKIR 36BR LI-ION with 2000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 410205/02 | NEW ASKIR 36BR LI-ION with 1000ml Flovac® Disposable Liner |
| RE 410205/03 | NEW ASKIR 36BR LI-ION with 2000ml Flovac® Disposable Liner |

MAIN APPLICATIONS Home-Care Patient Transfer Room/Ward Tracheostomy Emergency Veterinary Wall mount for ambulance Ambulance Car Emergency Rescue

NEW ASKIR 118 is an electric medical device for the nasal, oral and tracheal aspiration of body fluids in children or adults. It is available in two configurations, one specifically designed for use in ambulance car and emergency and the other for home-care and hospital applications. Large LCD for clear reading of vacuum values along with soft keys for vacuum adjustment increase the accuracy of aspiration. Smart operation thanks to the combination of the lightweight lithium-ion battery with the innovating FEEDBACK system that controls and manages the power of aspiration, providing a long autonomy of the battery and quiet noise level during operation. The PROXIMITY function to switch ON or OFF the device without touch prevents and avoids cross-contamination in-between patients. The unit is equipped with a long-life brushless motor eliminating any type of smell and coal residuals. The NEW ASKIR 118 series is available with various options of jar materials, such as the autoclavable polycarbonate (121°C), or the FLOVAC® disposable liners, or the APEC® that can resist up to 143°C. The ambulance wall mount is 10g dynamically tested according to the EN 1789:2007 last edition European Norm.

DIGITAL VERSION ACCESSORIES INCLUDED

- Liquid Collection Jar with overflow valve system (different options, see below)
- Silicone Tubes ø 8x14mm (autoclavable) Patient Tube length 150cm + Conical Connector ø 10-11-12mm
- Antibacterial & Hydrophobic Filter (single-patient) + CH20 Canula
- Universal switching power adapter (100-240V / 50-60Hz) and Cable
- 12V Car Adapter for RE410151/XX code only

Place of Manufacturing ——

BATTERY-OPERATED SUCTION UNIT

- Wall mount for ambulance (size cm 20x16x16) for RE410150/XX code only
- Protective Carrying Case (included for RE410150/XX / option for RE410151/XX code SP 0207/01)







DIGITAL VERSION TECHNICAL FEATURES

| BIOTIVE VEROIST VERSION | | |
|------------------------------|--|------------------------|
| Brushless Motor — | ——— Oiless and maintenance-free piston pump | |
| Power Feeding — | 14V 4A by AC/DC Universal Adapter 100-240V / 50-60Hz - 100VA (n | nodel UE60-140429SPA1) |
| | 14,8V == 5,2A Li-lon rechargeable battery - Autonomy 70 min Rech | arging Time 6 hours |
| | 12V == 4A Car adapter for RE410151/XX code only | |
| | Wall mount for ambulance (12V==4A) for RE410150/XX code only | |
| | -0.75 bar -75 kPa -563 mmHg (value at sea level - different altitudes ma | ay affect it) |
| ISO 10079-1 Classification — | HIGH VACUUM / HIGH FLOW | |
| Max free air flow rate ——— | • | Italian |
| | min. 46,7 dB max. 61,8 dB (depending on power supply) | Hallali |
| | ——— Non-stop operation (by mains only) | Medical |
| IP Code — | == | MICGICGI |
| 9 | kg 4.07 (unit packed with all accessories) | louch |
| Size — | | 100011 |
| Years of Warranty ———— | | MADEINITALY |
| Shipping carton — | 2 | MADE IN ITALY |

| DIGITAL VERSION AVAILABLE CONFIGURATIONS | ASKIR I 18 | ASKIR I 18 WM |
|---|--------------|---------------|
| NEW ASKIR 118 with 1000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 410151 | RE 410150 |
| NEW ASKIR 118 with 1000ml Autoclavable Jar in Apec®(max 143°C) | RE 410151/05 | RE 410150/05 |
| NEW ASKIR 118 with 1000ml Flovac®Disposable Liner | RE 410151/02 | RE 410150/02 |



NEW ASKIR 118 BASIC



NEW ASKIR 118 BASIC is an electric medical device for the nasal, oral and tracheal aspiration of body fluids in children or adults. It is available in two configurations, one specifically designed for use in ambulance car and emergency and the other for home-care and hospital applications. The unit is equipped with a long-life oiless piston pump motor providing 36 l/min suction capacity. The NEW ASKIR 118 BASIC series is available with various options of jar materials, such as the autoclavable polycarbonate (121°C), or the FLOVAC® disposable liners, or the APEC® that can resist up to 143°C. The ambulance wall mount is 10g dynamically tested according to the EN 1789:2007 last edition European Norm.

ANALOGIC VERSION ACCESSORIES INCLUDED

- Liquid Collection Jar with overflow valve system (different options, see below)
- Silicone Tubes ø 8x14mm (autoclavable) Patient Tube length 150cm + Conical Connector ø 10-11-12mm
- Antibacterial & Hydrophobic Filter (single-patient) + CH20 Canula
- Universal switching power adapter (100-240V 50/60Hz) and Cable
- 12V Car Adapter for RE410171/XX code only
- Wall mount for ambulance (size cm 20x16x16) for RE410170/XX code only
- Protective Carrying Case (included for RE410170/XX / option for RE410171/XX code SP 0207/01)







ANALOGIC VERSION TECHNICAL FEATURES

| ANALOGIC VERSION TE | CHINICAL FEATURES | |
|---|---|---|
| | Oiless and maintenance-free piston pump 14V = 4A by AC/DC Universal Adapter 100-240V / 50-60Hz - 100VA (m 14,8V = 5,2A Li-lon rechargeable battery - Autonomy 70 min Recha 12V = 4A Car adapter for RE410171/XX code only Wall mount for ambulance (12V = 4A) for RE410170/XX code only | |
| ISO 10079-1 Classification — Max free air flow rate — Max free air flow rate — Duty cycle — IP Code — Weight — Size — Years of Warranty — Shipping carton — | min. 54,7 dB max. 68,2 dB (depending on power supply) Non-stop operation (by mains only) IP22 kg 2.50 (unit packed with all accessories) cm 35 x 15 x 19 2 2 | y affect it) Italian Medical Touch MADE IN ITALY |
| Place of Manufacturing ——— | —— Italy | |

| ANALOGIC VERSION AVAILABLE CONFIGURATIONS | 118 BASIC | 118 BASIC WM |
|---|---------------------------|---------------------------|
| NEW ASKIR 118 BASIC with 1000ml Autoclavable Jar in Makrolon® (max 121°C) NEW ASKIR 118 BASIC with 1000ml Autoclavable Jar in Apec®(max 143°C) | RE 410171 RE 410171/03 | RE 410170 RE 410170/03 |
| NEW ASKIR 118 BASIC with 1000ml Flovac® Disposable Liner | RE 410171/03 | RE 410170/01 |



MAIN APPLICATIONS

Emergency Dept.

Home-Care

Patient Transfer

Room / Ward

Tracheostomy

Veterinary



C€0123

NEW ASKIR 230/12V BR is an electric suction unit for the aspiration of body liquids, oral, nasal and tracheal aspiration in adults or children. Suitable for emergency applications and for post-operative therapy, both in professional environment and home-care. Three different options for operation: AC/DC adapter, rechargeable battery and 12V make it a versatile suction unit approved for NON-STOP operation without overheating. Provided with visual and acoustic alarm indicating low battery level. The newly-designed ergonomic handle ensures a comfortable and secure grip.

ACCESSORIES INCLUDED

- Liquid Collection Jar with overflow valve system (different options, see below)
- Silicone Tubes ø 6x10mm (autoclavable) Patient Tube length 140cm
- Conical Connector ø 8-9-10mm
- Antibacterial & Hydrophobic Filter (single-patient) + CH20 Canula
- AC/DC Universal Adapter + Power Cord with European plug
- 12V Car Adapter

OPTIONS

- Stand on 5 Castors Ø 50mm with Brakes REF 27730 (antistatic upon request)

- Carrying Bag (for 1000ml jar) SP 0207/02

- Carrying Bag (for 2000ml jar) SP 0207

- Wall Mount 27736

- Yankauer Handle Flat Tip with Hole 2044403

- Yankauer Handle Crown Tip with Hole 2044401

- Yankauer Tube L= 180 204413018

TECHNICAL FEATURES

| Motor | —— Oiless and maintenance-free piston pump | |
|-----------------------------|--|--------------------------------|
| | —— 14V 4A by AC/DC Universal Adapter 100-240V / 50-60Hz | 100VA (modal LIE60 140429SPA1) |
| | 12V == 4A Internal rechargeable Pb battery - Autonomy 80 n | |
| | 12V == 1,9A Car adapter | illi Recharging Time 4 noors |
| | — HIGH VACUUM / LOW FLOW | |
| Max Vacuum (adjustable) ——— | -0.75 bar -75 kPa -563 mmHg (value at sea level - differen | nt altitudes may affect it) |
| Max free air flow rate | 16 l/min | |
| Noise Level | 63,0 dBA | Italian |
| Duty cycle | —— Non-stop operation (by mains only) | Hallan |
| IP Code | IP21 | Medical |
| Weight — | kg 4.55 (unit packed with all accessories) | Medical |
| Size — | | Touch |
| Years of Warranty — | 2 | IOUCII |
| Shipping carton — | 3 | |
| Place of Manufacturing ——— | —— Italy | MADE IN ITALY |

AVAILABLE CONFIGURATIONS

Place of Manufacturing —

| RE 310211 | NEW ASKIR 230/12V BR with 1000ml Autoclavable Jar in Makrolon® (max 121°C) |
|--------------|--|
| RE 310211/01 | NEW ASKIR 230/12V BR with 2000ml Autoclavable Jar in Makrolon® (max 121°C) |
| RE 310211/06 | NEW ASKIR 230/12V BR with 1000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 310211/11 | NEW ASKIR 230/12V BR with 2000ml Autoclavable Jar in Apec® (max 143°C) |
| RE 310211/03 | NEW ASKIR 230/12V BR with 1000ml Flovac® Disposable Liner |
| RE 310211/04 | NEW ASKIR 230/12V BR with 2000ml Flovac®Disposable Liner |
| | |

EMERGENCY



NEW ASKIR 30 12V is a desk-type electric suction unit for the aspiration of body liquids, oral, nasal and tracheal aspiration in adults or children. Designed for use in ambulance car. Equipped with aspiration regulator and vacuum indicator located on the front panel. Operates by 12V DC only!

NEW EMIVAC is a portable foot-operated suction unit suitable for emergency aspiration. No lubrication or battery change are needed and it's always ready for use. It can be used for soft aspirations such as tracheal suction and on small children and up to 300 mmHg. Provided with a polycarbonate 400 ml autoclavable jar with overflow valve. Foot-operated only!

ACCESSORIES INCLUDED

NEW ASKIR 30 12V

- Liquid Collection Jar with overflow valve system (different options, see below)
- Silicone Tubes ø 6x10mm (autoclavable) Patient Tube length 140cm
- Conical Connector ø 8-9-10 mm
- Antibacterial & Hydrophobic Filter (single-patient)
- CH20 Canula
- 12V Car Adapter

NEW EMIVAC

- Liquid Collection Jar with overflow valve system
- Silicone Tubes ø 6x10mm (autoclavable) Patient Tube length 140cm
- Conical Connector ø 8-9-10 mm
- Antibacterial & Hydrophobic Filter (single-patient)

| TECHNICAL FEATURES | NEW ASKIR 30 12V | NEW EMIVAC |
|--|--|--|
| Power Feeding ———————————————————————————————————— | Oiless and maintenance-free piston pump 12V HIGH VACUUM / HIGH FLOW -0.75 bar -75 kPa -563 mmHg *(value at sea level - different altitudes may affer | / Manual (foot-operated) MEDIUM VACUUM - 221/min -0.40 bar -40 kPa -300 mmHg ect it) |
| Max free air flow rate — Noise Level | 61,5 dBA Ton: 20min - Toff: 40min kg 2.50 cm 35 x 21 x 18 2 4 | 22 I/min // Foot-operated kg 1.15 cm 22 x 16 x 8 2 6 Italy ITALY |

| RE 310150/05 RE 310150/10 RE 310150/11 RE 310150/12 RE 310150/13 | NEW ASKIR 30 12V with 2000ml Autoclavable Jar in Apec® (max 143°C) NEW ASKIR 30 12V with 1000ml Flovac® Disposable Liner NEW ASKIR 30 12V with 2000ml Flovac® Disposable Liner |
|--|--|
| | |
| RE 310300 | NEW EMIVAC with 400 ml autoclavable jar in polycarbonate |







C€0123

ASKIR C30 BR is a portable suction unit for the aspiration of body liquids, oral, nasal and tracheal aspiration in adults or children. For professional use and with a powerful aspiration of max 36l/min. ASKIR C30 BR comes with double collection jars and on a stand with five antistatic castors for easy transport. Two different options for operation: AC/DC adapter and rechargeable battery in case of power black out make it a versatile suction unit approved for NON-STOP operation without overheating. Provided with visual and acoustic alarm indicating low battery level, the main unit is also equipped with vacuum-meter (mmHg & kPa) and vacuum regulator.

ACCESSORIES INCLUDED

- Liquid Collection Jar with overflow valve system (different options, see below)
- Silicone Tubes ø 8x14mm (autoclavable) Patient Tube length 150cm
- Conical Connector ø 10-11-12mm
- Antibacterial & Hydrophobic Filter (single-patient)
- Universal switching Power Adapter (100-240V/50-60Hz) + Power Cord

TECHNICAL FEATURES

| Motor — | Oiless and maintenance-free piston pump | |
|------------------------------|---|----------------------|
| Power Feeding — | 14V 4A by AC/DC Universal Adapter 100-240V / 50-60Hz - 100VA (mo | del UE60-140429SPA1) |
| _ | — 12V 4A Internal rechargeable Pb battery - Autonomy 60 min Recha | rging Time 4 hours |
| Max Vacuum (adjustable) ———— | — -0.80 bar -80 kPa -600 mmHg (value at sea level - different altitudes n | nay affect it) |
| ISO 10079-1 Classification — | — HIGH VACUUM / HIGH FLOW | |
| Max free air flow rate ———— | 36 l/min | Italian |
| Noise Level | 65,5 dBA (with jar) / 68,5 dBA (without jar) | Hallah |
| Duty cycle — | Non-stop operation (by mains only) | Medical |
| Weight — | kg 12.90 (unit packed with all accessories) | MEdical |
| Size — | cm 32 x 30 x 99 | Touch |
| Years of Warranty — | _ 2 | 104611 |
| Shipping carton — | _ 1 | |
| Place of Manufacturing — | — Italy | made in italy |

| RE 410251 | ASKIR C30 BR with 2x2000 ml autoclavable jars in polycarbonate Makrolon 2858 |
|--------------|---|
| RE 410251/01 | ASKIR C30 BR with 2x2000 ml Flovac® disposable liners and reusable containers |
| | Jars in APEC® autoclavable up to 143°C available upon request |

MAIN APPLICATIONS

Emergency Dept.

Endoscopy

Gastroenterology

General Surgery

Obstetrics

Dental Practice

C€0123



ASKIR C30 is a portable suction unit on castors for the aspiration of body liquids, oral, nasal and tracheal aspiration in adults or children. For professional use and with a powerful aspiration of max 40 l/min, ASKIR C30 comes with double collection jars and on a stand with five castors for easy transport. Main unit equipped with vacuum-meter (mmHg & kPa) and vacuum regulator.

| ACCESSORIES INCLUDED | BASIC | FS |
|---|-------|----|
| Liquid Collection Jar with overflow valve system (different options, see below) | 0 | 0 |
| Silicone Tubes ø 8x14mm (autoclavable) - Patient Tube length 150cm | 0 | 0 |
| Conical Connector ø 10-11-12mm | 0 | 0 |
| Antibacterial & Hydrophobic Filter (single-patient) + CH20 Canula | 0 | 0 |
| Power Cord with Schuko plug | 0 | 0 |
| Footswitch (may be ordered at a later time) | | 0 |

TECHNICAL FEATURES

| Motor — | Oiless and maintenance-free piston pump | |
|--|---|------------|
| Power Feeding — | 220-230V / 50-60Hz | |
| Max Vacuum (adjustable) ———— | -0.80 bar -80 kPa -600 mmHg (value at sea level - different altitudes may | affect it) |
| ISO 10079-1 Classification — | HIGH VACUUM / HIGH FLOW | |
| Max free air flow rate | 40 l/min | II _ |
| A CONTRACTOR OF THE CONTRACTOR | (1 E ID) | IT |

Noise Level -61,5 dBA Duty cycle -- Non-stop operation

kg 9.06 (unit packed with all accessories) Weight -

cm 32 x 30 x 99 Size -

Years of Warranty -Shipping carton -Place of Manufacturing -



MADE IN ITALY

| RE 410250 | ASKIR C30 BASIC with 2x2000 ml autoclavable jars in polycarbonate Makrolon 2858 |
|--------------|---|
| RE 410250/01 | ASKIR C30 FS with 2x2000 ml autoclavable jars in polycarbonate Makrolon 2858 + footswitch |
| RE 410250/10 | ASKIR C30 BASIC with 2x2000 ml Flovac® disposable liners and reusable containers |
| | Jars in APEC® autoclayable up to 143°C available upon request |





MAIN APPLICATIONS

Emergency Dept.

General Surgery

Ginecology

Neurosurgery

Obstetrics

Operating Theatre

Dental Practice

C€0123

Available in its three configurations, BASIC, FS and FULL, NEW HOSPIVAC 350 has been designed for professional aspiration of bodily fluids, tissues or bones of patients during or after surgery. The state-of-the-art 60 l/min oiless and maintenance-free pump provides high performances with excellent suction capacities and max vacuum built up within a few seconds. A clear dashboard along with a full range of accessories and antistatic castors with brakes make it the ideal device for surgical suction. The new MPR (Multi Purpose Rail) system enhances the versatility of the Hospivac series for easy and quick exchange of different accessories, with no need for tools. In fact, being equipped with five connections, all CA-MI accessories can be easily accommodated, such as rings of various diameters to fit jars of different sizes and types (2L, 3L, 5L), cannula holders or a medical stainless steel rail where to hook any other type of accessory by means of clamps. The new safety trap bottle is also a new standard accessory in the Hospivac series.

The new safety trap bottle is also a new standard accessory in the Hospivac series, bringing up to three the overflow protection systems, besides the valve integrated in the jar and the hydrophobic filter, thus providing the Hospivac series with the highest standards of safety.

| AVAILABLE MODELS AND ACCESSORIES INCLUDED | BASIC | FS | FULL |
|---|-------|----|------|
| Liquid Collection Jar with overflow valve system (different options, see below) | 2 | 2 | 2 |
| Rings to accommodate jars (3 sizes depending on the jar) | 2 | 2 | 2 |
| Safety Trap Bottle (220ml) | 1 | 1 | 2 |
| Antibacterial & Hydrophobic Filter (single-patient) | 1 | 1 | 2 |
| Silicone Tubes ø 8x14mm (autoclavable) - Patient Tube length 150cm | 1 | 1 | 2 |
| Conical Connector ø 10-11-12mm | 1 | 1 | 2 |
| Air suction inlet | 1 | 1 | 2 |
| Footswitch with intermittent or continuous operation | | 1 | 1 |
| Change-Over System from jar to jar by soft-touch keys | | | 1 |
| Power Cord with Schuko plug | 1 | 1 | 1 |

OPTIONAL ACCESSORIES

Rings available in three sizes:

- 2000 ml autoclavable jars

- 2000 ml and 3000 ml Flovac® disposable systems

- 5000 ml autoclavable jars

Cannula holder to store safely suction tube during operation

Footswitch with vacuum regulation function

Silicone Fetal Vacuum Cups

Standard medical stainless steel rail (25x10 or 30x10) and clamps

TECHNICAL FEATURES

| Motor — | Oiless and maintenance-free piston pump | |
|--------------------------------|---|------------|
| | 220-230V / 50-60Hz or 110-127V / 60Hz | |
| | -0.90 bar -90 kPa -675 mmHg (value at sea level - different altitudes may | affect it) |
| ISO 10079-1 Classification ——— | | , |
| Max free air flow rate | 60 l/min | 1+~ |
| Noise Level — | 51,7 dBA | |
| Duty cycle | Non-stop operation | 1/1 |
| Weight | 20 kg (unit alone without accessories) | IVIC |
| Size — | cm 46 x 42 x 85 | T |
| Years of Warranty — | | |
| Shipping carton ————— | 1 | |
| Place of Manufacturing ———— | . Italy | MAD |



NEW HOSPIVAC 400



Emergency Dept.

General Surgery

Ginecology

Neurosurgery

Obstetrics

Operating Theatre

Dental Practice

C€0123





MPR system
Multi Purpose Rail
See page 24

Available in its three configurations, BASIC, FS and FULL, NEW HOSPIVAC 400 has been designed for professional aspiration of bodily fluids, tissues or bones of patients during or after surgery. The state-of-the-art 90 l/min oiless and maintenance-free pump provides high performances with excellent suction capacities and max vacuum built up within a few seconds. A clear dashboard along with a full range of accessories and antistatic castors with brakes make it the ideal device for surgical suction. The new MPR (Multi Purpose Rail) system enhances the versatility of the Hospivac series for easy and quick exchange of different accessories, with no need for tools. In fact, being equipped with five connections, all CA-MI accessories can be easily accommodated, such as rings of various diameters to fit jars of different sizes and types (2L, 3L, 5L), cannula holders or a medical stainless steel rail where to hook any other type of accessory by means of clamps. The new safety trap bottle is also a new standard accessory in the Hospivac series, bringing up to three the overflow protection systems, besides the valve integrated in the jar and the hydrophobic filter, thus providing the Hospivac series with the highest standards of safety.

| AVAILABLE MODELS AND ACCESSORIES INCLUDED | BASIC | FS | FULL |
|---|-------|----|------|
| Liquid Collection Jar with overflow valve system (different options, see below) | 2 | 2 | 2 |
| Rings to accommodate jars (3 sizes depending on the jar) | 2 | 2 | 2 |
| Safety Trap Bottle (220ml) | 1 | 1 | 2 |
| Antibacterial & Hydrophobic Filter (single-patient) | 1 | 1 | 2 |
| Silicone Tubes ø 8x14mm (autoclavable) - Patient Tube length 150cm | 1 | 1 | 2 |
| Conical Connector ø 10-11-12mm | 1 | 1 | 2 |
| Air suction inlet | 1 | 1 | 2 |
| Footswitch with intermittent or continuous operation | | 1 | 1 |
| Change-Over System from jar to jar by soft-touch keys | | | 1 |
| Power Cord with Schuko plug | 1 | 1 | 1 |

OPTIONAL ACCESSORIES

Rings available in three sizes:

- 2000 ml autoclavable jars
- 2000 ml and 3000 ml Flovac $^{\! \tt B}$ disposable systems
- 5000 ml autoclavable jars

Cannula holder to store safely suction tube during operation

Footswitch with vacuum regulation function

Silicone Fetal Vacuum Cups

Standard medical stainless steel rail (25x10 or 30x10) and clamps

TECHNICAL FEATURES

Motor - Oiless and maintenance-free piston pump Power Feeding — 220-230V / 50-60Hz Max Vacuum (adjustable) — -0.90 bar -90 kPa -675 mmHg (value at sea level - different altitudes may affect it) HIGH VACUUM / HIGH FLOW ISO 10079-1 Classification — ___ 90 l/min Max free air flow rate ____ _____ 46,4 dBA Noise Level — Non-stop operation Duty cycle — _____ 21 kg (unit alone without accessories) Weight _____ ___ cm 46 x 42 x 85 Years of Warranty — Shipping carton ——— Place of Manufacturing — Italy



ON CASTORS SUCTION UNIT AVAILABLE MODELS and ACCESSORIES INCLUDED CONFIGURATIONS

| NEW HOSPIVAC 350 | | | AUTOCLAVABLE JARS | | | | | | DISPOSABLE LINERS | | |
|------------------|----------------|-------------------|--------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|----------------|----------------|
| NEW HOS | PIVAC 350 | | on° 2858 121°C) | Polysi (PS | ulfone SU) | Ap (max 1 | | Flovac® systems | | | |
| REF. | MODEL | 2 Jars 2000 ml | 2 Jars 5000 ml | 2 Jars 2000 ml | 2 Jars 5000 ml | 2 Jars 2000 ml | 2 Jars 5000 ml | 2 Jars 2000 ml | 2 Jars 3000 ml | FOOT SWITCH | CHANGE OVER |
| RE 410356 | BASIC 2 | | | | | | | | | | |
| RE 410356/06 | FS 2 | | | | | | | | | | |
| RE 410356/01 | FULL 2 | | | | | | | | | | |
| RE 410356/39 | BASIC 5 | | | | | | | | | | |
| RE 410356/40 | FS 5 | | | | | | | | | | |
| RE 410356/41 | FULL 5 | | | | | | | | | | |
| RE 410356/59 | BASIC PSU 2 | | | | | | | | | | |
| RE 410356/60 | FS PSU 2 | | | | | | | | | | |
| RE 410356/61 | FULL PSU 2 | | | | | | | | | | |
| RE 410356/62 | BASIC PSU 5 | | | | | | | | | | |
| RE 410356/63 | FS PSU 5 | | | | | | | | | | |
| RE 410356/64 | FULL PSU 5 | | | | | | | | | | |
| RE 410356/56 | BASIC AP 2 | | | | | | | | | | |
| RE 410356/38 | FS AP 2 | | | | | | | | | | |
| RE 410356/55 | FULL AP 2 | | | | | | | | | | |
| RE 410356/58 | BASIC AP 5 | | | | | | | | | | |
| RE 410356/54 | FS AP 5 | | | | | | | | | | |
| RE 410356/43 | FULL AP 5 | | | | | | | | | | |
| RE 410356/27 | BASIC FLOVAC 2 | | | | | | | | | | |
| RE 410356/29 | FS FLOVAC 2 | | | | | | | | | | |
| RE 410356/28 | FULL FLOVAC 2 | | | | | | | | | | |
| RE 410356/02 | BASIC FLOVAC 3 | | | | | | | | | | |
| RE 410356/09 | FS FLOVAC 3 | | | | | | | | | | |
| RE 410356/30 | FULL FLOVAC 3 | | | | | | | | | | |

| NEW HOSPIVAC 400 | | AUTOCLAVABLE JARS | | | | | | DISPOSABLE LINERS | | | |
|------------------|----------------|-------------------|--------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|----------------|----------------|
| NEW HOS | PIVAC 400 | | on° 2858 121°C) | Polysi (PS | ulfone SU) | Ap (max 1 | | Flovac® | Flovac® systems | | |
| REF. | MODEL | 2 Jars 2000 ml | 2 Jars 5000 ml | 2 Jars 2000 ml | 2 Jars 5000 ml | 2 Jars 2000 ml | 2 Jars 5000 ml | 2 Jars 2000 ml | 2 Jars 3000 ml | FOOT SWITCH | CHANGE OVER |
| RE 410350 | BASIC 2 | | | | | | | | | | |
| RE 410350/09 | FS 2 | | | | | | | | | | |
| RE 410350/01 | FULL 2 | | | | | | | | | | |
| RE 410350/36 | BASIC 5 | | | | | | | | | | |
| RE 410350/37 | FS 5 | | | | | | | | | | |
| RE 410350/38 | FULL 5 | | | | | | | | | | |
| RE 410350/57 | BASIC PSU 2 | | | | | | | | | | |
| RE 410350/58 | FS PSU 2 | | | | | | | | | | |
| RE 410350/59 | FULL PSU 2 | | | | | | | | | | |
| RE 410350/60 | BASIC PSU 5 | | | | | | | | | | |
| RE 410350/61 | FS PSU 5 | | | | | | | | | | |
| RE.410350/62 | FULL PSU 5 | | | | | | | | | | |
| RE 410350/40 | BASIC AP 2 | | | | | | | | | | |
| RE 410350/46 | FS AP 2 | | | | | | | | | | |
| RE 410350/33 | FULL AP 2 | | | | | | | | | | |
| RE 410350/48 | BASIC AP 5 | | | | | | | | | | |
| RE 410350/39 | FS AP 5 | | | | | | | | | | |
| RE 410350/47 | FULL AP 5 | | | | | | | | | | |
| RE 410350/08 | BASIC FLOVAC 2 | | | | | | | | | | |
| RE 410350/03 | FS FLOVAC 2 | | | | | | | | | | |
| RE 410350/11 | FULL FLOVAC 2 | | | | | | | | | | |
| RE 410350/27 | BASIC FLOVAC 3 | | | | | | | | | | |
| RE 410350/28 | FS FLOVAC 3 | | | | | | | | | | |
| RE 410350/25 | FULL FLOVAC 3 | | | | | | | | | | |



Emergency Dept.

General Surgery

Ginecology

Neurosurgery

Obstetrics

Operating Theatre

Dental Practice

C€0123



Internal Rechargeable Battery



MADE IN ITAL'

For environments where a battery back up is required, NEW HOSPIVAC BR is the unique solution for surgeons and professionals, providing high performances along with the internal rechargeable battery capable of operating the unit for for more than 4 hours in absence of mains electricity. With the Energy-Saving function, a pressure sensor placed in the PCB reduces the speed of the motor when the unit is ON and no aspiration is taking place. This extends the autonomy of the battery and reduces the noise level. Designed with fast connectors, the new Multi Purpose Rail enables the operator to easy interchange of accessories, such as rings of various diameters to accommodate jars of any sizes and types, safety trap bottles, cannula holders or a standard medical rail where to hook any accessory by means of clamps.

STANDARD ACCESSORIES INCLUDED

- 2 x Liquid Collection Jar with overflow valve system (different options, see below)
- 2 Sets of Silicone Tubes ø 8x14mm (autoclavable) Patient Tube length 150cm
- Conical Connector ø 10-11-12mm
- 2 x Antibacterial & Hydrophobic Filter (single-patient)
- Footswitch
- Power Cord with Schuko plug

FUNCTIONS

- Electronic Change-Over System from jar to jar
- Energy-saving
- Internal rechargeable battery and charger
- Footswitch with intermittent or continuous use

OPTIONS

- Vacuum Regulator Footswitch

- Cannula Container

- Silicone Fetal Vacuum Cups

TECHNICAL FEATURES

— Oiless and maintenance-free piston pump Motor — 220-230V / 50-60Hz with internal AC/DC Power Adapter Power Feeding -— Internal Rechargeable Battery (Lead-type 12V -- 20A) Battery Autonomy 250 min. - Recharging Time 8 hours Max Vacuum (adjustable) ______ -0.85 bar -85 kPa -637,5 mmHg (value at sea level - different altitudes may affect it) ISO 10079-1 Classification — HIGH VACUUM / HIGH FLOW Max free air flow rate ______ 50 I/min Absorbed Power ______90VA Duty cycle ——— Non-stop operation (by mains only) Weight _____ kg 20 _____ cm 46 x 42 x 85 Size — Years of Warranty — 2 Shipping carton —

AVAILABLE CONFIGURATIONS

Place of Manufacturing — Italy

| RE 410400 | NEW HOSPIVAC BR with 2x2000 ml autoclavable jar in polycarbonate Makrolon 2858 |
|--------------|--|
| RE 410400/03 | NEW HOSPIVAC BR with 2x5000 ml autoclavable jar in polycarbonate Makrolon 2858 |
| RE 410400/01 | NEW HOSPIVAC BR with 2x2000 ml Flovac® disposable liner and reusable container |
| RE 410400/02 | NEW HOSPIVAC BR with 2x5000 ml Flovac® disposable liner and reusable container |
| | Jars in APEC® autoclavable up to 143°C available upon request |

MPR system



Thanks to the new MPR System, HOSPIVAC series offer a great versatility to users when it comes to change type of jars for liquid collection, regardless in which configuration the suction unit has been supplied in origin. The table below shows the components of the MPR System.

| NEW HOSPIVAC SERIES JARS INTERCHANGE | | | | | | | | |
|--------------------------------------|---|---|--|--|--|--|--|--|
| COMPONENT | DESCRIPTION | REF. | | | | | | |
| | MPR - Multipurpose Rail with 5 locking slots. Supplied with each Hospivac. | 31255 | | | | | | |
| II | CAPS to close the locking slots when not in use | 31253 | | | | | | |
| | Safety trap bottle (220ml) | *** | | | | | | |
| | RING for 2L autoclavable jar RING for 5L autoclavable jar RING for 2L or 3L Flovac® RING for catheter holder | 31254 31254/01 31254/02 31254/03 | | | | | | |
| | Stainless steel standard medical rail, 25x10 Stainless steel standard medical rail, 30x10 | *** 23613 | | | | | | |
| I | Right HOOK for stainless steel rail Left HOOK for stainless steel rail | 31256 31257 | | | | | | |

| ASKIR C30 SERIES JARS INTERCHANGE | | | | | | | | | | |
|-----------------------------------|--|---|------------------------------|---|--|--|--|--|--|--|
| | TO SWITCH TO | TO SWITCH TO | TO SWITCH TO | TO SWITCH TO | | | | | | |
| EXISTING JARS | 2000 ml autoclavable jars | SWITCH TO 2000 ml oclavable jars DO NOT FIT TO SWITCH TO 2000 ml disposable liners Ring adapters SP 0078/04 to be removed from existing jar holder DO NOT FIT | 3000 ml disposable liners | | | | | | | |
| 2000 ml autoclavable jars | | DO NOT FIT | to be removed | Ring adapters SP 0078/04 to be removed from existing jar holder | | | | | | |
| 2000 ml disposable liners | Ring adapters SP 0078/04 to be inserted into existing jar holder | DO NOT FIT | | DO NOT FIT | | | | | | |

JARS

REUSABLE JARS are equipped with screw cover with handle for easy grip, autoclavable silicone o-ring for tight seal, overflow valve system integrated in the cover, clear graduated scale in ml with 100ml or 200ml intervals, CA-MI branding. Suitable for central vacuum systems and CA-MI suction units. Available in two types of polycarbonate, Makrolon® and Apec®.

| | REUSABLE | JARS in MAKROLON | N® – FOR STEAM | STERILIZATION UP | TO 121 ℃ | |
|---|----------|--|----------------|---|-----------|--|
| Low | | Jar with: cover overflow valve o-ring | Jar | Cover with: overflow valve o-ring | O-ring | Suitable for: |
| | 400 ml | RE 210301 | RE 210305 | RE 210302 | RE 210304 | EMIVAC |
| 100 - 1 | 1000 ml | RE 210001/02 | RE 210003 | RE 210352/01 | RE 210354 | ASPIRET ASKIR series (all except C30 series) Central Vacuum Plants |
| 1 m | 2000 ml | RE 210351/01 | RE 210353 | RE 210352/01 | RE 210354 | ASPIRET - ASKIR Series HOSPIVAC Series Central Vacuum Plants |
| | 4000 ml | RE 210006 | RE 210007 | RE 210008 | RE 210306 | HOSPIVAC Series Vuoto centralizzato |
| | 5000 ml | RE 210010 | RE 210013 | RE 210012 | RE 210307 | HOSPIVAC Series Central Vacuum Plants |

| REUSABLE JARS in APEC [®] 1745 – FOR STEAM STERILIZATION UP TO 143 °C | | | | | | | | | | |
|--|--|--------------|---|-----------|---|--|--|--|--|--|
| | Jar with: cover overflow valve o-ring | Jar | Cover with: overflow valve o-ring | O-ring | Suitable for: | | | | | |
| 1000 ml | RE 210009 | RE 210002 | RE 210352/02 | RE 210354 | ASPIRET ASKIR series (all except C30 series) Central Vacuum Plants | | | | | |
| 2000 ml | RE 210351/05 | RE 210353/01 | RE 210352/02 | RE 210354 | ASPIRET - ASKI R Series HOSPIVAC Series Central Vacuum Plants | | | | | |
| 5000 ml | RE 210010/01 | RE 210013/01 | RE 210012/01 | RE 210307 | HOSPIVAC Series Vuoto centralizzato | | | | | |

FLOVAC® DISPOSABLE LINERS equipped with polyethylene disposable liner, hydrophobic filter, antibacterial filter, overflow system, reusable container with clear graduated scale in ml with 50ml intervals. The gelling kit is a powder inside liners with germicidal function turning the sucked liquid into a semisolid mass, preventing cross-contamination risks of staff in charge for hygiene and waste disposal.

| | | FL | OVAC [®] DISPOSAI | BLE LINERS & | CONTAINERS | | |
|--|---------|--------------------------------|----------------------------|---|-------------------|-----------------------|--|
| | | Liner with: cover filter | | Liner with: cover filter gelling kit | | Reusable Container | Suitable for |
| | 1000 ml | 31848 | | 31858 | PLOVACE OF STREET | 31843** | ASPIRET ASKIR series (all except C30 series) |
| | 1000 ml | 31845 | | 31854 | | 31840 | Central Vacuum Plants |
| | 2000 ml | 31846 | | 31855 | | 31841 | ASPIRET - ASKIR Series HOSPIVAC Series Central Vacuum Plants |
| | 3000 ml | 31847 | | 31856 | 1 = 3 | 31842 | HOSPIVAC Series Central Vacuum Plants |

^{**} Requires additional round spacer (SP.0220) when ordered for ASKIR Series



The disposable soft LINER is made in polyethylene and is hermetically welded to a rigid lid inside which the hydrophobic, antireflux and antibacterial filter is placed. This filter also operates as overflow valve system deactivating suction whenever maximum fill capacity is reached. The liner has to be placed in its dedicated reusable and autoclavable FLOVAC® rigid CONTAINER in policarbonate. FLOVAC® systems replace therefore the use of autoclavable jars, decreasing the costs for cleaning and sterilization. A full line of accessories make FLOVAC® line the ideal partner for collecting liquids and fluids.

FLOVAC® LINER TECHNICAL FEATURES

| Lid material | HDPE (high density polyethylene) |
|-----------------------------|--|
| "VACUUM" port | Conic connector, female |
| "PATIENT" port | |
| "TANDEM" port | Ø 8.0 ÷ 9.2 mm |
| Maximum suction value | |
| Maximum graduation interval | 50 ml |
| Patient hose size | Inner $\emptyset \ge 6$ mm L=2.5 m max |
| Vacuum hose size | Inner $\emptyset \ge 6$ mm L=1.8 m max |

FLOVAC® FILTER TECHNICAL FEATURES

| Filtration efficiency (typical) | $>$ 99.99995% with particle size of 0.1 μ |
|---------------------------------|---|
| Membrane | 100% expanded PTFE GORE™ Medical Membrane |
| Prefilter | micro fiberglass |
| Support | non-woven PE/PES |



| Support ring for FLOVAC® container (all sizes) with 25x5 slide | 970010210 | |
|--|-----------|---|
| Support ring for FLOVAC® container (all sizes) with 30x5 slide | 970010220 | |
| Support ring for FLOVAC® container (all sizes) with 41x4 slide (also suitable for BAXTER wall slide) | 970010214 | 1 |
| Support ring for FLOVAC® container with 45x5 slide (also suitable for ABBOT wall slide) | 970010215 | |
| Support ring for autoclavable jars (1000 and 2000 ml) with 25x5 slide | 920200422 | |
| ON-OFF tap for mounting on FLOVAC® container support ring | 000010057 | |
| ON-OFF tap with control vacuum gauge for mounting on FLOVAC® container support ring | 000010056 | 2 |
| Plastic wall slide 25x5 | 920200004 | |
| Plastic wall slide 30x5 | 920200029 | 3 |
| Plastic wall slide 45x5 | 920200477 | |
| Metal clamp (chrome-plated) for 30x10 rail with slide 25x5 | 000230000 | |
| Plastic clamp (technopolymer) for 30x10 rail with slide 25x5 | 000230500 | 4 |
| 4-place trolley for FLOVAC® container with support ring, ON-OFF tap and control vacuum gauge | 000260950 | |
| 4-place trolley for FLOVAC® container with support ring, ON-OFF tap and control vacuum regulator | 000260955 | |
| 4-place trolley for FLOVAC® with support ring | 000260953 | |
| 2-place trolley for FLOVAC® container with support ring, ON-OFF tap and control vacuum gauge | 000260951 | 5 |
| 2-place trolley for FLOVAC® container with support ring, ON-OFF tap and control vacuum regulator | 000260956 | |
| 2-place trolley for FLOVAC® with support ring | 000260954 | |
| Tandem tube Ø 8x11 L=0.38 m for cascade connection | 970010120 | 6 |
| Disposable vacuum breaker | 000320000 | 7 |
| Disposable vacuum breaker with 1.8m hose | 000320010 | 8 |
| Specimen container | 000036100 | 9 |
| | | |



SPARE ACCESSORIES

| | | ASPIRET ASKIR 20 ASKIR 30 ASKIR 230-12V BR ASKIR 30 12V | ASKIR 36 BR ASKIR 36 LI-ION ASKIR 118 ASKIR 118 BASIC | EMIVAC | ASKIR C30 ASKIR C30 BR | HOSPIVAC 350 HOSPIVAC 400 HOSPIVAC BR |
|--|---|---|--|------------------|---------------------------|---|
| | SET of silicone TUBES, FILTERS of | and CONICAL CO | ONNECTORS | | | |
| 1 | Tube Ø 6x10mm Conical connector | RE 210355 | | RE 210355/01 | | |
| | Tube Ø 6x10mm Conical connector Antibacterial filter | SP 0036 | | SP 0043 | | |
| and the | Tube Ø 8 x 14 mm Conical connector | | RE 210355/03 | | RE 210355/03 | RE 210355/03 |
| | Tube Ø 8 x 14 mm Conical connector Antibacterial filter | | SP 0036/02 | | SP 0036/02 | SP 0032/01 (for 350 and BR) SP 0032 (for Hospivac 400) |
| | FLOVAC* liners Tube Ø 6x10mm Conical connector | SP 0158/01 | | | | |
| A. B. B. A. | FLOVAC* liners Tube Ø 8x14mm Conical connector | | SP 0160/01 | | SP 0160/01 | SP 0160/01 |
| | Roll of silicone tube Ø 6x10 mm | Length 1m = SP | 0045/02 - Lengt | th 10m = SP 0045 | 5/03 - Length 50r | m = SP 0045/04 |
| | Roll of silicone tube Ø 8X14 mm | Length 1m = SP | 0045/05 - Lengt | th 10m = SP 0045 | 5/06 - Length 50r | m = SP 0045/07 |
| | MALE CONNECTORS | | | | | |
| Comment of the last | Ø 8-9-10 mm (pack of 5's) | SP 0223 | SP 0223 | | SP 0223 | SP 0223 |
| | CONICAL CONNECTORS | | | | | |
| Maria | Ø 8-9-10 mm | RE 210410 | | RE 210410 | | |
| Contract of the Contract of th | Ø 10-11-12 mm | | RE 210420 | | RE 210420 | RE 210420 |
| | FILTERS (Antibacterial and Hydro | • | | | | |
| | Ø 64 with 8 mm connector | SP 0046 | | SP 0046 | | SP 0121 |
| | Ø 64 with 11mm connector | | SP 0121 | | SP 0121 | SP 0121 (350 and BR only) |
| | Ø 90 with 11mm connector | | | | | SP 0047 (for 400 only) |
| | ASPIRATION PROBES | | | | | |
| | CH20 | RE 210400 (10 pcs) | RE 210400 (10 pcs) | | RE 210400 (10 pcs) | |
| | YANKAUER CANNULAS | | | | | |
| à- | Yankauer Handle Flat Tip with Hole | 2044403 | 2044403 | 2044403 | 2044403 | 2044403 |
| | Yankauer Handle Crown Tip with Hole | 2044401 | 2044401 | 2044401 | 2044401 | 2044401 |
| | Yankauer Tube L= 180 | 204413018 | 204413018 | 204413018 | 204413018 | 204413018 |
| | CATHETER CONTAINER | | | | | |
| = | Tube of polycarbonate Ø 54 mm by 400 mm length. Fully autoclavable (121°C - 15 min) | | | | | 000032 |
| | SILICONE FETAL VACUUM CUP | S | | | | |
| 本本本 | Length 210 mm, Ø 50 mm, size XS | | | | VC-95100 | VC-95100 |
| İİİ | Length 210 mm, Ø 60 mm, size S | | | | VC-95200 | VC-95200 |
| 9 9 9 | Length 210 mm, Ø 70 mm, size M | | | | VC-95300 | VC-95300 |

AND CONSUMABLES

| | ASPIRET ASKIR 20 ASKIR 30 ASKIR 230-12V BR ASKIR 30 12V | ASKIR 36 BR ASKIR 36 LI-ION ASKIR 118 ASKIR 118 BASIC | EMIVAC | ASKIR C30 ASKIR C30 BR | HOSPIVAC 350 HOSPIVAC 400 HOSPIVAC BR |
|--|---|--|--------|----------------------------|---|
| VACUUM GAUGE in mmHg and Kpa | | | | | |
| Ø 40 mm with graduated scale | SP 0018 (for Aspiret) | | | | |
| Ø 50 mm with graduated scale | SP 0017 (for Askir) | SP 0017 (except ASKIR 118) | | SP 0017 | |
| Ø 63 mm with graduated scale | | | | | SP 0073 |
| ELECTRONIC BOARD | | | | | |
| for ASKIR 36 LI-ION, ASKIR 118 BASIC | | SP 0272 | | | |
| for ASKIR 230/12V BR, ASKIR 36BR | SP 0205 | SP 0205 | | | |
| for ASKIR C30 - FS version | | | | SP 0107 | |
| for ASKIR C30 BR | | | | SP 0205/01 | |
| for HOSPIVAC – BASIC version | | | | | SP 0107/02 |
| for HOSPIVAC – version FS and FULL | | | | | SP 0107/03 |
| for HOSPIVAC BR | | | | | SP 0271 |
| ON/OFF SWITCH | | | | | |
| Pack of 2's for ASPIRET, ASKIR 20 and 30 | SP 0009/04 | | | | |
| Pack of 2's for ASKIR 230/12V BR, 36 BR, C30 BR | SP 0009/08 | SP 0009/08 | | SP 0009/08 | |
| Pack of 1's for ASKIR C30, HOSPIVAC – BASIC | | - | | SP 0009/07 | SP 0009/07 |
| BATTERY PACK | | | | | 2 |
| Lead type for ASKIR 230/12V BR, 36 BR, C30 BR | SP 0012/01 | SP 0012/01 | | SP 0012/01 | |
| Li-ion type for ASKIR 36 LI-ION, 118, 118 BASIC | | SP 0012/03 | | | |
| Lead type for HOSPIVAC BR | | , | | | SP 0012/04 |
| WALL MOUNT | | | | | - |
| | | ASU 118 | | | |
| For ambulance, with recharge and operation function (12V 4A) | | (118-WM only) | | | |
| Wall mount for support | 27736 (except Aspiret and Twin) | 27736 (36 models only) | | | |
| FOOT-SWITCH CONTROL | | | | | |
| Footswitch intermittent or continuous operation | | | | SP 0068/01 (FS version) | SP 0068/01 (FS and FULL) |
| STAND on CASTORS | | | | | |
| Stand on 5 castors with brakes (antistatic upon request) | 27731 (for ASPIRET) | 27730 | | | SP 0113/01 (BASIC version) |
| Base on 4 antistatic castors only for HOSPIVAC | 27730 (for ASKIR serie) | (36BR and LI-ION) | | SP 0213 | SP 0113/03 (FS and FULL) |
| POWER ADAPTER | | | | | |
| Car adapter 12V for ASKIR 30 12V | SP 0021/01 | SD 0007/00 | | | |
| Car adapter 12V | SP 0007/02 (for 230 12V BR) | SP 0007/02 (not for 118 WM) | | | |
| Power adapter AC/DC | SP 0208/01 (for 230 12V BR) | SP 0208/01 | | SP 0208/01 (for C30 BR) | |
| Power cord | SP 0020/03 (for 230 12V BR) | SP 0020/03 | | SP 0020/03 (for C30 BR) | |
| CARRY BAG | | | | | |
| for any model with 1000 ml jar | SP 0207/02 | SP 0207/02 | | | |
| for any model with 2000 ml jar | SP 0207 | SP 0207 | | | |
| for ASKIR 118 | | SP 0207/01 — | | | |

DESK-TYPE









| MODEL | TYPE of JAR / CONFIGURATION | REF- NO. |
|-------------------------|--|--------------|
| NEW ASPIRET: | 1000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 310001 |
| | 2000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 310001/01 |
| | 1000ml Autoclavable Jar in Apec® (max 143°C) | RE 310001/19 |
| | 2000ml Autoclavable Jar in Apec® (max 143°C) | RE 310001/20 |
| | 1000ml Flovac® Disposable Liner | RE 310002 |
| | 2000ml Flovac® Disposable Liner | RE 310002/01 |
| NEW ASKIR 20: | 1000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 310100/12 |
| | 2000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 310100/13 |
| | 1000ml Autoclavable Jar in Apec® (max 143°C) | RE 310100/64 |
| | 2000ml Autoclavable Jar in Apec® (max 143°C) | RE 310100/70 |
| | 1000ml Flovac® Disposable Liner | RE 310101/12 |
| | 2000ml Flovac® Disposable Liner | RE 310101/13 |
| NEW ASKIR 30: | 1000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 310100/02 |
| | 2000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 310100/03 |
| | 1000ml Autoclavable Jar in Apec® (max 143°C) | RE 310100/74 |
| | 2000ml Autoclavable Jar in Apec® (max 143°C) | RE 310100/63 |
| | 1000ml Flovac® Disposable Liner | RE 310101/02 |
| | 2000ml Flovac® Disposable Liner | RE 310100/53 |
| NEW ASKIR 30 Proximity: | 1000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 310100/02 |
| | 2000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 310100/03 |
| | 1000ml Autoclavable Jar in Apec® (max 143°C) | RE 310100/75 |
| | 2000ml Autoclavable Jar in Apec® (max 143°C) | RE 310100/62 |
| | 1000ml Flovac® Disposable Liner | RE 310101/02 |
| | 2000ml Flovac® Disposable Liner | RE 310100/53 |
| | | |

EMERGENCY suction units





| MODEL | TYPE of JAR / CONFIGURATION | REF- NO. |
|------------------|--|--|
| NEW ASKIR 30 12V | 1000ml Autoclavable Jar in Makrolon® (max 121°C) 2000ml Autoclavable Jar in Makrolon® (max 121°C) 1000ml Autoclavable Jar in Apec® (max 143°C) 2000ml Autoclavable Jar in Apec® (max 143°C) 1000ml Flovac® Disposable Liner 2000ml Flovac® Disposable Liner | RE 310150/02 RE 310150/05 RE 310150/10 RE 310150/11 RE 310150/12 RE 310150/13 |
| NEW EMIVAC | 400 ml Autoclavable Jar in Policarbonate | RE 310300 |







| MODEL | | TYPE of JAR / CONFIGURATION | REF- NO. |
|------------------|-----------------|---|------------------------------|
| ASKIR C30 | BASIC | Double 2000ml Autoclavable Jars in Makrolon® (max 121°C) | RE 410250 |
| | FS | Double 2000ml Makrolon® Jars + Footswitch | RE 410250/01 |
| | BASIC AP | Double 2000ml Autoclavable Jars in Apec® (max 143°C) | RE 410250/16 |
| | FS AP | Double 2000ml Apec® Jars + Footswitch | RE 410250/15 |
| | BASIC FLOVAC | Double 2000ml Flovac® Disposable Liners | RE 410250/10 |
| | FS FLOVAC | Double 2000ml Flovac® Liners + Footswitch | RE 410250/14 |
| NEW HOSPIVAC 350 | BASIC 2 | Double 2000ml Autoclavable Jars in Makrolon® (max 121°C) | RE 410356 |
| | FS 2 | Double 2000ml Makrolon® Jars + Footswitch | RE 410356/06 |
| | FULL 2 | Double 2000ml Makrolon® Jars + Footswitch + Change-Over | RE 410356/01 |
| | BASIC 5 | Double 5000ml Autoclavable Jars in Makrolon® (max 121°C) | RE 410356/39 |
| | FS 5 | Double 5000ml Makrolon® Jars + Footswitch | RE 410356/40 |
| | FULL 5 | Double 5000ml Makrolon® Jars + Footswitch + Change-Over | RE 410356/41 |
| | BASIC PSU 2 | Double 2000ml Autoclavable Jars in Polysulfone | RE 410356/59 |
| | FS PSU 2 | Double 2000ml Polysulfone Jars + Footswitch | RE 410356/60 |
| | FULL PSU 2 | Double 2000ml Polysulfone Jars + Footswitch + Change-Over | RE 410356/61 |
| | BASIC PSU 5 | Double 5000ml Autoclavable Jars in Polysulfone | RE 410356/62 |
| | FS PSU 5 | Double 5000ml Polysulfone Jars + Footswitch | RE 410356/63 |
| | FULL PSU 5 | Double 5000ml Polysulfone Jars + Footswitch + Change-Over | RE 410356/64 |
| | BASIC AP 2 | Double 2000ml Autoclavable Jars in Apec® (max 121°C) | RE 410356/56 |
| | FS AP 2 | Double 2000ml Apec® Jars + Footswitch | RE 410356/38 |
| | FULL AP 2 | Double 2000ml Apec® Jars + Footswitch + Change-Over | RE 410356/55 |
| | BASIC AP 5 | Double 5000ml Autoclavable Jars in Apec® (max 121°C) | RE 410356/58 |
| | FS AP 5 | Double 5000ml Apec® Jars + Footswitch | RE 410356/54 |
| | FULL AP 5 | Double 5000ml Apec® Jars + Footswitch + Change-Over | RE 410356/43 |
| | BASIC FLOVAC 2 | Double 2000ml Flovac® Liners | RE 410356/27 |
| | FS FLOVAC 2 | Double 2000ml Flovac® Liners + Footswitch | RE 410356/29 |
| | FULL FLOVAC 2 | Double 2000ml Flovac® Liners + Footswitch + Change-Over | RE 410356/28 |
| | BASIC FLOVAC 3 | Double 3000ml Flovac® Liners | RE 410356/02 |
| | FS FLOVAC 3 | Double 3000ml Flovac® Liners + Footswitch | RE 410356/09 |
| NEW LOCDIVAC 400 | FULL FLOVAC 3 | Double 3000ml Flovac® Liners + Footswitch + Change-Over | RE 410356/30 |
| NEW HOSPIVAC 400 | BASIC 2 | Double 2000ml Autoclavable Jars in Makrolon® (max 121°C) | RE 410350 |
| | FS 2 | Double 2000ml Makrolon® Jars + Footswitch | RE 410350/09 |
| | FULL 2 | Double 2000ml Makrolon® Jars + Footswitch + Change-Over | RE 410350/01 |
| | BASIC 5 FS 5 | Double 5000ml Autoclavable Jars in Makrolon® (max 121°C) Double 5000ml Makrolon® Jars + Footswitch | RE 410350/36 |
| | FULL 5 | Double 5000ml Makrolon® Jars + Footswitch + Change-Over | RE 410350/37 RE 410350/38 |
| | BASIC PSU 2 | Double 2000ml Autoclavable Jars in Polysulfone | RE 410350/57 |
| | FS PSU 2 | Double 2000ml Polysulfone Jars + Footswitch | RE 410350/57 |
| | FULL PSU 2 | Double 2000ml Polysulfone Jars + Footswitch + Change-Over | RE 410350/58 |
| | BASIC PSU 5 | Double 5000ml Autoclavable Jars in Polysulfone | RE 410350/60 |
| | FS PSU 5 | Double 5000ml Polysulfone Jars + Footswitch | RE 410350/61 |
| | FULL PSU 5 | Double 5000ml Polysulfone Jars + Footswitch + Change-Over | RE.410350/62 |
| | BASIC AP 2 | Double 2000ml Autoclavable Jars in Apec® (max 121°C) | RE 410350/40 |
| | FS AP 2 | Double 2000ml Apec® Jars + Footswitch | RE 410350/46 |
| | FULL AP 2 | Double 2000ml Apec® Jars + Footswitch + Change-Over | RE 410350/33 |
| | BASIC AP 5 | Double 5000ml Autoclavable Jars in Apec® (max 121°C) | RE 410350/48 |
| | FS AP 5 | Double 5000ml Apec® Jars + Footswitch | RE 410350/39 |
| | FULL AP 5 | Double 5000ml Apec® Jars + Footswitch + Change-Over | RE 410350/47 |
| | BASIC FLOVAC 2 | Double 2000ml Flovac® Liners | RE 410350/08 |
| | FS FLOVAC 2 | Double 2000ml Flovac® Liners + Footswitch | RE 410350/03 |
| | FULL FLOVAC 2 | Double 2000ml Flovac® Liners + Footswitch + Change-Over | RE 410350/11 |
| | BASIC FLOVAC 3 | Double 3000ml Flovac® Liners | RE 410350/27 |
| | FS FLOVAC 3 | Double 3000ml Flovac® Liners + Footswitch | RE 410350/28 |
| | FULL FLOVAC 3 | Double 3000ml Flovac® Liners + Footswitch + Change-Over | RE 410350/25 |

DESK-TYPE BATTERY OPERATED suction units











| MODEL | TYPE of JAR / CONFIGURATION | REF- NO. |
|------------------------|--|--------------|
| NEW ASKIR 118 | 1000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 410151 |
| | 1000ml Autoclavable Jar in Apec® (max 143°C) | RE 410151/05 |
| | 1000ml Flovac® Disposable Liner | RE 410151/02 |
| NEW ASKIR 118-WM | 1000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 410150 |
| | 1000ml Autoclavable Jar in Apec® (max 143°C) | RE 410150/05 |
| | 1000ml Flovac® Disposable Liner | RE 410150/02 |
| NEW ASKIR 118 BASIC | 1000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 410171 |
| | 1000ml Autoclavable Jar in Apec® (max 143°C) | RE 410171/03 |
| | 1000ml Flovac® Disposable Liner | RE 410171/01 |
| NEW ASKIR 118 BASIC-WM | 1000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 410170 |
| | 1000ml Autoclavable Jar in Apec® (max 143°C) | RE 410170/03 |
| | 1000ml Flovac® Disposable Liner | RE 410170/01 |
| NEW ASKIR 230/12V BR | 1000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 310211 |
| | 2000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 310211/01 |
| | 1000ml Autoclavable Jar in Apec® (max 143°C) | RE 310211/06 |
| | 2000ml Autoclavable Jar in Apec® (max 143°C) | RE 310211/11 |
| | 1000ml Flovac® Disposable Liner | RE 310211/03 |
| | 2000ml Flovac® Disposable Liner | RE 310211/04 |
| ASKIR 36BR (LEAD) | 1000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 410200/03 |
| | 2000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 410200/09 |
| | 1000ml Autoclavable Jar in Apec® (max 143°C) | RE 410200/10 |
| | 2000ml Autoclavable Jar in Apec® (max 143°C) | RE 410200/12 |
| | 1000ml Flovac® Disposable Liner | RE 410201 |
| | 2000ml Flovac® Disposable Liner | RE 410201/01 |
| ASKIR 36BR (LI-ION) | 1000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 410205 |
| | 2000ml Autoclavable Jar in Makrolon® (max 121°C) | RE 410205/01 |
| | 1000ml Autoclavable Jar in Apec® (max 143°C) | RE 410205/04 |
| | 2000ml Autoclavable Jar in Apec® (max 143°C) | RE 410205/05 |
| | 1000ml Flovac® Disposable Liner | RE 410205/02 |
| | 2000ml Flovac® Disposable Liner | RE 410205/03 |
| | | |

ON CASTORS
BATTERY
OPERATED
suction units





| MODEL | | TYPE of JAR / CONFIGURATION | REF- NO. |
|-----------------|---|--|---|
| ASKIR C30 BR | BASIC BASIC AP BASIC FLOVAC | Double 2000ml Autoclavable Jars in Makrolon® (max 121°C) Double 2000ml Autoclavable Jars in Apec® (max 143°C) Double 2000ml Flovac® Disposable Liners | RE 410251 RE 410251/03 RE 410251/01 |
| NEW HOSPIVAC BR | FULL 2 FULL 5 FULL FLOVAC 2 FULL FLOVAC 3 | Double 2000ml Makrolon® Jars + Footswitch + Change-Over Double 5000ml Makrolon® Jars + Footswitch + Change-Over Double 2000ml Flovac® Liners + Footswitch + Change-Over Double 3000ml Flovac® Liners + Footswitch + Change-Over | RE 410400 RE 410400/03 RE 410400/01 RE 410400/02 |









EC Certificate

Production Quality Assurance System Directive 93/42/EEC on Medical Devices (MDD), Annex V (Devices in Class IIa, IIb or III)

No. G2 063105 0047 Rev. 01

Manufacturer: CA-MI S.R.L.

> Via Ugo La Malfa, 13 Frazione Pilastro 43013 Langhirano (PR)

ITALY

Product Aerosol Therapy Equipment, Kits for Aerosol Therapy, Thermal Water Inhaler, Suction Unit, Surgical Suction

Equipment, Breast Pump, Kit Accessory for Electric Breast Pump, Blood Pressure Monitor, Electronic Thermometer, Infrared Thermometer, Tens Device,

Pulse Oximeter

The Certification Body of TÜV SÜD Product Service GmbH declares that the aforementioned manufacturer has implemented a quality assurance system for manufacture and final inspection of the respective devices / device categories in accordance with MDD Annex V. This quality assurance system conforms to the requirements of this Directive and is subject to periodical surveillance. For marketing of class IIb and III devices an additional Annex III certificate is mandatory. All applicable requirements of the testing and certification regulation of TÜV SÜD Group have to be complied with. For details and certificate validity see: www.tuvsud.com/ps-cert?q=cert:G2 063105 0047 Rev. 01

ITA1626749 Report No.:

Valid from: 2021-02-09 Valid until: 2024-05-26

Date, 2021-02-09

Category(ies):

Christoph Dicks

Head of Certification/Notified Body







Product Service

Certificate

No. Q5 063105 0045 Rev. 03

Holder of Certificate: CA-MI S.R.L.

Via Ugo La Malfa, 13 Frazione Pilastro

43013 Langhirano (PR)

ITALY

Certification Mark:



Scope of Certificate:

Design and development, production, service and sale of medical equipments for surgery (electrical and manual suction pumps), electric breast pumps, medical devices for breathing (aerosol therapy equipments and thermal water inhaler) and related accessories, medical devices for monitoring of vital physiological parameters (pulse oximeters, thermometers, blood pressure monitors, sphygmomanometer and stethoscopes), incentive spirometers and medical devices for phlebology (graduated compression medical stockings). Distribution of active and non-active non implantable medical devices.

The Certification Body of TÜV SÜD Product Service GmbH certifies that the company mentioned above has established and is maintaining a quality management system, which meets the requirements of the listed standard(s). All applicable requirements of the testing and certification regulation of TÜV SÜD Group have to be complied with. For details and certificate validity see: www.tuvsud.com/ps-cert?q=cert:Q5-063105-0045-Rev.03

Report No.: ITA1885389

 Valid from:
 2022-08-02

 Valid until:
 2025-08-01

Date, 2022-08-02 Christoph Dicks

Head of Certification/Notified Body





Certificate

No. Q5 063105 0045 Rev. 03

Applied Standard(s): EN ISO 13485:2016

Medical devices - Quality management systems -

Requirements for regulatory purposes

(ISO 13485:2016) DIN EN ISO 13485:2016

Facility(ies): CA-MI S.R.L.

Via Ugo La Malfa, 13, Frazione Pilastro, 43013 Langhirano (PR),

ITALY

Design and development, production, service and sale of medical equipments for surgery (electrical and manual suction pumps), electric breast pumps, medical devices for breathing (aerosol therapy equipments and thermal water inhaler) and related accessories, medical devices for monitoring of vital physiological parameters (pulse oximeters, thermometers, blood pressure monitors, sphygmomanometer and stethoscopes), incentive spirometers and medical devices for phlebology (graduated compression medical stockings). Distribution of active and non-active non implantable medical devices.

CA-MI S.r.I.

Via Strada per Parma 34, Frazione Pilastro, 43013 Langhirano (PR), ITALY

Warehouse of active and non-active non implantable medical devices and components used in production.

CA-MI S.r.I.

Via Ugo La Malfa 27, Frazione Pilastro, 43013 Langhirano (PR), ITALY

Production of medical devices for surgery (electrical and manual suction pumps), warehouse of active and non-active non implantable medical devices and components used in production.