

Name Bezel color Type-model Panel Viewable image size Max view area (W x H) Native resolution Aspect ratio Pixel pitch (mm) Dot/Pixel per Inch Brightness Contrast ratio Pixel response time Color gamut Viewing angle at 10:1 CR Stand Bezel width Dimensions (HxWxD) Power supply Weight Limited warranty Available date		T24i Wide Flat Panel Monitor Black 61A6MAR3US / 61A6MAT3EU / 61CEMAT2EU TFT-LCD, In-Plane Switching (IPS), White LED backlight 23.8" (604.7mm) diagonal 20.75" x 11.67" (527.04mm x 296.5mm) 1920x1080 16:9 0.2745 x 0.2745 mm 93 dpi 250 nits or cd/m² (typical) 1000:1 (typical) 6ms (typical) 72% 178° (+/- 89°) horizontal, 178° (+/- 89°) vertical Tilt, swivel, pivot, and height adjustable stand Sides: 0.08" (2.0mm) 14.7" H x 21.26" W x 10.3" D; 373.4mm H x 540.2mm W x 261.75mm D 16.5 watts typical, 55 watts maximum (with USB 3.0 hub), <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) 11.57 lb; 5.25 kg 3 year (includes backlight) April 2017		Features • Widescreen 23.8-inch monitor • Supports 1920x1080 resolution • Supports ThinkCentre Tiny Clamp Bracket • Supports optional soundbar • Includes dual input connection for attachment to two systems concurrently • EPEAT Gold certified • Microsoft® Windows® 7 certified • Microsoft Windows 10 certified	
VESA-compliant Power management Ergonomics Emission standards Environmental		VESA DDC2B/CI ENERGY STAR® qualified ISO 9241-307 FCC Class B TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, RoHS, EPEAT™ Gold rating		 ThinkVision T24i Wide Monitor	
Preset resolutions		VGA: 640x480, 720x400 SVGA: 800x600 XGA: 1024x768 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900, 1680x900 WSXGA+: 1680x1050 Full HD: 1920x1080 HDMI: 17; DP: 17			
Viewing adjustments Rotating screen On screen display Control features USB hub Multiple input Monitor connectors		Tilt: 30° back, -5° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand Screen pivots 90 degrees from landscape to portrait On screen display with digital user controls (8 languages) Direct access (buttons on front) for power, menu, input source select and brightness and automatic image setup USB 3.0 Hub: 1 port into PC (USB 3.0); 4 ports for accessories (4 USB 3.0) Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue (2) HDMI (1.4), digital, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)			
Signal cables Mounting features Security					
Ship group		Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter USB signal cable, 1.8 meter black power cord			
Limited Warranty See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281		Accessories Kensington MicroSaver Cable Lock73P2582 Kensington Twin Head Cable Lock45K1620 See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision			