



NSP 6060 Serisi Paslanmaz Pompa
NSP 6060 Series Stainless Steel Pumps

Pompa Tipi Pump Type Type De Pompe Tipo De Bomba نوع المضخة	Motor Tipi Motor Type Type de moteur Tipo de motor نوع المحرك			Su Miktarı / Flow Rate Quantité d'eau / Caudal / كمية الماء							
	Type	KW	HP	m3/h	0	20	40	50	60	70	78
				lt/sn	0.0	5.6	11.1	13.9	16.7	19.4	21.7
NSP 6060-01	4"	2.2	3	14	13	9	8	7	4	1	
NSP 6060-02	4" - 5" - 6"	4	5.5	28	26	19	17	15	10	5	
NSP 6060-03	4" - 5" - 6"	5.5	7.5	42	39	30	26	23	16	10	
NSP 6060-04	4" - 5" - 6"	7.5	10	56	52	41	35	31	22	14	
NSP 6060-05	5" - 6"	9.2	12.5	71	66	51	44	39	28	18	
NSP 6060-06	5" - 6"	11	15	86	79	62	54	46	34	22	
NSP 6060-07	6"	13	17.5	100	92	73	63	54	40	26	
NSP 6060-08	6"	15	20	114	106	84	73	62	46	30	
NSP 6060-09	6"	18.5	25	130	120	96	83	71	54	36	
NSP 6060-10	6"	18.5	25	143	133	105	92	78	60	41	
NSP 6060-11	6" - 7"	22	30	158	147	116	102	86	67	45	
NSP 6060-12	6" - 7"	22	30	172	159	126	110	94	72	50	
NSP 6060-13	6" - 7"	26.5	35	188	174	138	120	102	79	55	
NSP 6060-14	6" - 7"	26.5	35	200	186	148	130	110	85	58	
NSP 6060-15	6" - 7"	26.5	35	217	198	156	137	115	90	61	
NSP 6060-16	6" - 7" - 8"	30	40	230	212	169	147	125	95	65	
NSP 6060-17	6" - 7" - 8"	30	40	242	222	178	155	132	100	68	
NSP 6060-18	6" - 7" - 8"	37	50	260	242	193	168	143	110	77	
NSP 6060-19	6" - 7" - 8"	37	50	272	255	203	177	151	117	80	
NSP 6060-20	6" - 7" - 8"	37	50	287	267	212	185	158	122	85	
NSP 6060-21	6" - 7" - 8"	37	50	300	280	222	194	165	128	90	
NSP 6060-22	7" - 8"	45	60	322	302	242	211	180	142	100	
NSP 6060-24	7" - 8"	45	60	350	327	262	229	195	154	107	
NSP 6060-26	7" - 8"	55	75	382	358	287	250	215	168	120	
NSP 6060-28	7" - 8"	55	75	410	384	308	268	230	180	128	
NSP 6060-30	7" - 8"	55	75	440	410	328	285	245	192	135	
NSP 6060-32	7" - 8"	66	90	470	436	350	303	260	204	143	
NSP 6060-34	7" - 8"	66	90	500	461	371	321	275	216	150	
NSP 6060-36	8"	75	100	530	486	392	339	290	228	157	
NSP 6060-38	8"	75	100	560	511	413	357	305	240	165	
NSP 6060-40	8"	75	100	590	536	434	375	320	252	172	

Basma Yüksekliği Total Dynamic Head
Tete Dynamique Totale Cabeza Dinamica total إجمالي ريس حيوية



Max. water temperature : 30°C
Frequency : 50 Hz.
Voltage : 380-415 V
Max. sand content : 50 gr/m3
Outlet connection diameter : 3"-4"
(inside threaded)
Strainer : Stainless steel (AISI 304-430)
Coupling : Stainless steel (AISI 304-420-303)
Pump Shaft :Stainless steel (AISI 304-420)
Impeller : Stainless steel (AISI 304L)
Diffuser : Stainless steel (AISI 304L)
Rotation : CCW
Revolution : 2900 rpm
Shaft diameter : 25 mm

The hydraulic working characteristics have been taken with water at 15° C , at the atmospheric pressure of 1 bar and specific gravity is 1 gr/cm3

Due to continuous improvement in design we reserve the right to amend specifications or data without prior notice



NSP 6060 Serisi Paslanmaz Pompa
NSP 6060 Series Stainless Steel Pumps

